THE SOCIETY OF CHEMICAL INDUSTRY.

INCOME AND EXPENDITURE ACCOUNT FOR YEAR ENDING 31st DECEMBER, 1912.

EXPENDITURE.		INCOME.	
	£ s. d.		£ s. d.
To Journal—Editorial and Sundry expenses—		By Entrance Fees	222 12 0
Editor's Salary	542 16 0	„ Life Composition Fees	141 10 3
Do. Expenses	29 8 8	„ Annual Subscriptions	5090 10 0
Do. Assistant	130 0 0	„ Journal Advertisements	355 18 0
Abstractors	658 4 7	„ „ Sales	778 11 8
Sub-Editor's Salary	150 0 0		
Indexing Journal, &c.	129 8 6	„ Collective Index—Subscriptions	1134 9 8
Foreign Journals	33 1 10	„ Decennial Index—Sales	1 10 0
Sundry Journals	36 8 4	„ Dividends and Interest on Investments—	3 15 0
French and U.S.A. Patents and Specifications	63 5 0		
Insurance of Stock	7 3 0		
	1769 15 11	£ s. d.	
Publishing expenses—		4476 9 2 Metropolitan 3% Consolidated	126 9 4
General	1730 2 3	1000 0 0 New Zealand 3% (1945)	28 5 0
Postage on Copies	762 7 0	1277 4 8 New South Wales 3% (1935)	36 1 8
	2492 9 3	1231 0 10 Consols 2½%	28 19 8
	4262 5 2	600 0 0 Gas Light and Coke Co. 3% Debentures	16 19 0
„ Sectional expenses—		1084 13 4 North British Rly. 3% Consolidated	30 12 10
Birmingham & Midland	20 0 0	1606 0 0 Midland Rly. 2½% Perpetual Preference	30 18 6
Canada	47 6 2	1509 0 0 Great Eastern Rly. 4% Irredeemable	56 16 8
Liverpool	40 4 4	673 0 0 South Eastern Rly. 4½% Preference	28 10 4
London	114 17 9	1000 0 0 Metropolitan Water Board 3% Debentures	28 5 0
Manchester	79 6 10	200 0 0 Nottingham Joint Station 3%	6 13 0
Newcastle-on-Tyne	29 8 11	1250 0 0 Great Western Rly. 5% Guaranteed	58 17 2
New England	40 0 0	800 0 0 Great Northern Rly. 3% Debentures	22 12 0
New York	160 0 0	450 0 0 Nottingham and Grantham Canal 4½% Consolidated	17 6 0
Nottingham	30 8 4	724 8 0 India 3½%	23 17 8
Scotland	19 6 2	834 0 2 India 3%	23 11 8
Sydney	11 1 0	700 0 0 Canadian Stock 3½%	11 10 9
Yorkshire	24 19 4		34 13 5
	616 19 4		618 19 8
„ Annual Meeting expenses	161 1 2		
„ Journey to New York—Mr. Cresswell	150 0 0		
„ Expenses in connection with new Offices, including dilapidations in old Office	138 1 6		
„ Working expenses—			
Medallists' Portraits	20 8 6		
Shaw Medal	3 2 6		
	32 11 0		
Secretary's Salary	300 0 0		
Assistant to Secretary and Editor	225 0 0		
Honorarium to Treasurer's Assistant and for Clerical Assistance	77 10 0		
Rent, Lighting and Cleaning	216 10 5		
Stationery and Binding	113 15 8		
Postages, Bank Charges, Telephone, and Sundry expenses	157 3 7		
	1122 10 8		
„ Excess of Income over Expenditure	778 8 9		
	£7219 6 7		£7219 6 7

London Section.

Meeting held at Burlington House, on Monday, June 2nd, 1913.

DR. W. R. HODGKINSON IN THE CHAIR.

SOME EXPERIMENTS ON THE THEORY OF ELECTROTANNING.

BY DR. E. K. RIDEAL AND U. R. EVANS.

It has for some time been known that the diffusion of tanning substances into hides—a process which is usually rather slow—could be accelerated considerably by causing a current of electricity to flow through the liquid in which the hides are being tanned. Many attempts have been made to utilise this fact in “quicktanning processes.”

The first use of “galvanism for tanning purposes” was made as early as 1849 by Crosse, who placed electrodes of zinc and lead in an ordinary tanpit. Rebu in 1861 made

further experiments, and de Mertass of St. Petersburg in 1874 designed an electric-tanning process, which continued to be used in nearly 600 pits for some years. Processes for electrical tanning were also worked by Nielson (of Norrköping, Sweden) about 1889, and by Worms and Bale in France in 1887. The latter (this J., 1888, p. 443) used the combination of “electricity and motion.”

About 1888 Groth invented his method of electrical tanning; in this process, also, the hides were kept in motion during the electrical treatment; Rideal and Trotter (this J., 1891, p. 425), who examined the process scientifically, found that the acceleration was largely due to the electricity, although partly due to the motion.

But all these processes have been, on the whole, empirical, and very little work has been done to ascertain the exact nature of the forces in action and of the influence of external conditions. Such an investigation, however, must be introductory to an attempt to settle the best conditions under which good leather can be produced both quickly and cheaply. And, until such experiments have been made, it is not possible to condemn electrotanning merely because certain leathers of inferior quality—said to have been “electrically tanned”—have come on to the market.

c. The nature of the electrode material will have a large influence upon the amount of electrodic decomposition of the tanning-matter. This is of the utmost importance, both with a view to avoiding loss of tannin, and also because the products of decomposition are often electrolytes and produce the undesirable effects that have been described.

Experimental.

Two classes of experiments were performed. Firstly, experiments were made in cells divided by porous partitions in order to investigate separately the effect of electrodic decomposition at the two poles, and also to note the influence of the electrodic material on this decomposition. At the same time, the phenomenon of electric endosmose was observed and its amount measured.

noted in each case. The liquid used was generally tannic acid solution in both compartments, but in some cases the outer solution contained only dilute potassium chloride; to test the influence of additions to the tannin liquor, salts were in some experiments added in varying proportion to the tannic acid solution. The conductivity of the solution in both cells was measured before and after the experiment, and in some cases the "acidity" was also determined by the electrometric method of Sand, Wood and Law. (This J., 1911, p. 3, 872.) These numbers gave a clue to the amount of decomposition that was caused at the electrodes, the electrodic material being also varied in different experiments. The volume of liquid in the two compartments was noted after the experiment, and thus the rate of endosmose could be arrived at.

But for the purpose of examining the migration of tannin through a substance, a porous pot was clearly unsuitable. The greater portion of the work was therefore devoted to tracing the progression of tannin under the influence of an electric current, through narrow tubes filled with gelatine jelly. This jelly contained a trace of ferric chloride, and as the tannin penetrated into it, the colouration (due to the so-called "ferric tannate") was produced, and forms a means of observing its advance quantitatively. In most experiments, additions were made to the tannin solution, for the purpose of ascertaining their effect on the migration.

I. "Divided cell experiments."

It is impossible to describe in detail the various experiments made in porous pots. The general method of procedure was as follows: A round porous pot containing one electrode was placed in a glass jar containing the other electrode; measured volumes of liquid were poured into the two compartments, and a known E.M.F. (usually 4 volts) was applied for several hours; the current passing was measured on an ammeter and the temperature, etc., was

The details of two experiments may be given as an example. They are shown for comparison in parallel columns:—

	Exp. A.	Exp. B.
Electrolyte in both compartments	1 per cent. tannic acid	1 per cent. tannic acid
Electrode material	Carbon	Copper
Electrode area	51 sq. in.	51 sq. in.
Temperature	18°	18°
E.M.F. applied	4 volts	4 volts
Current amps.	0.004 sinking to 0.001	0.002 sinking to 0.001
Specific resistance, of solution used, before electrolysis, per cm. cube	7481	10,660
Specific resistance, after experiment, in cathode compartment, per cm. cube	6454	2000
Specific resistance, after experiment, in anode compartment, per cm. cube	567	3258

Similar results were obtained with 4 per cent. tannic acid.

Although no two experiments with porous pots can be exactly comparable, the general conclusions arrived at were clear:—

(1) A copper cathode causes more cathodic decomposition to a tannic acid solution than a carbon cathode; but a copper anode brings about less anodic decomposition than a carbon anode. This is to be expected.

(2) The addition of salts such as potassium sulphate do not interfere seriously with the rate of endosmose at constant E.M.F. But they reduce the amount of tannin matter which takes part in the endosmose. Thus a pure tannin solution moving through a porous pot carries its tannin with it, but, in the presence of potassium sulphate, the solvent "leaves the tannin behind."

(3) The endosmose takes place in the "positive to negative" direction.

II. "Jelly Tube" Experiments.

A jelly consisting of 5 per cent. Nelson No. 2 gelatine, dissolved in water containing 0.1 per cent. of ferric chloride (a strength which produces a good colouration with tannin) was introduced into a series of glass tubes (Fig. 1).

These glass tubes are 10 cms. long and of 0.2 cms. internal bore; they contain a length of about 3.6 cms. of the jelly situate at about 2 cms. from the top end. The bottom of each tube was placed in a small test-tube (0.6 cms. diam.) and was filled up to the gelatine with a 4 per cent. solution of tannic acid. The space above the gelatine (and also the test-tubes) was similarly filled with the same solution T. By means of copper wires C, C' connected to mercury troughs any number of these tubes could be connected to sources of current at different E.M.F.s. The wires at the bottom formed the positive electrodes, and those above the negative electrodes.

A series of such tubes were arranged vertically, attached to a thin board behind. By means of a strip of squared paper placed as a scale behind the row of gelatine containing tubes, the advance of the colouration produced by the interaction of the migrating tannin with the ferric chloride solution could easily be followed. Readings of this advance from both ends were taken over a period of about 30 hours. In some tubes pure tannic acid solution was used, in others small quantities of substances, whose influence we were anxious to investigate, were added to the solution at both ends of the tubes. The E.M.F. applied was varied in the case of different tubes; in the second series of experiments, a number of blank experiments were made in which no E.M.F. was applied, with a view to obtaining separately the transfer due to natural diffusion. In this second series of experiments the concentration of the substance added was varied, while in the third the strength of tannic acid solution employed is also changed. The "age" of the jelly also differs in the three series of experiments, i.e., the gelatine has been permeated for a different time with the ferric chloride.

FIG. 1.

In every case the tannin was observed to enter the tube in *both* directions. The most important migration is in the negative to positive direction, and is apparently due to *ionic or cataphoretic* movement. The less rapid entry of the tannin—in the positive to negative sense—is presumably due to the *endosmose* observed in the porous pot experiments; this view is confirmed by the form of the boundary of advance, which supports the view that the solvent as a whole is penetrating the jelly, and taking advantage of any flaws occurring therein. (Fig. 2.) The advance in the opposite direction shows a smooth front.

FIG. 2.

Curves were plotted to show the gradual movement of the tannin into the jelly in both directions. A few of these curves are shown as examples. The abscissae represent the time in hours, the ordinates the position on the tubes.

A	New Jelly	No added substance
B	" "	75 H ₂ SO ₄
C	" "	75 Boric
D	" "	75 Formic
E	Older Jelly	No addition
F	" "	Formic acid, various strengths

A few of the experiments made in the first series had to be repeated, notably those in which potash, sodium acetate and phenol respectively were added to the tannin solution, since it became evident that the colouration the advance of which had been followed was not due to the formation of ferric tannate, but to ferric hydroxide, acetate and phenate respectively. A few other apparently anomalous results obtained in the first series were subsequently explained. It was observed that the older the jelly, the slower was the diffusion; this was due to the hardening action of the ferric salt.

Discussing the form of the "negative to positive" movement (ionic or cataphoretic) as shown by the downward curves, we see that

(1) The greater the potential gradient, the quicker the transference, in general;

(2) On the whole, additions to the tannic acid, in concentrations between N and N/75 have very little effect upon the rate of migration of tannin at constant voltage. In one or two cases, e.g., in presence of N/75 formic acid

FIG. 3.

at 4 volts in old jelly, the addition seems to cause a slight acceleration to the transfer; but this is not enough to compensate for the disadvantages caused by such additions.

(3) The curves tend to approximate to a certain typical form (Fig. 3) in which the gradient falls off at first with the time, finally becoming constant. This is due to two causes:—

a. Natural diffusion at first aids the migration.

β. There is a tendency for polarization to occur. Thus this "typical form" of curve becomes all the more marked when strong electrolytes are substituted for weak ones.

The upward curves show the "positive to negative" (endosmotic) movement.

(1) This is much less rapid than the "negative to positive" migration, being comparable to the rate of natural diffusion.

(2) It is less dependent on the applied E.M.F.

(3) In the presence of comparatively large quantities of such electrolytes as potassium sulphate, sulphuric acid and formic acid, at the lower voltages, tannin does not seem to take part in the endosmosis.

Strong tannic acid solutions show a more rapid diffusion (in both directions) than weak ones.

The main conclusions to be drawn from the experiments are as follows:—

(1) Ionic or cataphoretic migration is the main agency involved in the transference of tannin through gelatinous substances and *not* endosmosis (which causes a less rapid transfer in the opposite direction).

(2) The addition of acids and metallic salts decrease the transfer per kilowatt hour because

A. They cause conduction of current in a way which does not involve the transfer of tannin.

B. They cause polarization at an unduly early stage, and so reduce the effective E.M.F.

C. They reduce or inhibit the tannin carried by endosmosis, especially at high concentrations.

D. Some have a specific slowing action upon the ionic migration.

Incidentally in their presence, when attackable anodes (e.g., of copper) are used, these suffer an undue electrochemical attack.

(3) If we assume that the jelly offers an approximate analogy to the structure of a hide substance it is clear that, in the absence of acids and conducting salts, a very small expenditure of electrical energy can cause a great increase in the rapidity of the transference of tannin through a hide—which is probably the slowest part of the tanning process.

(4) The electrode material has an important influence on the success of an electrotanning process, because if an unsuitable material be used, an undue decomposition will occur at the electrodes, and so (A) tanning matter will be destroyed (B) acids will be produced, which will produce the undesirable effects outlined above.

For this reason it is best to use *cathodes of carbon and anodes of copper*, and to keep the bath sterile; in this way, an undue wastage of energy and tannin is avoided. But for some purposes the tanner insists upon a bath containing relatively large amounts of organic acids (which may be necessary for the reaction between the tannin matter with the hide substance, after it has penetrated into the latter); in such a case, it would be extravagant to use copper anodes, which would be quickly attacked in the highly conductive solutions, and carbon anodes also may be employed. But so far as possible, every endeavour should be made to keep the total conductivity of the tan bath as low as possible.

It must, of course, be remembered that the transference of tannin into the hide substance is not the only part of the tanning process, although it is doubtless the slowest and most unsatisfactory. But, after the tanning substances have entered the hide, there is doubtless some sort of chemical reaction between them and the hide material, and it is for the tanning chemist to settle the conditions most favourable to this combination. Possibly these may not be the conditions which are most suitable for the economical electrochemical transference of the tannin through the hide; but if the electrochemist clearly states what conditions are most favourable to his part of the process, and the tanning chemist will tell us within what limits the chemical interaction will proceed satisfactorily, doubtless some compromise could be arrived at, which would result in a successful tanning process. (For instance, the electro-

chemist will desire as low a bath acidity as possible; the tanning chemist may—for some purposes—prefer a high one; but there may be some intermediate strength which would suit both.)

It may be suggested as a possibility that endosmosis—which involves the bodily transfer of the solution through the hide—may prove a destructive form of introduction of tanning matter into the latter; for, as was observed in the case of the jelly-tube experiments, advantage will be taken of any points of weakness in choosing its path, and this weakness will, therefore, probably be increased. If this is so, it may well be advantageous to avoid endosmosis as much as possible, and it is satisfactory to find that it is not the main agency of transport involved in electrotanning. The fact that the entry of the tannin is dissimilar in the two directions, as well as the fact that hides are themselves dissimilar on the two sides, must be taken into account in the settlement of the relative times during which the current should pass in the two directions.

Within the last few months, O. J. Williams has published a research upon the subject of electrotanning. The figures which he quotes have little bearing on the matter since he assumes electric endosmosis to be the only agency at work. But he is right in regarding the loss of tannin matter by electrolytic decomposition as one of the main problems to be dealt with in an electrotanning process. He proposes the employment of an alternating current, which in his view should cause no decomposition, and yet allow the endosmosis to proceed. But it is difficult to see how—unless a valvelike structure be assumed to exist in the hide—an alternating current of sufficiently high frequency to prevent electrolytic decomposition could, *per se*, produce any endosmotic movement of tanning liquor through the hide. The best method of preventing the electrolytic destruction of tannin is a careful choice of the material and form of the electrodes employed, and a scientific control of the composition of the bath.

DISCUSSION.

Mr. W. COLEBROOK REYNOLDS asked whether the movement of the iron of the indicator towards the cathode had been taken into account. If not, the apparent movement of the tannic acid would be partly illusory.

Dr. PARKER said that 17 or 18 years ago he had gone over to Sweden to investigate the process of tanning assisted by the electric current, and he was very much impressed with a demonstration of it in a large tannery at Wenersborg, Sweden, where they were tanning some 400 to 500 hides each week. The tanning process was apparently accelerated and the penetration of the tannin into the fibres of the hide was apparently assisted by the electrical current. During the past 18 years, however, great changes have taken place in the processes of leather manufacture. Years ago sole leather required twelve months to be properly tanned. Nowadays that period had been reduced to as many weeks, and good leather could even be tanned in as short a time as twelve days. Some years ago, in Vienna, a tanner, in order to win a bet, undertook to tan some leather and have it made into a pair of boots, all within forty-eight hours. An ox was slaughtered in the city abattoir at six o'clock in the morning. The hide was immediately conveyed to the tannery, tanned, dried and finished, and within forty-eight hours after the tanner appeared in the café wearing the finished boots. In this instance there was no record as to the quality of the leather. If leather could be made and turned into a pair of boots in forty-eight hours, any claim made on behalf of electrical acceleration fell rather flat. For some years he had initiated and carried out in his laboratory various tests connected with electrical tanning, and he had failed to produce a process which offered considerable commercial advantages. In other words, he had never been able to tan on a practical scale quicker or better by the aid of electrical current than he had been able to tan by various mechanical means with chemical assistance, added to which the latter were cheaper. Practical tanners did not worry so much about the quality of the leather as the cost of production. What was wanted to-day was that from a given weight of hide substance a given weight of finished leather should be produced at a certain cost per lb., and they were loath to

adopt any process which, if it gave the same results, would add a fraction of a penny to the cost of production, even if the leathers produced by this means were slightly better. Thanks to Procter's work and to the work of other of their members, they had advanced very considerably in their knowledge of the chemistry both of the raw materials and of the process of leather manufacture during the last eighteen years. They now understood more fully the action of the acids and alkalis upon hides. They understood how to accelerate the penetration of the tan through the hide substance—so much so that really good leather could be turned out in the tanyard in fourteen days—therefore, the advantage of speed claimed by those who advocated the use of electricity was not now so important a matter as it was eighteen years ago. The authors, while they had not dealt with the subject from a practical standpoint, had certainly given some theoretical points for consideration, and he was thinking how those theories which they had propounded might be carried out on a practical scale. If they would come to the Leathersellers' Technical College he would provide 20 or 40 hides, or as many as they wanted, and they could fit up their apparatus, and if they got any more weight than he could get, or if they could produce leather more quickly than he could, or better leather, and, last but not least, cheaper, they would have him for a convert at once. He would be prepared to take corresponding hides to them, using the same liquors but using drums or paddles, as the case might be. All that took place in the process of leather manufacture was not yet understood, but much information had been gained by the work of Procter and others in connection with colloidal chemistry, and the researches which had been carried out dealing with the effect of swelling and tanning of hides by means of acids and various salts in the liquors. He did not desire to convey the impression that he looked upon the use of electricity in connection with tanning to be hopeless, but he had tried it with weak currents, alternating and direct, and had tried it all ways, but he had now given it up. Another point, and one on which he bowed to the authors of the paper, was that he was not sure whether his process would conserve the tanning acid as much as they claimed to do. They did not give figures, but they pointed out that there was not the same decomposition of tannic acid by their process as by the ordinary processes, but he had been taught to believe that the decomposition of tannic acid, or rather the hydrolysis of tannin, produced beneficial acids, and the fermentation of the glucoses produced acids. Unless the early liquors were kept acid enough, that is to say, if one did not have a proper fermentation going on in the tanyard which could produce sufficient lactic, acetic and propionic acids, they would not get sufficient swelling. If the leather was not sufficiently swelled in the early processes of tanning they would neither get sufficient weight into the leather, nor would the leather be thick and solid, as it must be to possess good wearing qualities; and unless these acids were present there would not be the deposition of semi-soluble substances inside the hide. It had been claimed as an advantage that the electrical process kept the liquors sterile. He would be rather sorry for the tanner whose liquors were sterile, because, unless he had misunderstood the authors, he was afraid that if the liquors were kept sterile and there was no acidity present, the leather would be flat, tinny and brittle, and practically would not produce a commercial product.

Dr. E. RIDEAL, in reply, said it had been mentioned that the decomposition at the electrode varied, and it seemed to have been gathered from the paper that the rate of movement in the liquid itself varied with the nature of the electrodes used. That was not what they had intended to convey. What they had intended to say was, that, supposing they had a soluble anode, the decomposition was less than if they had an insoluble anode, because, instead of oxygen being liberated and attacking the tanning substance, the electrode itself went into solution and the tannic acid was left unchanged. The actual actions in the body of the electrolyte itself, the velocity of the tanning, and the rate of diffusion was not influenced very much by the electrodes. With reference to an iron chloride indicator, certainly iron travelled a certain rate with the current, but there was always sufficient iron to give a colouration; and the natural diffusion was also a check on

it, because the same error ran through the whole of the results, which were strictly comparable.

With reference to the unsuccessful nature of the past experiments on practical electric tanning on a large scale, he thought a great deal could be attributed to the high conductivity of the bath itself. When they worked on a large scale they got little traces or possibly even large amounts of salts of lime, etc., which got in from the previous treatment undergone by the hides before they were ready for the tan bath; that affected the conductivity and thus permitted a great deal of current to go through which was not aiding the tanning, which in fact acted rather detrimentally to the tannic acid; for the greater current caused greater action at the electrodes themselves, which action decomposed the tannic acid and involved a great waste of tannic acid. If, however, the bath had to be acid, carbon electrodes should be used instead of copper ones. They did not intend to suggest that the liquor was kept sterile by means of electric current itself, but they suggested it should be kept sterile by adding some suitable steriliser, provided that the right quantity of acid which was demanded was kept there. Apparently in practice the baths might get very powerfully acid and the liquor become inefficient, or they might cease to be sufficiently acid. There ought to be some degree of acidity which is the correct acidity for hide treatment. Procter was not quite certain which was the correct acidity, but that should be experimentally arrived at.

THE JOINT ACTIONS OF CATALYTIC AGENTS.

DEHYDRATION OF ETHYL ALCOHOL AND ETHYL ETHER.

BY GENERAL W. IPATIEW.

In a communication by Sprent (this J., 1913, 32, 171—173) on a technical process for the preparation of ethane is described a method of hydrogenisation of ethylene by hydrogen and reduced nickel under pressure and at a high temperature. The ethylene employed was obtained by passing the vapours of ethyl alcohol over alumina as catalyst.

In this communication no reference was made to the fact that the use of alumina was first made by myself (Ber., 1903, 36, 2016) in a series of experiments in which it was shown that by means of this agent at temperatures of 350°—360° C. theoretically quantitative yields of ethylenic hydrocarbons could be obtained from the respective aliphatic as well as cyclic alcohols (Ber., 1904, 37, 2990). Shortly afterwards I showed that the alumina required special preparation, otherwise it was not active. For efficient action it must be precipitated and then gently ignited—only so much that it will still dissolve readily in hydrochloric acid or caustic soda.

I showed that in the presence of alumina ether was first formed, from the alcohol, which then split up into water and ethylene, and this first phase of the catalytic action was a reversible one:—

At the same time I showed that methyl ether could be prepared by heating methyl alcohol and alumina in my high pressure apparatus. Although these results were published in German in the *Berichte*, publications have appeared from Senderens and Mailhe several years later, since 1908, in which they state that alumina is the most convenient catalytic agent and that this alumina must be heated to redness, and that this ignited oxide converts alcohols into ethers or ethylenic hydrocarbons, depending on the temperature to be subsequently employed.

As Senderens and Mailhe do not refer to my work in their publications, although attention (Ber. 1910, 43, 3383) was drawn in the *Berlin Berichte* to this lapse, Sprent naturally, but in error, ascribes the priority of employment