LVI. Experiments on the electricity of high-pressure steam

H.L. Pattinson Esq. F.G.S.

To cite this article: H.L. Pattinson Esq. F.G.S. (1840) LVI. Experiments on the electricity of high-pressure steam, Philosophical Magazine Series 3, 17:111, 375-379, DOI: [10.1080/14786444008650195](https://doi.org/10.1080/14786444008650195)

To link to this article: <http://dx.doi.org/10.1080/14786444008650195>

Published online: 01 Jun 2009.

Submit your article to this journal [↗](#)

Article views: 2

View related articles [↗](#)

LVI. *Experiments on the Electricity of High-Pressure Steam.*
By H. L. PATTINSON, Esq., F.G.S.

To the Editors of the Philosophical Magazine and Journal.
GENTLEMEN,

A VERY singular phænomenon, viz. the production of electricity by two steam-boilers, has been observed in this neighbourhood within the last few weeks, the particulars of which I have the pleasure of transmitting to you for publication in your valuable *Journal*. The boilers in question are situated at Cramlington Colliery, eight miles north-east of Newcastle, where they supply steam to a high-pressure engine of 28-horse power, employed on the waggon-way to haul full and empty waggons to the top of two inclined planes, leading to the Colliery on the one hand, and to the river Tyne on the other. The boilers are cylindrical, with circular ends, each twenty-one feet long, and five feet diameter. They are supplied with water from an adjacent pond by iron feed-pipes, four inches diameter, and the steam they produce is conveyed to the working cylinder by other iron pipes, six inches diameter, which pipes form also a direct metallic communication between the tops of the boilers. By means of appropriate valves the steam is supplied to the cylinder from one or other boiler at pleasure. A pipe, two inches diameter, leads from the bottom of one boiler on the outside of the brick-work to the ash-pit, through which the sediment deposited by the water is occasionally blown from one of Scott's patent collecting cones, and a similar pipe is attached to the other boiler. The boilers are set in brick-work in the usual way, the fires below, with flues reaching all round, and passing into the chimney also in the usual manner. The flues are covered with large flat bricks, and in the space between the boilers the two flues are necessarily separated by a brick wall. The safety-valves are attached to the boilers by flange joints; and between the flanges, to render them steam-tight, is placed a ring of plaited hemp covered with a cement of litharge, sand and linseed oil, mixed up together, and when applied of the consistence of glaziers' putty. This cement, as it soon becomes hard, is used about the engine for steam joints which occasionally fail; but all the joints of the pipes are made of iron borings and

a much smaller scale, and about which there are as yet doubts whether it is to be referred to mere evaporation, as Harris says, or to chemical action, according to others. This point it neither settles nor illustrates; but it gives us the evolution of electricity during the conversion of water into vapour, upon an enormous scale, and therefore brings us much nearer to the electric phænomena of volcanos, water-spouts and thunder-storms, than before.—M. F.

sal-ammoniac, as ordinarily employed by engine-wrights. The steam is worked at a pressure of thirty-five pounds per inch.

The joint between the top of one of the boilers and the seat of its safety-valve had given way, and steam was issuing forcibly through this aperture, when on Tuesday, September 29th last, the engine-man, William Patterson, while standing with this current of steam blowing upon his legs, took hold of the weight attached to the lever of the safety-valve, to try the strength of the steam, when he felt a peculiar pricking sensation in the ends of his fingers, but as the steam prevented him from seeing distinctly, he thought he had merely struck his fingers rather suddenly against the weight. On Friday, October 2nd, on taking hold of the lever, he again felt a sensation in his fingers of the same kind as before; and on Saturday, the 3rd, on touching the weight, this sensation was stronger, and more distinct; so much so, as to arrest his attention and lead him to mention it to some other workmen employed about the engine, who all handled the weight, and convinced themselves that there was something about it very unusual. During the time they were thus employed, Patterson applied his finger gently to the lever, and perceived a spark. This was repeated by the whole party, and they soon found that sparks could be obtained from any part of the end of the boiler, as far as the valve upon the steam-pipe connecting the two boilers, and also from the pipe through which the sediment is blown, as already described. They observed further, that while standing in the volume of steam issuing from the joint, and touching the boiler, these sparks were always much stronger than when the boiler was touched by a person not in the current of steam. In one or two cases, according to their account, when the current of steam issuing from the joint was very strong, the person exposed to it being probably partially insulated by standing upon the dry and warm brick-work surrounding the boiler, gave strong sparks to others out of the current on bringing his hands to theirs; and once or twice they felt, under these circumstances, something like a slight electrical shock. It may be observed, that at this time the weather was exceedingly fine and dry. It was not long before the engineer of the colliery, Mr. Marshall, became acquainted with these circumstances, and his first feeling was to apprehend that the boiler was in danger of exploding, for, as he said, "when there was fire on the outside of the boiler, he did not know what there might be within." He accordingly sent to Messrs. Hawks's, of Gateshead, who built the boiler, for a person to examine it, and Mr. Golightly, their manager in that department, went out on Wednesday, the 7th inst., for that purpose. He gave his opinion as to the safety of the boiler, and

returned much surprised at the phenomena it presented. The singular circumstance of a steam-boiler yielding electrical sparks, and giving shocks, now began to be noised abroad; and my friend, Mr. Henry Smith, of Newcastle, who had heard the account both from Mr. Golightly and Mr. Marshall, wrote me a note acquainting me with the matter, and desiring me to go with him to see it, which I did on the 11th inst., and again on the following day, having with us the second time proper electrical apparatus. On our first visit, the boilers being unplugged and empty, we merely satisfied ourselves as to all the particulars of their setting, etc., already detailed. Next day, on our arrival, we found the engine at work, the steam up to a pressure of thirty-five pounds an inch, and blowing off strongly at the joint in the boiler. The day was a little damp, but yet not unfavourable, and we were informed on alighting that the indications of electricity were very faint and weak; however, we proceeded to our examination, of which the following is the result.

1. On touching the boiler with the blunt point of a penknife anywhere about the circular end, the weight or the safety-valve itself, with the steam strongly blowing out of the joint, but with no part of the person exposed to the volume of steam, no spark could be perceived whatever.

2. On immersing one hand in the current of steam, and touching the parts of the boiler already named with the point of a penknife held in the other, a very minute but distinct spark was perceived, and this occurred equally on all parts of the boiler, or safety-valve, within reach.

3. By standing in the current of steam, so as to allow it to blow forcibly upon the person, the spark became larger; it was then one-eighth of an inch long.

4. On holding a large shovel in the current of steam with one hand, and touching the boiler with a penknife held in the other, a spark was obtained three-eighths of an inch long.

5. The cap of a gold-leaf electrometer, the bottom of which was held in the hand, was applied to the weight, the body of the operator being entirely out of the current of steam; and no divergence was produced whatever.

6. The electrometer held in the hand had its cap applied to the weight, the other hand of the operator being immersed in the current of steam: strong divergence was immediately produced.

From this it was evident that the electricity proceeded from the steam; but as the boiler-house was damp, so that insulation by glass could not well be preserved, a copper wire was attached to the shovel already mentioned, the end of which wire terminated in the engine-house, some yards distant from the

boiler-house, where was placed a table. The shovel was held by Mr. Smith in the current of steam, with its edge about an inch and a half from the aperture through which the steam issued, and the wire leading away from the shovel was insulated by being attached to sticks of sealing-wax held by assistants. Mr. Smith stood on an insulating stool.

7. On touching a pith-ball electrometer, the threads of which were five inches long, with the insulated wire leading from the shovel held as mentioned, the balls diverged four inches with positive electricity.

8. The wire was attached to an insulated tin conductor, when it yielded sparks half an inch in length.

9. A pointed wire attached to this conductor exhibited the brush of light a quarter of an inch long, which always attends the escape of positive electricity from a point into the air.

10. A small jar was now charged so strongly as to give a rather disagreeable shock. By this time a large crowd of men, women and boys from the "Pit Row," or pitmen's residences near the colliery, attracted by the novelty and singularity of the circumstances, had gathered about us, filling the engine-house and looking on with great curiosity and interest. A circle of sixteen of these men and women was formed, and they received together, much to their surprise and merriment, a powerful shock from the charged jar. This was several times repeated, the numbers receiving the shock varying each time from twelve to twenty.

11. A stout card was perforated by a discharge of the jar; and cotton wrapped round the end of a copper wire and dipped in pounded resin, readily set on fire.

12. When the edge of the shovel was made to approach the aperture through which the steam issued as near as three-quarters of an inch, very vivid and bright sparks of that length passed continually between it and the boiler.

13. The second boiler did not discharge steam through any fissure, but on lifting its valve by the hand it blew off in a strong current. When the shovel was held in one hand in this current of steam issuing from the safety-valve, and the boiler was touched with a penknife held in the other, a spark passed exactly, as under the same circumstances in the boiler subjected to the above experiments.

From this it would appear that the steam of both boilers was in the same electrical condition.

During the whole of these experiments the engine was doing its work as usual, occasionally going and occasionally standing; but no difference was observed in the electricity given off by the steam.

I have been most careful to supply an exact account of the

facts of this extraordinary, and, as far as I know, unprecedented case, but I do not offer any theory to account for the phænomena. It is hardly possible to suppose that there is any local peculiarity about these boilers, or the place where they are situated, to occasion the highly electrical condition of the steam produced in them; and yet it is as difficult to suppose the fact of high-pressure-steam being electrical, a general one; for if it were so, it could hardly, up to this time, have escaped observation. The conditions, therefore, under which steam becomes electrical require to be investigated, and it is not unlikely that the investigation may lead to important results.

I am, Gentlemen,

Your obedient Servant,

Bentham-Grove, Gateshead,
October 19, 1840.

H. L. PATTINSON.

LVII. *Note on Elimination.* By J. J. SYLVESTER, F.R.S.,
Professor of Natural Philosophy in University College, London.*

THE object of this brief note is to generalize Theorem 2. in my paper on Elimination which appeared in the last December Number of this Magazine. The Theorem so generalized presents a symmetry which before was wanting. Here, as in so many other instances, the whole occupies in the memory a *less* space than the part.

To avoid the ill-looking and slippery negative symbols, I warn my reader that I now use two rows of quantities written one over the other, to denote the product of the terms resulting from *taking away* each quantity in the under from each in the upper row.

Let $h_1 \ h_2 \dots h_n$ be the roots of one equation of co-existence.

$k_1 \ k_2 \dots k_m$ of the other.

And let the prime derivative of the degree r be required. Take *any* two integer numbers p and q , such that $p + q = r$. The derivative in question may be written,

$$\Sigma \left(\frac{(x-h_1 \cdot x-h_2 \dots x-h_p)}{(x-k_1 \cdot x-k_2 \dots x-k_q)} \frac{(h_1 \ h_2 \dots h_p)}{(k_1 \ k_2 \dots k_q)} \times \frac{(h_{p+1} \ h_{p+2} \dots h_n)}{(k_{q+1} \ k_{q+2} \dots k_m)} \right)$$

$$\frac{(h_1 \ h_2 \dots h_p)}{(h_{p+1} \ h_{p+2} \dots h_n)} \times \frac{(k_1 \ k_2 \dots k_q)}{(k_{q+1} \ k_{q+2} \dots k_m)}$$

N.B. Whatever p and q be taken, so long only as $p + q$

* Communicated by the Author.