Concerning Ice

High Pressure Experiments on Water Carried on by Dr. Bridgman of Harvard

SUMMER is at hand, and anything cooling is of interest. In this connection it may be asked how the reader would like to have a choice of five kinds of ice? The possibility of such a choice is not far away, according to recent discoveries in experimental science. And together with the new facts about ice, other amazing discoveries have been made. Among them is the fact that steel can be stretched more than its own diameter before breaking; that ordinarily soft and flexible substances are found to increase their stiffness under pressure; that water can be decreased in volume almost at will without removing any of the contents.

The experiments on high pressure outlined, with others, are being conducted by Dr. P. W. Bridgman of the Jefferson Physical Laboratory at Harvard University. In these experiments pressures were carried up to ten times the firing pressure of smokeless powder in large guns. A pressure of 300,000 pounds to the square inch was obtained. To visualize this figure in another way, it represents the pressure that would be exerted by a body of water 120 miles deep. It would take a column of solid rock some fifty miles high to exert such a pressure on its base.

Under the influence of such pressure as this, substances ordinarily soft and pliable show remarkable stiffness. Paraffin wax at 300,000 pounds is more rigid than soft steel. A piece of the steel, bedded in the paraffin when the latter substance is made to flow under this pressure, will go with the stream and become bent and distorted with the wax, now harder than itself. Soft India rubber, it was found, at these pressures becomes so brittle that it will crack like glass, and so hard that irregularities in its surface can be impressed upon soft steel.

The first subject chosen for the measurement of compressibility was water, and in this article attention will be centered on it. Water is generally considered almost incompressible, but under a pressure of 180,000 pounds to the square inch the astonishing decrease in

Cross-section of the cylinder shown in the upper left view of the group below

volume of 20 per cent is produced. This phenomenon occurs without the slightest decrease in the actual mass of water present. But certain irregularities in the water induced the experimenter to believe that he was measuring sometimes liquid water and sometimes ice.

Ice usually weighs less than water; that is why it floats. But under the pressures applied by Dr. Bridgman there are four different kinds of ice which are heavier than water. Under ordinary circumstances, when water freezes to ice there is an increase of vol-

ume; but under these high pressures the freezing is accompanied by a decrease in volume with a corresponding decrease in pressure, while when the ice melts again to water the volume increases and the pressure rises.

An interesting by-product of the experiments was the designing of a packing which would keep absolutely tight the vessel in which the pressures were to be produced, preventing the liquid from leaking out. There was absolutely no difficulty in this regard after a while, for it was discovered that with the right packing, the greater the pressure the less can the liquid leak.

The ordinary screw-tightened packing is certain to leak, because the pressure so exerted cannot possibly equal the pressure of the experiment which exists in the fluid. A packing so compressed will leak as soon as the pressure of the screw is exceeded by that of the water which the packing holds back. But with the simple idea of a packing that tightens itself by the pressure of the vessel, the only limit to the compression that can be reached is set by the strength of the vessel itself. The problem was faced with misgivings, for the pressures it was proposed to exert were unheard of with ordinary vessels. The second part of the preliminary work, therefore, consisted in finding what pressures a steel vessel would support, steel having been selected as the best material of which to make the container. These experiments were not without danger, for in the event of the vessel's failure there would be an explosion that might be serious.

In all the experiments the pressures were produced by pushing a piston, by means of a hydraulic press, into the cylinder containing the liquid. Two very interesting problems in relative strength were introduced, for the two parts of the apparatus were subjected to different strain. In the piston the strain is one of compression, while in the cylinder it is one of bursting, or

(Continued on page 519)

Outside of a cylinder stretched from .5 to 1.375 inch before rupture. - A cross-section of this cylinder is shown in the upper illustration

One of the halves of a steel cylinder split by 450,000 pounds internal pressure

Apparatus used in the high-pressure experiments

Handy rack for radiators before or after repair

The Armed and Armored Limousine of a Chinese Governor

AN automobile fortress that is at the same time one of the most luxurious limousines ever built has just been delivered to his excellency Tsan Tso-Lin, the Governor General of Manchuria. The machine, which in appearance and fact is the last word in luxurious transportation, is also an armored car, bullet and bomb proof and prepared either for offense or defense. It is likely to be a model for similar cars for other nervous rulers now that news of its construction is no longer a secret.

When General Tsan appears in the streets of Mukden or other Manchurian cities he will apparently be traveling simply in an amazingly luxurious limousine. The car has disk wheels, special headlights and is of a deep tan color with mahogany top and trimmings. Inside, the fittings and finish are fully worthy of the official position of its owner. To conform to the colors of Chinese royalty the cushions, seat backs and arms are upholstered in purple and gold mohair. The panels lining the body are entirely of inlaid mahogany, and there are vanity cases of the same material on either side. The fittings and all metal used in the tonneau are of silver and cloisonné. Perhaps the most beautiful part of the interior decoration is the flowered marquetry inlaid in the door panels. In each of these panels more than 20 different kinds of wood are used.

This is the car as it appears to the eye. But if an attempt is made by some assassin to end General Tsan's

(Continued on page 520)

The limousine that can be instantly converted into a traveling fort

cause so necessary—is the air hose. You may run over this, where it stretches its snaky length across the garage entrance as it extends from the pump to the wheel of a waiting car, dozens of times without damage to your own tires or to the hose; you may then run over it once more and damage either or both. You may also trip over it with more or less disastrous results. The garage in which our pictures are taken overcomes all this by putting the air hose overhead, slinging it over a reel that is placed at a strategic point to give it the proper degree of easy mobility. The utility of both these simple but seldom-thought-of devices is evident at a glance, and the second one might even be installed with profit in the single-car private garage, where some other agent than elbow grease is employed in the pumping job.

A Tripod-less Motion Picture Camera for Aerial Work

THE main thing in making motion pictures is to keep turning the crank at an even speed, two turns per second, no matter what happens. Under normal conditions this is not so difficult to do, but when making aerial views with a motion picture camera the most intrepid cameraman is apt to become irregular on his turns with poor films as a result. What is more, the vibration of the airplane engine is transmitted through the tripod to the camera, with further complications.

Realizing these difficulties in the way of aerial motion pictures, Frank Morris of New York has developed an electrically-driven motion picture camera which is shown in the accompanying illustration. The camera shown here appears to be a French Débré, somewhat modified and equipped with a 1/20-horsepower electric motor operating on an eight-volt storage battery. An extra large direct-view finder is mounted on top of the camera, while a pair of handles is used to hold the camera steady. Furthermore, the cameraman wears a pneumatic chest pad against which he holds the camera, so as to make for greater steadiness while absorbing all vibration.

Aside from aerial photography the electrically-driven camera may be used in filming automobile and horse races, athletics, sports, and so on, where the lens must be trained on a rapidly moving object.

An overhead reel for the garage air-hose

Using X-Rays to Determine Proper Fit of Shoes

CERTAIN manufacturers endeavor to prove the merits of their shoes by showing photographs of the bones of the feet first in the ordinary shoe and then in their specially-shaped shoe. Of course, such pictures are interesting, but they fail to leave a permanent impression in most instances; so that when any of us happen in the shoe store for a new pair of shoes, we are guided by the appearance of the shoes rather than by orthopedic considerations. Hence, after all said advertising and warnings, we continue to buy shoes that jam and twist and deform the small bones of the feet.

Some time ago X-ray machines of a special design were introduced in shoe stores both here and abroad for the purpose of determining when shoes fit and when they do not. One of these X-ray machines appears in the accompanying illustration. The shoe customer, wearing a given pair of shoes, stands on the platform of the apparatus and by looking through the long hood at the top, views the X-ray image of the shoes and feet. The positions of the various bones can be instantly seen. What is more, only a low power X-ray tube is used, and ample lead screening is employed to protect the customer and the shoe salesman from injury.

It is interesting to note the ever-widening field of X-rays. Today X-rays are being used in numerous industries for inspecting materials and goods to detect hidden flaws and to discover causes of trouble in certain apparatus without complete dismantling. For customs inspection purposes X-rays have a very definite application, which, as yet, has been hardly touched.

Shoe customer studying the fit of a pair of shoes by means of a special X-ray apparatus

Electrically-driven motion picture camera that does away with the usual cumbersome tripod

tempt to enforce this. In many more the nuisance has got to such a point that it has been necessary to institute recognized public parking plots. Those who attend the ball games in New York know perhaps the most extensive of these—we have seen half a mile of the Speedway curb banked solid with cars, backed in as close together as the prohibition against two bodies occupying simultaneously the same space would permit. But in the more crowded sections of New York and other cities there are no extensive curb areas available for parking in this fashion. It is therefore necessary to utilize to the utmost whatever of open space there may be at hand. Our final picture shows how this is done in one instance. In a wide and little used street chalk lines are carefully laid down, so that two double ranks of cars may be parked without interfering with the entrance or exit lines. This is economy of space carried to the last degree.

Racing with Model Yachts

(Continued from page 511)

In the Regatta races boats sail according to class; but in the point races class is not taken into account. Prizes are given to the winners for the season.

The Prospect Park Model Yacht Club at present is made up of former members of the Brooklyn Model Yacht Club and the Yankee Model Yacht Club, who agreed to join into one organization for at least six months. This plan has worked out very well and will no doubt result in a permanent organization probably under the present name.

The enthusiasm of the yacht races is not confined to the older members of the club, the younger members being fully as expert yachtsmen. On the large lake at Prospect Park, the triangular course is five-eighths of a mile, and on the windward and leeward course the yachts sail a half-mile by covering their course twice. Some excellent scores have been made over this course. Thus the schooner "Fairwind" covered the triangular course in 12 minutes 55 seconds. The "Hilma" covered the same course in elapsed time 13 minutes, or 15 minutes 17 seconds by corrected time.

Quite a lively sight is the start of one of these races when more than half-a-dozen of the yachts are jockeying for the best position to cross the line, while on the shore opposite the stake stands the timer with his watch and recording tablets, keeping accurate account of the time each one crosses.

Collisions happen frequently, but they are not usually serious, the damage being easily remedied. In a heavy wind the yachts heel over to an alarming degree, but thanks to their deep lead keels, always right themselves. So great is the speed of the large yachts that the owners frequently have to put in some hard rowing to keep up with the diminutive but fast-moving craft.

Concerning Ice

(Continued from page 512)

tension. The problem of the strength of the piston did not prove of difficulty, for it was found that the compression supported by a piece of glass-hard steel held rigidly is surprisingly large. Several grades of steel were found which would support a compression of 600,000 pounds and one grade stood up under as much as 750,000 pounds per square inch.

No theory of the strength of a cylinder was of much value for very high pressures. It is of no use to make indefinitely thick walls, nor indeed to make them more than a certain thickness; for the inside layers support most of the pressure in any event. The outer layers of a very thick cylinder do not take up the stress from the inner layers. Dr. Bridgman concluded that the best way to make a cylinder support a high pressure was first to stretch it on the inside by applying a much higher pressure than it was intended

Starrett Hack Saw Chart									
MATERIAL TO BE CUT	No. of Strokes per Minute		No. of Strokes per Foot		No. of Strokes per Inch		No. of Strokes per Square Foot		Notes
	Light	Heavy	Light	Heavy	Light	Heavy	Light	Heavy	
Light Angle	100	100	100	100	100	100	100	100	
Channel	100	100	100	100	100	100	100	100	
Two Iron	100	100	100	100	100	100	100	100	
Ornamental	100	100	100	100	100	100	100	100	
Heavy Angle	100	100	100	100	100	100	100	100	
Channel	100	100	100	100	100	100	100	100	
Two Iron	100	100	100	100	100	100	100	100	
Light Structural	100	100	100	100	100	100	100	100	
Heavy Structural	100	100	100	100	100	100	100	100	
Rail Cutting	100	100	100	100	100	100	100	100	
Steel and Iron Pipe	100	100	100	100	100	100	100	100	
Coupling and	100	100	100	100	100	100	100	100	
Waste Pipe	100	100	100	100	100	100	100	100	
Solid Block	100	100	100	100	100	100	100	100	
Cold Rolled	100	100	100	100	100	100	100	100	
Machine Steel	100	100	100	100	100	100	100	100	
Tool Steel	100	100	100	100	100	100	100	100	
Cast Iron	100	100	100	100	100	100	100	100	
Aluminum	100	100	100	100	100	100	100	100	
Other Metal and	100	100	100	100	100	100	100	100	
Tablet	100	100	100	100	100	100	100	100	
Less than 1/8 inch	100	100	100	100	100	100	100	100	
Over 1/8 inch	100	100	100	100	100	100	100	100	

The gage of a blade directly affects its cutting speed.

Take two hacksaws, both suited to cutting some particular kind or shape of metal but differing only in the matter of gage. The thinner of the two will cut the quicker.

The contact area of the larger blade—the square area of the saw in actual contact with the work—means more friction to be overcome, and after the first few cuts, more weight upon the saw becomes necessary.

The Starrett Hack Saw Chart indicates the most efficient type of blades to use on any given kind of work. Starrett Saws, used according to it, give the best results.

Send for Catalog No. 22 "B"

THE L. S. STARRETT COMPANY

The World's Greatest Toolmakers
Manufacturers of Hack Saws Unexcelled.

ATHOL, MASS.

Use Starrett Hack Saws

Attention to Details Essential to Efficiency

The necessity of increasing the weight as the saw is dulled must not be overlooked, and is a factor for which no absolute rule can be given. The most that can be said is, knowing approximately the time in which a certain blade should cut an average specimen of a certain kind and size of material, the weight should be increased by increments of from 5 to 10 pounds as often as the time of three successive cuts is above the average. Remember that the weight on a heavy gage saw must be increased faster, in proportion to the extra amount of dulled surface

or contact area, than for a thinner gage saw, regardless of the difference in weights on the first cut with each. In Hack Sawing, as in any other form of work, common sense, attention to detail and observation of manufacturers' instructions are great assets.

To sum up: The attainment of real efficiency in cutting metals with either hand or power Hack Saws depends upon:

1. The selection of the proper make of saw.
 2. The selection of the proper saw of that make for the material that is to be cut.
 3. The proper use of the saw selected.
- It is possible for any user of Hack

Saws, at the expense of time and money, to evolve for himself a system for selecting and using Hack Saws to the best advantage. It is likely there are many machinists whose experience is sufficiently wide to warrant their making their own selection of saws and establishing their own code of usage. To this class of men, this book will have been but little more than a confirmation of facts they already know. To the man who has not had the advantage of such wide experience, it is hoped that this book will prove of value in his search for the means of more efficient work and methods.—From "Hack Saws and Their Use," published by The L. S. Starrett Co., for free distribution.

ITH Double Seal Piston Rings

These Old Trucks Have
More Pep and Pulling Power
Than They Did When New

READ THIS LETTER

Fleming Bros.

RELIABLE GROCERIES and MEATS

Business as Usual as Ever for All Our Old Friends & Neighbors
Very Respectfully and Sincerely Yours
Dear Sirs: The 1921 We Done It

6903-5 Westworth Ave. and 1833 W. 103rd Street

TELEPHONE: Westworth 2441
Beret 202

Chicago, Ill., May 25 1921

Double Seal Ring Co.,
2335 Michigan Ave.,
Chicago, Ill.,

Gentlemen:

We have had your Double Seal Rings in two of our trucks for three years and they are both running as good as the first day we put the rings in. We are very highly pleased with the rings. They save us considerable in gas and oil. These trucks have more "pep" and pulling power than when they were new.

We have given the rings a good test and therefore we can honestly recommend them.

Yours truly, *Joseph Fleming*
Fleming Bros.

Double Seal Ring Company
General Sales Office, 2335 Michigan Avenue, Chicago, Illinois
Branches in 30 Large Cities

to maintain in practice. It was found that a cylinder treated in this way is in a state of internal strain, exactly as is a gun which has had hoops shrunk on it from the outside. As a result of the experiments a cylinder half an inch in diameter was stretched to 1.2 inch in diameter before breaking; and the break, when it came, started on the outside.

In the preliminary work on steel cylinders many cylinders were broken. This gave opportunity for interesting observations on the manner of rupture at high pressures, and two facts not to be expected from ordinary theory were noted. The same specimen of steel which stretched more than its diameter under pressure, if tested for strength in the ordinary way, would have broken when the strain became about 30 per cent, whereas the strain here was about 140 per cent before rupture took place. In all cylinders tested the break started at the outside, where the stress and strain were both least. There is reason to believe, however, that very brittle substances like glass would break on the inside, as predicted by the ordinary theory. The determining factor here, according to the experiments, is the plasticity of the substance.

Another important factor was the devising of some means of accurately measuring the pressures. None of the ordinary pressure gages were found to be of the slightest service at these high pressures. Again, strange to say, the very simplest method that can be conceived proved to be the best. It consists in inserting a steel piston through a hole in the wall of the cylinder and measuring the force necessary to prevent it from being blown out by the pressure within.

The minute the preliminaries were concluded and the actual experiments with water begun, it was found that the high pressures made the water disobey all the ordinary rules. The application of ordinary pressure to ice causes it to melt. But when ice is subjected to pressure at temperatures lower than ten below, Fahrenheit, it is no longer possible to make it melt, but instead it changes in form, passing over into another kind of ice more dense than water, instead of less dense like ordinary ice.

The pressure required to produce this second kind of ice is about 33,000 pounds per square inch. These two forms of ice are comparable to the two forms of carbon—graphite and diamond; with this difference: the new kind of ice changes to ordinary ice the moment the pressure on it is relieved, just as ordinary ice changes to water on the provision of sufficient heat. Old principles are borne out, however, and old reasoning supported, by the fact that when the ice is of less density than water, the freezing point is lowered by the application of pressure; while if the ice is of the denser-than-water variety, pressure raises the freezing point.

The Armed and Armored Limousine of a Chinese Governor

(Continued from page 513)

term of office with a bullet, as is so frequently the fate of Chinese officials, the car can be transformed in a twinkling. Down from inside the roof come steel shutters covering all the windows and reaching to the steel plates built inside the walls of the car. Concealed loopholes open on each side and in the rear, and six automatics or rifles can come into action. Another steel shutter rises out of the partition between the tonneau and the driver's seat, closing off danger from the front. A Colt machine gun appears from under the driver's seat and is fastened on to a special bracket built in at the right hand side of the cowl. The luxurious car is thus turned into a fortress.

As an additional measure of safety in dangerous times, there are fastened to each side of the car three swivels. Belts are provided that fasten into these with

LEGAL NOTICES

PATENTS

IF YOU HAVE AN INVENTION which you wish to patent you can write fully and freely to Munn & Co. for advice in regard to the best way of obtaining protection. Please send sketches or a model of your invention and a description of the device, explaining its operation.

All communications are strictly confidential. Our vast practice, extending over a period of seventy years, enables us in many cases to advise in regard to patentability without any expense to the client. Our Handbook on Patents is sent free on request. This explains our methods, terms, etc., in regard to Patents, Trade Marks, Foreign Patents, etc.

SCIENTIFIC AMERICAN

Contains Patent Office Notes, Decisions of interest to inventors—and particulars of recently patented inventions.

MUNN & CO., SOLICITORS OF PATENTS
Woolworth Building, NEW YORK
Tower Building, CHICAGO, ILL.
Scientific American Building, WASHINGTON, D. C.
Hobart Building, SAN FRANCISCO, CAL.

Annual Subscription Rates Scientific American Publications

Scientific American (established 1845) one year\$6.00
Scientific American Monthly (established 1876) one year\$7.00
Postage prepaid in United States and possessions, Mexico, Cuba and Panama.

Foreign Postage
Scientific American \$1.50 per year additional.
Scientific American Monthly 72c per year additional.

Canadian Postage
Scientific American 75c per year additional.
Scientific American Monthly 36c per year additional.
The combined subscription rates and rates to foreign countries, including Canada, will be furnished upon application.
Remit by postal or express money order, bank draft or check.

AGENTS WANTED

AGENTS, \$50 to \$200 a week. Free samples. Gold Sign Letters for Store and Office Windows. Anyone can do it. Big demand. Liberal offer to general agents. Metallic Letter Co., 431X N. Clark St., Chicago.

BUSINESS OPPORTUNITY

SUBSTANTIAL manufacturing corporation wants capable men to establish branch and manage salesmen. \$300 to \$2000 necessary. Will allow expenses to Baltimore as explained. Address, Mr. Clemmer, 603 N. Eutaw St., Baltimore, Md.

BUSINESS OPPORTUNITY

YOU CAN have a business profession of your own and earn big income in service fees. A new system of foot correction; readily learned by anyone at home in a few weeks. Easy terms for training; openings everywhere with all the trade you can attend to. No capital required or goods to buy, no agency or soliciting. Address Stephenson Laboratories 23 Back Bay, Boston, Mass.

CORPORATION SERVICE

GREAT CARE should be exercised at the inception of a new enterprise to insure its financial success. We render a specialized, complete service. If you contemplate incorporation or reorganization let us solve your problem. Inquiries solicited. Industrial Engineering Corporation, Engineering Building, 114 Liberty Street, New York.

FOR SALE

STEEL Tower and Tank—Capacity about 1,800 gallons. In good condition. Can be seen on premises. A. J. Murphy, Laurel House, Lakewood, N. J.

FOREIGN STAMPS

65 DIFFERENT STAMPS, including China, Japan, French Colonies, etc., given to applicants for our high grade approval selections. Send references and 2c stamp to the EDGEWOOD STAMP CO., Dept. G, Milford, Conn.

HELP WANTED

SPLENDID clerical work opportunity. Spare or whole time. No canvassing, good money. Chautauqua Business Builders, Jamestown, N. Y.

INCORPORATION IN ARIZONA

COMPLETED in 1 day. Any capitalization, least cost, greatest advantages. Transact business anywhere. Laws, By-Laws and forms free. Stoddard Incorporating Co., 8-A, Phoenix, Ariz.

WANTED

MANUFACTURING rights on metal articles. Also metal stampings and model work on contract. We are ideally located and equipped to develop patents. Meyers Company, Box 263, Bedford, Indiana.

Stop Oil Pumping Increase Mileage
Decrease Oil, Fuel and Water Consumption.
Save Regrinding Costs.

ZELNICKER EVER-TYTE PISTON RINGS - ST. LOUIS
Send for Free Evidence Booklets

Experimental and Model Work

Fine Instruments and Fine Machinery,
Inventions Developed.
Special Tools, Dies, Gear Cutting, Etc.
HENRY ZUHR, 489-93 Broome St., New York City

THE ENGLISIDE
Beach Haven, N. J.

Beach Haven has the best combination of sea shore features on the Atlantic Coast. A Matchless bay for sailing, always good fishing, perfect beach and bathing. The ENGLISIDE has all modern conveniences, private baths with salt and fresh water, and is a home as well as a hotel. Sure relief from hay fever. Open June 17th to September 20th. Send for booklet.

THE ENGLISIDE COMPANY, Inc., Owners
ROBERT F. ENGLE, Treas. and Mgr.
BEACH HAVEN, N. J.

WELL DRILLING

A Paying Business

Everybody wants a dependable, fresh water supply. The contractor with his Ithaca Well Drill finds arduous limit to his business. We supply standard outfits complete, mounted with power, or separate outfits to operate with your own engine or tractor. Widely adaptable in use—Water, Gas and Oil Wells, Blast Hole Drilling, Prospecting for Minerals. Small investment starts operator in fine paying, permanent business, all his own. Write for catalog.

WILLIAMS BROS.
434 West State St. Ithaca, N. Y.

MAXIM SILENCERS

For Rifles, Target Pistols, Exhausts, Air Compressors, Farm Engines, Motor Boats, Large Stationary and Marine Oil Engines

Manufacturing rights available. Write for information

MAXIM SILENCER COMPANY
94 Homestead Ave. Hartford, Conn.

Order Your Scientific and Technical Books Now

They are difficult to obtain and prices are constantly increasing. We will quote present price on any book of this nature and the price will hold unless the publisher should increase his price in the interim. Write for our 96-page catalog—the most complete scientific and practical catalog now issued. In addition, our 1920-1921 list will be sent you as soon as ready, and the prices in this list will hold good in possibly 80 per cent of cases; but you will be notified of any change before filling order. There will be no obligation in requesting catalog for we want you to know our Book Department. Write today. You'll find it valuable for suggesting books you need.

SCIENTIFIC AMERICAN PUBLISHING CO., Room 676, Woolworth Bldg., New York City

Indicating **Tycos** Temperature Instruments Controlling

The capacity as well as the desire to serve every temperature need in industry characterize the *Tycos* organization. From manufacture to application *Tycos* service is thorough, practical and reliable—complete whatever the problem.

Request catalogs, mentioning specific needs.

Taylor Instrument Companies
Rochester, N. Y.

There's a *Tycos* or *Tycos* Temperature Instrument for Every Purpose 779

Lupton
STEEL SHELVE

Tool Stands, Tool Cabinets, Pressed Steel Bench Legs, etc.

Order from Warehouse Stock
DAVID LUPTON'S SONS CO.
Clearfield and Weikel Sts.
Philadelphia

For Gunsmiths, Tool Makers, Experimental & Repair Work, etc.

From 9-in. to 18-in. swing. Arranged for Steam or Foot Power, Velocipede or Stand-up Treadle.

W. F. & J. Barnes Co.
Established 1872.
1999 Ruby Street
Rockford, Ill.

SOUTH BEND LATHES
For the Machine and Repair Shop

9' Lathe	\$215.00
11' Lathe	\$275.00
13' Lathe	\$365.00
15' Lathe	\$450.00
16' Lathe	\$525.00

South Bend Lathes are made in eight sizes, 9-in. to 24-in. swing, inclusive. Established 1906. Free Catalog.

South Bend Lathe Works
421 Madison Street
South Bend, Ind.

ICE MACHINES Corliss Engines, Brewers and Bottlers' Machinery

The VILTER MFG. CO.
989 Clinton Street
Milwaukee, Wis.

ASBESTOS

We are miners and shippers of Crude Asbestos in any quantity. We produce all grades at our world famous **BELL ASBESTOS MINES** in Canada. We also carry fibres, spin yarns, weave cloths, and make all sorts of Asbestos products.

For inquiry you want in Asbestos, turn to
KEASBEY & MATTISON COMPANY
DEPT. 8-1
AMBLER, PENNA., U. S. A.
Owners of the world's largest Asbestos Mines

1/4 H. P., 110 volts, A. C., 60 cycle, single phase, 1750 R. P. M. MOTORS

LARGE QUANTITIES NEW WASHING MACHINE MOTORS

These are of standard manufacture and carry the full factory guarantee. Shipped in original boxes. Complete as set. Suitable for operating Coffee Grinders, Cream Separators, Bottle Washers, Air Compressors, Sewing Machines, etc.

We will send C.O.D. subject to full examination. Money Refund Guaranteed.

\$22.75

MADE IN U.S.A. BY THE
W. E. JOHNSON - Box 21 - W. E., Pittsburgh, Pa.

a snap hook so that soldiers may be strapped to the running board and have both hands free to use rifles. Handles have been attached to the steel roof of the car for their convenience. So if attacked the car can in a moment become a bullet proof steel box, defended by a machine gun and six soldiers on the outside and by six more rifles from the inside.

The Print and Label Law (Continued from page 514)

ities, substantially as in the trade-mark law. Consequently a design to be placed on letter heads, cards, etc., as mere ornamentation and not being itself suggestive of any other article of manufacture, was denied registration; as was also a print designed to be used as a marker for a highway, though the same might be eligible for registration at the Copyright Office as "pictorial illustrations or works connected with the fine arts."

The word "designed" in this connection does not refer to the state of mind or intention of the author, but to the subject-matter or quality of the print or label itself, and if that subject-matter does not suggest or in some manner identify the particular goods for which it is used, the work is not registrable in the Patent Office.

The Commissioner must determine for himself whether or not the work presented is registrable as a print or label, and his decision, even though erroneous, cannot be reviewed by mandamus proceedings. But no nice application of rules will be made in the Patent Office to determine the degree of artistic quality displayed by the print or label; it will be registered as a matter of course when recognized to be of a character which is commonly regarded as the result of artistic or intellectual effort, or which might properly be so regarded. Registration will only be refused if the article belongs to that class which is not intended for the production of artistic effect on the beholder and which does not in fact produce any; as where the label consists only of printed text with directions for use of the contents of the box or bottle to which it is applied.

On the basis of the foregoing principles the present rules of the Patent Office define a print as "an artistic and intellectual production designed to be used for an article of manufacture and in some fashion pertaining thereto, but not borne by it; such, for instance, as an advertisement thereof"; and a label as "an artistic and intellectual production impressed or stamped directly upon the article of manufacture, or upon a slip or piece of paper or other material to be attached in any manner to manufactured articles or to bottles, boxes, and packages containing them, to indicate the article of manufacture." No print or label can be registered unless it properly belongs to an article of manufacture and is descriptive thereof and is as above defined; but no examination will be made as to its novelty.

Protection of Life Against Fire (Continued from page 516)

closed stairs—fire-resisting enclosure with fire doors. (d) Interior stairs—not enclosed. (e) Elevator. (f) Outside stairs—not enclosed. (g) Outside fire escape, stairway type. (h) Outside ladder. (i) Special forms of fire escapes, such as chutes, poles and ropes.

The horizontal exit is believed by most fire protectionists to be the best for the protection of life, especially where there are a large number of persons on one floor. The occupants, after passing through a fire door or across a bridge are in a protected area from which they may descend in safety without excessive haste. Adequate stairways must, however, be provided for moving the occupants to the ground level as soon as they have passed through the horizontal exit.

(Continued on page 523)

Stopped, locked or lowered from any angle up to 45°

There is no gradual "settling" of the raised truck body when it is held by a Van Dorn Hoist.

Stopping the hoist, firmly and positively locks it, and the body will be held rigidly in any angle until it is *pulled down* by the same power which raises it. Gravity plays no part in the operation. Work can be performed on the chassis under the raised body with perfect safety.

Operation of the Van Dorn Mechanical Hoist is automatic in every detail. The hoist is started, stopped or lowered with the body at any angle up to 45°—at which extreme dumping angle it automatically stops. The truck can be driving away with the body lowering—the hoist stopping and disengaging automatically when the body settles to its bed.

Complete bulletin descriptive of Van Dorn Mechanical Vertical and Horizontal Hoists, and Truck Bodies sent to any truck operator.

Write

THE VAN DORN IRON WORKS COMPANY
Cleveland

Branches Long Island City, N. Y., and Philadelphia
Distributors in all other cities

Van Dorn Mechanical Dump Truck Hoists, Bodies, Frames, Pressed Parts

Cut away view of the Van Dorn Mechanical Hoist showing the screw jack principle of operation and the automatic lubricating device.