Foot Inclosed in Conventional Shoe.

The Bare Foot.

Foot in the New Army Shoe.

Scientific Foot Treatment for the Army

Trying on Shoes by X-Rays

AFTER four years of exhaustive experiments the Board of Army Officers appointed to study foot troubles of United States soldiers with a view to offering a remedy has completed its work and has recommended the adoption of a new kind of footwear—a perfect fitting shoe.

Under the old regulations shoes of two patterns were ordered, one a straight and the other a slightly curved last, neither of which, however, gave satisfaction on long marches, and for years the percentage of imperfect feet in the army has been appalling. On long marches men have been forced to drop out of line on account of blisters, bruises and other shoe troubles. The new shoe, which the board has been so long in perfecting, has a low flat heel, a broad round toe and a quarter of an inch more swing or curve than the old style, the straight last having been abandoned altogether.

The investigations carried on by the board were of the most complete and painstaking character, and X-ray photographs resulted in some very interesting information as to the effect on the feet of standing in certain positions, and marching in both heavy and light equipment. Civilians might study these tests in shoe fitting with bene-

ficial results, especially those troubled with aching feet. The heaviest tests were made with the soldier in his full uniform and carrying the maximum amount of equipment of 40 pounds. In the course of these investigations the tendency of the feet to spread as the weight was thrown on them, was fully studied, and the X-ray shows the position taken by the various bones of the feet as affected by the changing position and weight. Photographs showing some remarkable experiments have been taken of the feet in the old-style shoe with 40 pounds of pressure on the soldier's back, and the same foot in the new shoe. Invariably in the old shoe some of the toes were pushed completely out of their proper position, but in the new shoe each toe has plenty of room, thus making marching with full equipment as easy as possible.

The board during its labors examined thousands of soldiers' feet under varying conditions, carefully taking note and making report on each foot where trouble was caused by a shoe. These feet were also measured and photographed in every conceivable position, ranging from the most complete repose to the severest possible strain under the conditions of service.

In the final tests at Fort Leavenworth the new shoe proved beyond doubt the success of the board's arduous work. A march of nine days, covering 118 miles, was made by 375 men. Part wore the old-style shoe and the others the new shoe. The latter finished the tramp easily, while a great percentage of those equipped with the old-style footwear were forced to quit on account of shoe trouble.

The method now adopted by the army for "breaking in" new shoes and making them conform to all the little quirks of individual feet, resulting in a perfect fit, is unique. After the shoes are fitted to the soldiers' feet they are made to stand in water to their shoe tops until the leather is thoroughly soaked, then they are marched around until the shoes have dried on their feet, when forever after the new footwear is as comfortable as the proverbial "old shoe." This may seem a somewhat heroic method, but in practice it is found thoroughly effective.

The new shoes will be made both in black and tan, the former to be used with the blue uniform and with full dress and the latter about the garrison and in the field.

The Permeagraph

A Graphical Machine for the Magnetic Testing of Iron and Steel

By Nathan C. Johnson, Research Fellow in Mechanical Engineering, Cornell University

THE determination of the magnetic properties of iron by any of the ordinary ballistic or magnetometric methods commonly in use is at best a tedious and cumbersome process. Without regard to the process employed, it may be fairly said that the nature of the operation and the apparatus is such that only in the hands of a skilled operative and at the expenditure of much time and patience can good results be obtained. Further, for a comprehensive view of the results obtained, the instrument readings have to be laboriously plotted on cross-section paper, with often the added inconvenience of deriving these plotted points from the instrument readings.

With a view to overcoming these difficulties and at the same time of obtaining permanent, comprehensive records that could be readily filed away, the machine presented herewith, which the writer ventures to call the "Permeagraph," has been devised. It presents several features not contained in any other apparatus and it is believed that it will find a considerable field of usefulness.

In much commercial testing of iron, comparative results graphically presented would be sufficient for every ordinary purpose where the iron under test is compared to a sample of known properties. Such comparative curves for different irons are shown in the attached print, Fig. 1. These curves were traced by the machine and have not been corrected in any way. The properties of the irons is evident at a glance; and with proper calibration, the exact qualities of each could be scaled off without trouble.

The curves shown in Fig. 1 were taken with carefully prepared samples, that is, the length and cross section of each is the same and one end of each has been accurately surfaced off. This, however, is not always necessary. The curves shown in Fig. 2 have been obtained with a sample of transformer iron which has simply been cut from the sheet with snip shears and placed on the top of the standard sample in the machine. The curve of the standard sample is the lower one. The curve of the transformer iron is the upper and the properties of the

latter can, if needed, be readily deduced therefrom.

These matters will be better understood by reference to the construction of the machine, as shown in the prints. By reference to the photograph and diagram, it will be seen that in general the device consists of a means for measuring the induction of the sample by means of its attractive power on a movable yoke, which is part of a closed magnetic system; and of a drum (15) carrying a piece of paper for the record, actuated by a D'Arsonval system (16) in shunt with the magnetizing coil (2). More particularly, the magnetic circuit consists of a massive frame (3) and a movable yoke (4) whose magnetic reluctance as compared to the flux to be induced in the sample (1) when excited by the coil (2) is made very small. The yoke (4) rests on two needle points at (7) on the lower part of the yoke; and is counter-balanced by the adjustable weight (5). The yoke (4), also has an extension, preferably of non-magnetic metal, on its forward end, carrying the cone-ended adjusting screw (20). From this screw a double-pointed steel pencil (10) ex-

The Permeagraph, View in Perspective.

View, Partially in Section, Showing Details.

tends downward and bears on a corrugated copper diaphragm (11), covering an oil reservoir (8). From this reservoir, a pipe (12) leads to a Bourdon tube (13), the whole system of reservoir, pipe and Bourdon tube being completely filled with kerosene oil. Connected to the free end of the Bourdon tube by means of a straight line motion (not shown in the photograph) is the arm (14), carrying on its outer end a V-shaped pen, such as is commonly used on recording instruments. This arm (14) is counterbalanced by a small adjustable weight.

From the preceding, it will be seen that by this construction, we have left three air gaps in the magnetic system, i. e.: one where the sample rests on the lower part of the yoke; one between the upper end of the sample and the movable, upper part of the yoke; and one between the upper and lower portions of the yoke.

The last of these is almost wholly eliminated by grinding the surfaces in contact and properly adjusting the screws (7). The first one—that between the bottom end of the sample and the yoke—is also made as small as possible by careful grinding of the surfaces; and the effect of this is also made as small as possible by making the gap at the other end of the sample relatively large. It will thus be seen that so far as the magnetic circuit is concerned, we shall have a means of measuring, through the movement of the pen attached to the Bourdon tube, the induction in the sample (1), due to its attraction of the yoke (4) and the resultant pressure on the diaphragm covering the oil reservoir.

The operation of the apparatus is simple. The D'Arsonval system actuating the drum is, as before stated, in shunt with the magnetizing coil around the sample. This gives us H on the curve. The pressure exerted on the diaphragm actuates the pen, giving us the values of B^2 corresponding. It is true that to get this latter motion, we have some motion of the diaphragm, which means some motion of the arm of the yoke (4), with consequent lessening of the air gap between (4) and the sample (1). But this motion is that corresponding to the change of volume of the Bourdon tube in altering from the elliptical to the circular, with a $3/32$ -inch maximum movement of the free end; and this change of volume is distributed over the area of a 9-inch diaphragm; and this movement of the diaphragm as related to the air gap is lessened by the ratios of the distances of the screw (20) from the screws (7) and that of the center line of the sample (1) from the screws (7), so that it may be taken as negligible. With the maximum induction obtainable in soft Swedish iron in the machine shown in the photograph, this lessening of the air gap is 0.0008 inches.

In inserting a sample in the machine, the yoke (4) is lifted. A bracket (23) at the back of the frame takes the weight of (4) in so doing and relieves the needle

points (7). The sample in place (4) is again lowered until the screw (20) rests on the steel pencil (10). The current is then increased steadily by means of a water rheostat, or other rheostat giving a smooth curve; and if the pen has been placed in contact with the paper on the drum, a B^2-H curve for the sample will be traced. When a maximum is reached, the current is decreased to zero, thus tracing half of the hysteresis loop. Residual magnetism in the sample will hold the pen above zero; and when the current is again gradually increased after reversal, the opposing induced flux will first bring it to zero of B , then cause it to rise again. In this way, a complete and accurate hysteresis loop may be traced by even an unskilled operative in about two minutes, the only limiting feature as regards time being the lagging of the induced magnetism in the sample behind the inducing force. This soakage effect requires a slow and steady varying of the current for best results.

It will be noticed from Fig. 3 that the hysteresis loop has both horns above the axis of x . This is because the pressure is expressed positively only. If it is desired to have this appear in the customary form, one-half of the loop may be turned over.

While the hysteresis loop may be quite accurately taken in this way and the loss determined by integration, it is recognized that the better way to determine iron losses is probably by some method such as the Epstein, or by the improved apparatus of Burrowes. The province of the Permeagraph is the rapid, comparative testing of irons.

In this connection, the method of determining the quality of transformer iron without accurate preparation of the sample, should be referred to again. All that is necessary to do is to cut off a piece of the sheet sufficiently large to cover the end of the sample—in the machine shown, the sample being $1\frac{1}{4}$ inches in diameter. After running a curve with the standard sample, place the small piece of sheet metal over the end. Then run the curve again. It will be seen that this curve is quite distinctive, for by cutting down the air gap between the sample and the yoke to the extent of its permeability, the value of B will be increased and this increase will be registered by the pen. It matters not what sort of contact this small piece makes with the yoke or the sample. The resistance of the air gap will be decreased by its presence and this will show in the increased attraction of the yoke (4).

Friction between the pen and the paper on the drum is eliminated by mounting a vibrator on the pen standard

and so adjusting the pen that contact with the paper is made through a minute drop of ink. The vibrator shakes the pen enough to cause it to draw the line without more than instant contact at any time.

An obvious refinement would be to make the sample longer in proportion to its diameter; and to fashion the pole pieces to secure concentration over the air gap (21) between the yoke (4) and the sample and to diminish leakage. Further, an auxiliary coil (6) wound over the back of the yoke, excited by a current having a constant value such that the flux induced in the yoke will just overcome the reluctance of the yoke and the air gap has assisted in giving good results. All these refinements are not shown in the photograph, which was taken before they were added to the machine; but with their aid, results have been obtained which warrant the writer in believing this device will find place in commercial work.

How Accidents Originate.—The Imperial Insurance Department of Germany recently published data concerning the causes of accidents, which are interesting as well as instructive. The figures, as given below, do not, however, cover all accidents reported, but only those for which damages had been recovered:

		%
1. Motors, transmission, machine work	14,094	20.3
2. Lifting appliances (elevators, cranes, hoists)	3,097	4.5
3. Steamboilers, steam conduits	158	0.2
4. Explosions and explosives	552	0.7
5. Combustible, hot and caustic substances (gases, vapors)	2,208	3.6
6. Collapsing, demolishing; dropping and falling objects	11,012	15.5
7. Fall from ladders and stairs; excavations, hatchways, etc.	10,451	15.1
8. Loading and unloading; carrying and lifting	8,630	13.0
9. Vehicles (running over or falling off)	4,469	6.5
10. Railways	5,059	7.3
11. Navigation and traffic on water....	573	0.8
12. Animals (blow, thrust, bite).....	1,032	1.6
13. Tools and implements	4,611	6.5
14. Other objects or events.....	3,365	4.4
Total	69,311	100.0

From these figures we learn that but 24 per cent of all accidents fall to modern machine operations. The majority, nearly 45 per cent, are the results of gravitation (falling, lifting, carrying), while transportation causes about 14 per cent of these accidents. The figures also show that neither the increase in the number of persons insured, is the cause of the growing number of accidents, nor are these caused by the extended application of elementary forces (at the expense of hand operations), as is generally supposed.—*Zeitschr. f. Gewerbe Hygiene.*

Fig. 1.—Permeagraph Curves for Different Samples of Iron. 1. Cast Iron. 2. Machine Steel. 3. Swedish Charcoal Iron. 4. Annealed Laminated Steel.

Fig. 2.—Curve of Transformer Iron Obtained by Placing Sample on Top of Standard Sample and Running the Curves. Curve A, Standard Sample With Transformer Iron. Curve B, Standard Sample Alone.

Fig. 3.—Hysteresis Loop for Soft Steel, With Virgin Curve, Taken on the Permeagraph.