(*Paper No. 1671.*)

“New Zealand Lighthouses.”

By JOHN BLACKETT, M. Inst. C.E.

IN 1870 the Author was appointed Marine Engineer for the colony of New Zealand, and in that capacity was immediately called upon to arrange for the erection of a number of lighthouses. Two separate trips were undertaken, each being a complete circumnavigation of the Middle and North Islands respectively, for the purpose of determining the sites for the intended lights. During these trips full and accurate information was obtained on which to base a scheme for lighting those parts of the coasts not already provided for, and the work of erection was ordered to be commenced forthwith. The following description will show the progress made in lighthouse construction in New Zealand, and the details may be useful for reference in planning similar structures in other colonies or countries where similar or nearly similar conditions may obtain.

The sites selected presented very various conditions in reference to convenience of access and to the obtaining of materials for construction; several being on the mainland, where the making of roads or tramways was the principal difficulty to be encountered; others on islands, some of which presented fair landing conveniences, but others being rocky and precipitous demanded special arrangements for landing and conveying the materials and apparatus to the site of the buildings, mostly on the summit.

After due consideration of the subject of materials, it was determined to use timber, not only for the dwellings and stores, but also for the towers, as being cheaper, and more expeditiously erected than brickwork or masonry, and more easily handled at inconvenient or dangerous landing places. At the same time it was considered that well built timber structures would be much less liable to damage by earthquakes, the probable effect of which, on such structures, frequently of a lofty character, and on a comparatively small base, should not be lost sight of, more especially as earthquakes are not of rare occurrence in New Zealand, and are occasionally severe.

To ensure great strength and durability in the towers the

Australian timber called iron-bark, which is hard and heavy, has been adopted for all the main framing; and totara, a very durable New Zealand timber, for all the minor parts of the framing and for the outer boarding, &c. The latter timber has also been used for the piles, ground-plates, and weather boarding of the dwelling-houses, stores, &c., which, as a rule, are roofed with stout corrugated galvanised iron plates. One style of construction has been adopted in all the later buildings as ensuring better work and giving more satisfaction than any other method of framing that has been tried; but the whole of the lighthouse towers enumerated in the subsequent list are not thus framed. The same style has been adopted in some of the American lighthouses. On each side of any tower, whether square, hexagonal, or octagonal, is made a separate and complete frame thoroughly braced, and bolted together. The proper number of these frames being placed together, well fitted, blocked, and bolted to each other, constitutes the tower; and this method has been found to produce a building possessing great stiffness and solidity.

The frames thus connected stand on a ground plate prepared for their reception; this, in the case of solid rock, is simply bolted down to it with rag bolts; but in loose rock a deep and wide trench is excavated and filled with concrete to form a solid mass to which the ground plate is secured with bolts. Where ordinary soil or clay exists to a considerable depth, the ground plates rest on a pair of long piles at each angle, either driven or sunk and rammed, and resting on a stout connecting foot-piece.

The framing is purposely made heavy, but to give greater weight and solidity, and to ensure stiffness and immovability in the towers in windy and exposed situations, the spaces between the weather-boarding and inner lining for a height of 8 or 10 feet are filled solid all round with dry clean shingle or broken stone; this has an excellent effect in stiffening the tower.

The towers are ventilated by three or four ventilators in each floor; these open to the air level with the floor, then turn upwards between the weather-boarding and the lining to a height of 4 or 5 feet, where they pass through the inner lining, and are each fitted with a hinged door, by which the supply of air, by one or more according to the force and direction of the wind, is regulated.

The coping-plate is made distinct from the upper top-plate of the main framing, and is kept apart from it by short joists interposed crosswise; this gives a space in which to screw up the nuts of the

holding-down bolts for the lantern sole-plates, and is found to be a convenient arrangement; the lining-boards opposite this space being made fast with screws only, so that they may be easily taken off to give access to these bolts.

The batter of the sides of the towers is 1 horizontal to 9 vertical.

The lantern and lighting apparatus are imported complete and ready for fixing. The lanterns, lamps, and fittings are on the plan of the Northern Board of Lighthouses, United Kingdom; the lights (Dioptric Holophotal) have been supplied by Messrs. Chance Brothers and Co., Birmingham, and latterly by Messrs. Barbieri and Feneste, Paris, the supply of the whole being under the direction and supervision of Messrs. D. and T. Stevenson, of Edinburgh.

Until about 1877 colza oil was used in all the New Zealand lighthouses, but at that time paraffin oil was tried, and being found to answer the purpose well, and being cleaner and cheaper than colza oil, it is now being generally adopted as fast as the necessary alterations to the lamps can be made. One of the lighthouses, viz., that being erected at Hokitika, will be lighted with ordinary coal gas from the town gasworks.

As a rule, the lighthouses in New Zealand are maintained and tended in the ordinary manner with first, second, and third keepers, space being generally found for the erection of proper dwellings for them and their families. In one case only, that of the "Brothers" in Cook Strait, has it been found necessary to establish a "rock station," where three men only are stationed, one man of whom is relieved every month.

The lighthouses built in New Zealand after the year 1870, and those now being erected, up to the present time have cost about £96,000. They are as follows:—

Cape Maria Van Diemen, extreme north	1st order, revolving 1', visible 24½ miles, with red light over Columbia Reef.
Moko-Huiori, Hauraki Gulf (projected and in hand)	1st order, flashing 10".
Maunkau Harbour, South head	3rd order, fixed, visible 26 miles.
Portland Island, Hawkes Bay	2nd order, revolving 30", visible 24 miles, red light over the Bull Rock.
Napier, Hawkes Bay	4th order, fixed, visible 24 miles.
"Brothers," Cook Strait	2nd order, flashing 10", visible 22 miles, with red light over Cook's Rock.

Cape Foulwind, West coast, Middle Island	2nd order, revolving 30", visible 19½ miles.
Hokitika, " "	4th order, fixed (gas).
Akaroa, East coast, " "	2nd order, flashing 10".
Luiruru, " "	5th order, fixed, visible 14½ miles.
Moeraki, " "	3rd order, fixed, visible 19½ miles.
Cape Saunders " "	2nd order, revolving 1'.
Puysegur Point, Preservation Inlet, extreme south-west angle, Middle Island	2nd order, flashing 10", visible 19½ miles.
Centre Island, Foreaux Straits . . .	1st order, fixed, visible 22½ miles.

The lighthouses erected before 1870 are as described below, viz. :—

Tiri-Tiri, Hauraki Gulf	1st order, fixed, visible 23½ miles.
Tonui Passage, between Auckland and Thames. }	5th order (on iron screw piles).
Cape Farewell Spit, Western head of Blind Bay. }	2nd order, revolving 1', visible 17 miles. Skeleton wood tower, 120 feet.
Nelson, Boulder Bank, Blind Bay . . .	4th order, fixed, visible 12½ miles. Cast iron tower, 60 feet.
Pencarrow, Wellington Heads	2nd order, fixed, visible 30 miles.
Cape Campbell, East coast, Middle Island, south entrance to Cook Strait. }	2nd order, revolving, visible 19 miles. Skeleton wood tower.
Godley Head, Port Lyttleton	2nd order, fixed, visible 27 miles.
Taiarou Head, Port Chalmers entrance .	3rd order, fixed, red, visible 20 miles.
Nugget Point, South-east coast, Middle Island. }	1st order, fixed, visible 23 miles. Stone tower, 20 feet.
Dog Island, Foveaux Lights, off Bluff Harbour. }	1st order, revolving 30", visible 18 miles. Stone tower, 90 feet.

The two lists together make a total of twenty-four lighthouses, and the coasts of New Zealand, even at this early stage of its history, are well and efficiently lighted.

The communication is accompanied by eight sheets of engravings, from which Plate 15 has been prepared.