- 17—J. W. McBain and M. E. Laing, *J. Chem. Soc.*, **117** (1920), 1508; J. W. McBain, W. F. Drake, and C. S. Salmon, *Proc. Roy. Soc.*, **98A** (1921), 395.
- 18—H. N. Holmes, *J. Am. Chem. Soc.*, **42** (1920), 2049.
- 19—P. Scherrer, *Nachr. Kgl. Ges. Wiss. Göttingen*, **1918**, 96.
- 20—R. H. Bogue, *Chem. Met. Eng.*, **23** (1920), 61; *J. Am. Chem. Soc.*, **44** (1922), 1313, 1343; *J. Franklin Inst.*, **193** (1922), 795; **194** (1922), 75.
- 21—H. D. Dakin, *J. Biol. Chem.*, **44** (1920), 524.
- 22—R. H. Bogue, *Chem. Met. Eng.*, **23** (1920), 105, 154.
- 23—J. Alexander, *J. Am. Chem. Soc.*, **43** (1921), 434.
- 24—F. Elliott and S. E. Sheppard, *J. Ind. Eng. Chem.*, **13** (1921), 699.
- 25—A. W. Thomas, *Ibid.*, **12** (1920), 177; A. W. Thomas and M. W. Kelly, *J. Am. Chem. Soc.*, **44** (1922), 195.
- 26—F. L. Seymour-Jones, *J. Ind. Eng. Chem.*, **14** (1922), 130.
- 27—C. E. K. Mees, *J. Franklin Inst.*, **1921**, 631.
- 28—S. E. Sheppard, Monograph on Gelatin, in press.
- 29—J. Alexander, A. C. S. Monograph on Gelatin and Glue, in preparation.
- 30—L. Thiele, "Leim und Gelatine," Leipzig, **1922**.
- 31—R. H. Bogue, "The Chemistry and Technology of Gelatin and Glue," McGraw-Hill Book Co., New York, **1922**.
- 32—F. G. Donnan, *Z. Elektrochem.*, **17** (1911), 572; Donnan and Harris, *J. Chem. Soc.*, **99** (1911), 1554; Donnan and Garner, *Ibid.*, **115** (1919), 1313.
- 33—E. Hatschek, *Kolloid-Z.*, **7** (1910), 301; **8** (1911), 34; *Trans. Faraday Soc.*, **9** (1913), 80.
- 34—E. Fischer, Levene and Anders, *Z. physiol. Chem.*, **35** (1902), 70.
- 35—Skraup and von Biehler, *Monatsh.*, **30** (1909), 467.
- 36—D. D. Van Slyke, *J. Biol. Chem.*, **10** (1911), 15; **22** (1915), 281.
- 37—M. Kind, U. S. Patent 1,046,307 (1912).
- 38—R. H. Bogue, *J. Ind. Eng. Chem.*, **14** (1922), 435.

Progress on Emulsions

By Leon W. Parsons

ASSISTANT DIRECTOR, RESEARCH LABORATORY OF APPLIED CHEMISTRY, MASSACHUSETTS INSTITUTE OF TECHNOLOGY, CAMBRIDGE, MASS.

THIS ARTICLE indicates briefly several main channels through which progress is being made in studying emulsions. Several fairly complete summaries of the literature on emulsions are available, to which the reader is referred for details.¹ With emulsions, the "practice of the art," extensive although incompletely understood, is far ahead of the "science," a condition quite universal in applied colloid chemistry. For discussion, a rough division may be made into theoretical aspects and practical applications, subdividing the latter into, first, the formation of stable emulsions, and, second, the breaking of undesirable emulsions.

THEORETICAL ASPECTS

NATURE OF PHASES USED—Frequently, the presence of various impurities in the nonaqueous phase has been unintentionally a major factor in determining the behavior of the resulting emulsions. On account of the complexity of these systems, the writer believes that steady progress will be made only by adopting a more "synthetic" program in studying emulsions, namely, using the purest liquids available for the two phases, and, after determining the characteristics in these supposedly simple systems, building up gradually more and more complex phases, determining the effect of the added substances and comparing the effects with the phenomena encountered in complex commercial systems. Bhatnagar has selected pure British Pharmacopeia paraffin oil for important studies on emulsion stability and in this laboratory Nujol, a highly refined mineral oil, has served very satisfactorily as a nonaqueous phase for studying mineral oil emulsions.

NATURE AND FUNCTION OF EMULSIFYING AGENT—This factor has influenced greatly various theories of emulsification. Emulsifying agents are either in true or colloidal solutions or are finely divided solids in suspension. Surface tension does not always play a major role. Briggs mentions several very good emulsifying agents which do not lower the surface tension. Holmes' work on gelatin indicates cases where viscosity rather than surface tension determines the stability. Fischer believes that the emulsifier must be a hydrated or solvated colloid combining with the continuous phase.

¹ Clayton, *J. Soc. Chem. Ind.*, **38** (1919), 113; Liesegang, *Z. deut. Ol- Fett-Ind.*, **40** (1920), 501; A. A. Thomas, *THIS JOURNAL*, **12** (1920), 177; Bancroft, *J. Phys. Chem.*, **16** (1912), 177, 345, 475, 739; **17** (1913), 501; **19** (1915), 275, 513; **20** (1916), 1; Bancroft, "Book on Applied Chemistry," **1921**; "The Physics and Chemistry of Colloids," Report of Faraday Society, October 25, 1920, p. 17; Clayton's book on "Emulsions" being published.

Bancroft, in correlating earlier theories, states that emulsification is due to a solid or plastic film formed between the two phases by adsorption, the type of emulsion being determined by the wetting of the film by the two liquids, whichever wets the film more becoming the external phase. Data obtained by R. E. Wilson indicate that emulsifying agents form a film possessing the properties of a plastic solid rather than a viscous liquid.

Pickering's early work on finely divided solids as emulsifying agents in which is suggested the idea of relative wetting as a determining factor in influencing the type of emulsion has been continued recently by Briggs, who has shown conclusively the similarity between emulsions obtained with finely divided solids and with so-called soluble emulsifying agents, as soaps.

A new theory is proposed by R. T. A. Mees² to explain the emulsifying power of soaps by combining the theory of Harkins and Langmuir which deals with the orientation of soap molecules at interfaces and the previously mentioned hydration theory of Fischer.

Several abnormal effects of emulsifying agents have been observed. In this laboratory, it has been found recently that a solution of sodium oleate, after aging, can produce a water-in-oil (Nujol) emulsion, possibly because of the formation of an acid oleate by hydrolysis, a change in degree of hydration, or the formation of a plastic film in the solution. Similar water-in-oil emulsions are obtained with sodium oleate and stearate when ground in oil and shaken with water, but no such effect was noticed on grinding a polyvalent soap in water and subsequently shaking with oil. Ammonium oleate, a monovalent soap, is said to be capable of producing a water-in-oil emulsion.

In brief, there is urgent need for further work on the soaps and the finely divided solids to correlate their physical and chemical characteristics and their behavior when used as emulsifying agents. More definite data are needed on the quantitative determination of relative wetting, on changes which may accompany abnormal effects, and also on the changes in physical structure of soaps. Photomicrographic methods and the ultramicroscope should prove valuable laboratory tools.

METHODS OF PREPARATION—These consist fundamentally in breaking up into droplets what is to be the dispersed phase and then causing the emulsifying agent to go into the inter-

² *Chem. Weekblad*, **19** (1922), 82.

face. The breaking up is accomplished mechanically and the emulsifying agent may be added either to the internal phase, may be suspended or dissolved in the continuous phase, or may be formed by chemical action at the interface. Briggs has shown that intermittent shaking is considerably more effective than continuous shaking. Clayton believes that shaking is an inferior method of making emulsions, since, as the emulsion becomes more perfect, the smashing action between heavy and light particles decreases, whereas it should increase. He suggests that according to Briggs it would appear that the ideal process of emulsification is one in which the dispersed phase is broken up as much as possible, while the continuous medium is left undisturbed as far as possible; and that continuous shaking might give equally as good results as intermittent, provided the emulsified portions of the mixture are continually removed from the mass so that the energy of shaking is concentrated on the remainder.

METHOD OF TESTING PHASE RELATIONSHIPS—Both Briggs' drop method and Robertson's color indicator method have been criticized by Bhatnagar; the former, on account of the fact that a single drop may not always represent accurately the emulsion; the latter, on account of possible disturbance to equilibrium by introducing the oil-soluble dye. Bhatnagar has developed an electrical conductivity method for determining the type of emulsion which, it seems, may also be open to criticism because of disturbance of equilibrium. By careful microscopic inspection, aided by a microphotographic attachment, the writer has been able to utilize both the Briggs and the Robertson tests very satisfactorily. Care must be taken, however, to observe closely the internal phase.

STABILITY—Considerable experimental work is being conducted on the stability of various emulsions. This depends on a number of factors, such as the nature of the emulsifying agent, volume ratio, properties of nonaqueous phase, etc. In emulsions of two pure liquids, the factors affecting stability, such as viscosity, size of particle, difference in specific gravity, and electrical charge, will also influence the stability of emulsions with emulsifying agents, though their effects may not be predominant.

The inversion point evidently marks a region of instability and is of great importance from both a theoretical and a practical standpoint. Clowes and Bhatnagar have both studied this extensively. Similar studies on the effect of different variables on the inversion point have been conducted in this laboratory for Nujol-water systems.

There is a rich field for investigation in studying the action of various electrolytes on the properties of emulsions. Bhatnagar has extended the early work by Donnan, Ellis, Lewis, and Hatschek and has pointed out the resemblance between neutral oil emulsions and suspension colloids. He records a parallelism between the reversal of phases in emulsions and the precipitation of colloid sols in suspensions, and indicates the possibility of clearing up the mysteries of coagulation and of developing a rational theory of colloidal solutions and emulsification.

PRACTICAL APPLICATIONS

FORMATION OF STABLE EMULSIONS—Many liquid emulsions are being developed. The U. S. Bureau of Entomology is studying oil emulsions for contact insecticides and is obtaining interesting results with a nicotine oleate emulsion. The scope of medicinal emulsions is enlarging greatly. The problem of preparing cutting or so-called soluble oils is being investigated by several oil companies, the chief difficulty being in the selection of the most suitable oil-soluble colloids. Attempts are being made to develop an emulsified light fuel for use in tractors.

Many solid or semisolid systems, involving emulsions,

are of great commercial importance. Clayton has studied carefully the production of margarine, one of the most complex solid emulsions. By different mechanical treatments with the same material, either type of emulsion may be obtained and the problems in margarine manufacture offer an extremely fertile field for research. The emulsion chemistry of household products, such as mayonnaise, has undergone considerable development. A systematic study of lubricating greases (water-in-oil emulsions) is greatly needed. Various polishes and creams, including toilet preparations, offer great opportunities for development to the colloid chemist. Asphalt emulsions are finding extended use for paving purposes and for application to paper pulp in forming water-resistant stock. Emulsification of mineral oils in the cooking of rags for paper stock has been studied recently.

Some other systems involving emulsions which are being studied are: ready mixed paints; emulsified fats for leather; artificial leather; emulsions of japan in water; soap emulsions of fat solvents; rubber latex; and biological phenomena.

BREAKING OF THE EMULSIONS—A beginning is just being made to study systematically the breaking of undesirable commercial emulsions, such as those encountered in refining wool fat and particularly in the petroleum industry. At the recent emulsification symposium of the Petroleum Section³ the general nature of the problems involved was indicated. The systems are extremely complex and illustrate clearly the aforementioned need for more careful synthetic studies. The Bureau of Mines at its Oklahoma Station is starting an investigation of oil field emulsions. This laboratory is also conducting a fundamental investigation of commercial petroleum emulsions. The American Petroleum Institute has outlined a program for studying this problem.

In conclusion, it may be noted that there is great activity along both theoretical and practical lines on emulsion research. Considerable information is necessarily kept secret by various companies, but there is a keen desire to obtain accurate scientific data on emulsions and to apply such data to their particular problems. The need for cooperative research between universities and commercial laboratories is great and, with the rapid advances which have been made in colloidal chemistry during the past ten years, the results of such cooperative research should be extremely valuable.

³ THIS JOURNAL, 13 (1921), 1008.

Inventions by British Government Workers

A committee of representatives of British governmental departments and British scientific men has recently recommended a comprehensive scheme of dealing with inventions by government workers or by individuals aided or maintained from public funds. The committee recommends the organization of an interdepartmental patents board. Pending a decision in each case by this board, all rights in inventions made by government employees shall belong to the government. If the inventor can satisfy the board that he derived no assistance from the nature of his employment in making the invention, he shall be entitled to all rights therein. The question of whether the inventor is entitled to any reward in addition to the enjoyment of commercial rights shall be decided by the board. Where the rights in an invention capable of commercial exploitation belong to the government, the invention shall be exploited commercially for the benefit of the government. A system of awards and merits for the inventor is proposed, which should be passed upon by an awards committee, to be organized within the proposed patents board. These are not intended as substitutes for commercial profits, but as a recognition of merit and as an incentive to government workers.

Many people were overcome and \$1,000,000 damage was done by a fire in the storage warehouse of the Manufacturers' Transit Co., New York City, July 18. Explosions of magnesium powder used largely in flashlights, were responsible for the blaze.