

1 **This is the pre-peer reviewed version of the following article: González-García, S., Bacenetti, J.,**  
2 **2019. Exploring the production of bio-energy from wood biomass. Italian case study. Science of**  
3 **the Total Environment 647, 158–168.**

4 **Creative commons licencing option to comply with Elsevier's requirements is Attribution-Non**  
5 **Commercial-No Derivatives (CC-BY-NC-ND)**

6  
7 **Exploring the production of bio-energy from wood biomass. Italian case study**

8 Sara González-García<sup>1\*</sup> and Jacopo Bacenetti<sup>2</sup>

9 <sup>1</sup>Department of Chemical Engineering, Institute of Technology, University of Santiago de  
10 Compostela. 15782- Santiago de Compostela, Spain.

11 <sup>2</sup>Department of Environmental Science and Policy, Università degli Studi di Milano, Via G. Celoria 2,  
12 20133-Milan, Italy

13 \* Corresponding author: E-mail address: [sara.gonzalez@usc.es](mailto:sara.gonzalez@usc.es)

14  
15 **Abstract**

16 The concerns related to the environmental impact related to energy production from fossil fuel are  
17 increasing. In this context, the substitution of fossil fuel based energy by bio-energy can be an  
18 effective solution. In this study, the production of electricity and heat in Italy in a combined heat and  
19 power plant (CHP) based on an Organic Rankine Cycle (ORC) turbine from wood based biomass both  
20 from forest and agricultural activities has been analysed considering four potential alternative  
21 scenarios to the current energy status: biomass from very short rotation forestry (VSRF) poplar and  
22 willow stands as well as residues from natural forests and from traditional poplar plantations. The  
23 evaluation has been performed by applying Life Cycle Assessment (LCA) method and an attributional  
24 cradle-to-gate approach has been followed. The expected savings of greenhouse gases emission and  
25 fossil fuels demand have been quantified, as well as derived emissions of toxic pollutants and  
26 substances responsible for acidification, eutrophication and photochemical oxidant formation. The  
27 results have been also compared with the conventional Italian scenario considering the current Italian  
28 electricity profile and heat production from natural gas. Among the different scenarios, due to the

29 lower transport distance, the use of biomass from traditional poplar plantation residues shows the  
30 lowest impact. The biomass combustion emissions are the main hotspot for several evaluated impact  
31 categories (e.g., particulate matter formation, human toxicity). In fact, when the produced bio-energy  
32 is compared to the reference system (i.e., electricity produced under the Italian electric profile) the  
33 results do not favor bio-energy systems. The results reported in this study support the idea that forest  
34 residues would be an interesting and potential feedstock for bio-energy purposes although further  
35 research is required specifically with the aim of optimizing biomass supply distances.

36

37 **Keywords:** CHP; Environmental sustainability; Forest residues; Life Cycle Assessment-LCA; Poplar;  
38 Willow

39

## 40 **1. Introduction**

41 Mitigation of climate change and derived effects is a global challenge (IPCC, 2007) motivating the  
42 international community to introduce easing strategies (Oreggioni et al., 2017). Therefore, European  
43 Union's energy and climate change plans try to avoid the use of fossil-based energy by means of the  
44 promotion of bio-energy (Directive 2009/28/EC; European Commission, 2018). In this sense, energy  
45 industries have contributed to ~32% of global CO<sub>2</sub> emission over the last 20 years (Janssens-  
46 Maenhout et al., 2012; Oreggioni et al., 2017) as well as heating and cooling processes are  
47 responsible for approximately 50% of the final European energy demand (Tsupari et al., 2017). Finally  
48 it is important to note that, in Europe, fuel combustion in energy industries is the most important  
49 contributor to anthropogenic climate change, with 28.5% of total greenhouse gases (GHG) emissions  
50 in 2015 (Eurostat, 2018).

51 Bio-energy is a critical issue for multiple reasons besides environmental concerns such as i) to  
52 guarantee energy security through a more diversified energy mix and less reliance on imported fossil-  
53 energy carriers, ii) the sustainable use of natural resources as well as iii) the need to revitalize rural  
54 economies (Buonocore et al., 2012; Börjesson Hagberg et al., 2016). Thus, an increased share of  
55 renewable energy is mandatory in energy system to satisfy the mentioned issues besides reducing  
56 greenhouse gases (GHG) emission. In addition, improvements in power plant efficiency and the  
57 incorporation of carbon capture and storage (CCS) processes are also required, receiving the latter  
58 special attention in recent years (Tsupari et al., 2017).

59 Bio-energy systems include a full range of products such as bio-ethanol, bio-diesel, biogas, electricity  
60 and heat, all of them from a large range of potential feedstocks – e.g., wood from forests, crops,  
61 seaweed and animal, forest and agricultural wastes (González-García et al., 2014). Moreover, biomass  
62 as its primary product is a versatile energy source that can be stored and converted to energy on-  
63 demand (De Meyer et al., 2014). The waste-to-energy concept is being highly promoted as a part of  
64 the efforts into sustainable development in energy sector (Ferreira et al., 2017). The use of forest and  
65 agricultural residues as well as other biomass waste from agricultural and industrial activities for bio-  
66 energy production (mainly electricity and heat) plays a key role in the energy system (Eurostat, 2015)  
67 and it is expected to increase over the next few years. According to MISE (2012), the share of energy

68 from renewable energy sources should reach in 2020 the 17% of the total national energy  
69 consumption. In this sense, there is a clear potential for increased use of wood for energy purposes in  
70 the EU, mostly related to forest residues and complementary fellings (SFC-WGII, 2008).

71 However, discrepancies also exist regarding bio-energy supply from biomass mostly due to the high  
72 cost associated to the production of biomass-based electricity (Cleary and Caspersen, 2015b).  
73 Therefore, to beat this economic barrier, many governments offer subsidies to encourage investment in  
74 bio-energy technologies. Bio-energy production costs, outside of the cost of feedstock production,  
75 tend to decrease with scale (Cameron et al., 2007; Dornburg and Faaij, 2001). Thus, supply-side  
76 funding programs frequently provide greater economic support for smaller-scale projects within a  
77 given technology class. However, the discontinuous availability and the relatively high maintenance  
78 and logistic costs hinder the economic convenience of biomass for large scale energy production (De  
79 Meyer et al., 2014). Therefore, numerous efforts are being carried out to make the whole process  
80 achievable from an economic approach (De Meyer et al., 2014)

81 Production of heat and electricity from woody residues either from forest or agricultural activities  
82 could considerably increase the contribution to energy security, reduce GHG emission and add value  
83 to waste materials (Matsumura et al., 2005; Fernandes and Costa, 2010; Aldana et al., 2014). Indeed, it  
84 is a common practice in factories such as pulp mills where pulp is generated together with heat and  
85 electricity (Sandin et al., 2015). Different studies evaluated the potential quantities of available forest  
86 biomass residues for energy production in countries such as Portugal (Fernandes and Costa, 2010;  
87 Viana et al., 2010; Lourinho and Brito, 2015) or Uganda (Okello et al., 2013). According to them, only  
88 if cogeneration is implemented the wood fuel resource should be sufficient to satisfy the required  
89 capacity demand. However, special attention must be paid into the biomass-supply competition with  
90 pellets production, one of the largest internationally traded solid biomass commodities for energy  
91 purposes mainly derived from wood residues (Sikkema et al., 2011; Monteiro et al., 2012).

92 Italy's energy profile relies to a very large extent on imports to meet its energy needs since Italian  
93 energy reserves are scarce. In this sense, Italy is a net importer of electricity and only 88.2% of  
94 demand is satisfied by a national production. Regarding its power production capacity, 15.3%

95 corresponds to hydropower and 15.9% derives from renewable sources, and the remaining is produced  
96 from fossil sources (Terna, 2016).

97 Hence, its interest on promoting a sharp increase on power production from renewable sources, being  
98 Italy considered one of the European countries (together with France, Germany, Sweden, Finland,  
99 Spain and United Kingdom) with the main bioenergy markets in 2020 (Calcante et al., 2018; Scarlat et  
100 al., 2013).

101 Poplar and willow are short rotation coppice-species most cultivated in Italy, specially in Po Valley  
102 (Northern Italy), for bio-energy and industrial (e.g., pulpwood and paper) purposes (González-García  
103 et al, 2012; Bacenetti et al., 2016). Poplar and willow cultivation (either at short rotation or very short  
104 rotation forestry regimes, SRF and VSRF respectively) includes activities such as harvesting and  
105 biomass collection, which are repeated in different times depending on the cultivation regime. Both  
106 activities involve the production of leaves and stools that, usually, remains in the plantation as nutrient  
107 and carbon supplier (González-García et al., 2012). Nevertheless, they could be used for bio-energy  
108 applications (Muth et al., 2013).

109 Traditional poplar plantation also exists in Italy mainly in Po Valley mostly destined to roundwood  
110 production for furniture sector (Verani et al., 2017). It involves a non-intensive management regime  
111 involving the production of potential woody biomass with only one harvesting event as difference to  
112 SRF and VSRF regimes.

113 In the case of Italy, forests are widespread in all the regions of the country being destined to firewood  
114 and roundwood production (Proto et al., 2017). Forestry with 10,467,000 ha cover about 34.7% of  
115 Italy (INFC, 2015). Although a variety of management systems exist for forests, shelter cut (high  
116 forest) in combination with natural regeneration is widespread. In this case, woody residues (mainly  
117 tops and brances), produced during logging operations, can be used for bio-energy applications.

118 In this study, the production of electricity and heat in Italy from wood based biomass either from  
119 forest and from agricultural activities has been analysed considering different production scenarios and  
120 final uses. The interest behind this study is the promoting use of biomass in small combustion  
121 installations in Italy as substitute for fossil fuels (Benetto et al., 2004; Caserini et al., 2010). Biomass  
122 from VSRF poplar and willow stands as well as residues from natural forests and from traditional

123 poplar plantations have been considered for analysis. Attention has been paid on dedicated energy  
124 crops (i.e., willow and poplar) due to the current Italian interest on biomass power plants.

125 The results have been also compared with the conventional Italian scenario considering the current  
126 Italian electricity profile and heat production from natural gas. The assessment has been performed by  
127 applying Life Cycle Assessment (LCA) methodology in an attributional approach and a cradle-to-  
128 power plant gate perspective. A comprehensive and transparent analysis has been performed to  
129 facilitate comparisons between the proposed bio-energy scenarios.

130

## 131 **2. Materials and methods**

132 Life Cycle Assessment (LCA) is a widely used and standardised tool for the systematic evaluation of  
133 environmental aspects of a production system through all stages of its life cycle (ISO 14040, 2006). It  
134 is considered an ideal instrument to evaluate the environmental dimension of sustainability. Numerous  
135 studies related to bio-energy production have been also used this methodology to assess their  
136 environmental consequences (Benetto et al., 2004; Keoleian and Volk, 2005; Caserini et al., 2010;  
137 Cherubini and Strømman, 2011; González-García et al., 2014; Asdrubali et al., 2015; Patel et al.,  
138 2016). Within these studies, special attention was paid into liquid fuels production being the number  
139 of published studies focused on heat and power generation slightly lower (Cherubini and Strømman,  
140 2011). However, its applicability in this area has been entirely demonstrated.

141

### 142 **2.1. Goal and scope definition**

143 This study aims to assess and compare the environmental consequences and energy requirements  
144 associated with the production of bio-energy (heat and power) for district heating systems and national  
145 grid supply from different biomass sources including energy crops derived from VSRF and forest  
146 residues. Biomass combustion is the simplest thermochemical conversion technology being heat and  
147 power (under co-generation regime) the main co-products of direct combustion of lignocellulosic  
148 material (Patel et al., 2016). Thus, different scenarios have been proposed for assessment trying to  
149 identify hotspots and differences.

150 In addition and as reference system for the comparison of the results, the production of heat  
151 considering a fossil source (i.e., natural gas) in a domestic boiler in the domestic sector as well as  
152 electricity production in the Italian national grid have been considered within the analysis to be  
153 compared with the designed scenarios proposed for analysis. The rationale behind this consideration is  
154 that the bio-energy modelled scenarios allow saving of both fossil based production routes.

155

## 156 **2.2. Functional unit**

157 The functional unit considered to report the environmental profile is 1 kWh of electricity (kWh<sub>e</sub>)  
158 produced in a combined heat and power plant (CHP) based on an Organic Rankine Cycle (ORC) and  
159 with an energy efficiency of 20% in the ORC and 85% in the boiler, regardless the biomass source.  
160 The consideration of an energy-based functional unit has also been considered in previous LCA  
161 studies available in the literature (González-García et al. 2014) allowing the comparison with  
162 alternative production systems with independence of the feedstock used (Muench and Guenther,  
163 2013).

164

## 165 **2.3. System boundaries definition**

166 An attributional cradle-to-gate approach has been followed in this study in all the scenarios proposed  
167 for analysis i.e., from raw materials extraction till the production of energy in the plant. Thus, the  
168 further use of the produced electricity has been excluded from analysis. The CHP is mainly constituted  
169 by two different sections. The first one is characterised by a biomass boiler (thermal power of 6.047  
170 MW) fed with the woody biomass while the second section is mainly constituted by a ORC turbine  
171 with 1 MW of electric power. The Organic Rankine Cycle's principle is based on a turbogenerator  
172 working as a conventional steam turbine to transform thermal energy into mechanical energy and  
173 finally into electric energy. Instead of generating steam from water, the ORC system vaporises an  
174 organic fluid, characterised by a molecular mass higher than that of water (e.g., HCFC-123 with a  
175 molecular weight of  $152.9\text{g}\cdot\text{mol}^{-1}$ ), which leads to a slower rotation of the turbine, lower pressures  
176 and no erosion of the metal parts and blades.

177 At the CHP plant, the heat produced by the biomass boiler is transferred, using a diathermic oil (310-  
178 315 °C and 6 bar), to the ORC where is transformed in mechanical power and, through a electrical  
179 generator, in electricity. More in details, the organic fluid vapor rotates the turbine, which is directly  
180 coupled to the electric generator. Afther that, the exhaust vapor flows through the regenerator, where it  
181 is then condensed in the condenser and cooled by the cooling circuit. The thermal energy used in the  
182 district heating is recovered at the condenser. The district heating distribution grid considered is  
183 around 1.5 km -length and presents a lifespan of 30 years.

184 **Figure 1** displays the foreground system boundaries corresponding to the four scenarios considered as  
185 base case studies. All electricity produced is directly fed into the Italian national grid. There is no  
186 recycling to satisfy electricity demand in the CHP unit due to technical reasons (the different electric  
187 devices for biomass loading, exhaust gas treatment, ash removal etc. must operate also when the ORC  
188 does not work for maintenance or breakages) (Fiala, 2012). Regarding heat, only the 16% of all heat  
189 produced in sent to a nearby hospital and school to satisfy heating requirements. The remaining 84%  
190 is considered as a waste since it is not recovered.

191 <**Figure 1** around here>

192 Scenario 1 (Sc1) is based on the consideration of residues from natural regeneration forestry and  
193 industrial activities as feedstock. These stands are naturally managed i.e., they are handled under low  
194 management intesity. The forest stands are untouched forests with a history of limited management  
195 (Buiteveld et al., 2007). Thus, no activities are performed throughout the lifespan (> 60 years) after  
196 initially diversifying the forest structure (Buiteveld et al., 2007). Biomass extracted is mostly  
197 dedicated as raw material (roundwood) for furniture sector. Wood residues such as tops and branches  
198 are recovered in the harvesting activities as well as throughout the lifespan of the plantation. In this  
199 scenario, these residues are considered as raw material for bio-energy production (see **Figure 1a**).  
200 Firstly, wood residues are chipped into the forestry using a self-propelled chipper and after they are  
201 transported to the bio-energy plant. Residues from furniture production activities are also considered  
202 and chipped in the plant. In this scenario, the entire environmental burdens of the multifunctional  
203 process (only derived from logging operations) are allocated to the main product (roundwood).  
204 Therefore, wood residues are considered waste and free of environmental burdens except with regard



205 to forest residues chipping and chip wood transport. This approach is sometimes deemed reasonable  
206 specially if the demand of the co-products has no influence on the production capacity of the system  
207 (Sandin et al., 2015).

208 Scenario 2 (Sc2) and Scenario 3 (Sc3) consider the biomass from VSRF stands of poplar and willow  
209 species, respectively, as feedstock for heat and power generation (see **Figure 1b**). The management of  
210 VSRF plantations has been considered within the system boundaries considering all processes  
211 performed in the stands from field preparation and management, harvesting and field recovery at the  
212 end of the lifespan of the plantations (approximately ten years in both species) in agreement with  
213 González-García et al. (2012) and Bacenetti et al. (2016). It is important to highlight that as difference  
214 to forest stands dedicated to roundwood production for industrial uses, all the produced biomass  
215 (including wood residues such as branches, stools and leaves) is recovered and sent to bio-energy  
216 production. The total trees are felled, and directly chipped on the field by means of a forage harvesters  
217 equipped for a specific header.

218 Scenario 4 (Sc4) is based on the valorisation of forest residues derived from traditional poplar stands  
219 which are mainly dedicated to the production of roundwood for pulpwood and furniture production.  
220 Wood residues are managed in the same way as in Sc1, being chipped in the power plant before their  
221 combustion in the CHP unit. All forest operations carried out in the stands have been computed within  
222 the foreground system boundaries (see **Figure 1c**). Thus, organic fertilisation, ploughing, harrowing  
223 and planting have been considered as part of field preparation activities. Herbicide and pest control,  
224 mechanical weed control, irrigation (if necessary depending on the climatic conditions) and harvesting  
225 at the end of the lifespan (12 years) have been included in stand management and harvesting stage.  
226 Finally, field recovery after the harvesting is also performed with an forestry shredder. In this scenario,  
227 economic allocation has been assumed to share out the environmental burdens derived from forest  
228 activities between both co-products (roundwood, 55 €/t and wood residues 4.5 €/t) (Lovarelli et al.,  
229 2018). The rationale behind this approach is the market interest on both co-products.

230 Within each scenario, avoided processes have also been accounted since it is assumed that biomass  
231 combustion allows savings of natural gas for heat production. Therefore, the production of the amount

232 of heat sent for final use in the surroundings (hospital and school) considering the combustion of  
233 natural gas in a domestic boiler has been contemplated

234

#### 235 **2.4 Hypotheses and Life cycle inventory**

236 A reliable environmental assessment requires the collection of high quality inventory data. The  
237 biomass conversion process into heat and power present a wide range of material and energy  
238 exchanges with the technosphere and the environment. Thus, masss and energy flows need to be  
239 estimated as well as avoided impacts related to the processes involved in each scenario. Therefore, the  
240 mass and energy flows corresponding to the foreground systems (**Figure 1**) have been modelled and  
241 quantified for each type of feedstock. A summary of the most relevant inventory data per scenario is  
242 reported in **Table 1**.

243 <**Table 1** around here>

244 The estimation of the amounts of biomass necessary to produce 1 1 kWh<sub>e</sub> (functional unit) has  
245 followed the method defined by Butnar et al. (2010) based on the power plant capacity, the operation  
246 hours, the efficiency, the low heating value (LHV) and moisture content for each biomass source  
247 (**Table 2**).

248 <**Table 2** around here>

249 Regarding the production of the feedstocks, forestry residues production (Sc1) has been excluded from  
250 the system boundaries due to the allocation of all environmental burdens derived from forestry  
251 management to the roundwood (main product). Regarding VSRF poplar and willow biomass  
252 production (Sc2 and Sc3, respectively), inventory data regarding forest activities performed in the  
253 stands have been taken from González-García et al. (2012) and Bacenetti et al.(2016), respectively. In  
254 the case of traditional poplar stands, their management has been included within the system  
255 boundaries of Sc4. The following inventory data have been accounted for: the amount of machinery  
256 needed for each specific forest process (tractors and forest equipment), fuel consumption (and  
257 production) in all forest activities (considering operating rate and diesel consumption) as well as the  
258 production of all the agro-chemical inputs to the field, such as herbicides (glyphosate and  
259 gluphosinate-ammonium) and pesticide (Deltamethrin). Regarding fertilisation, it is performed using

260 cattle manure considered as a waste in farming activities. Therefore, impacts from background  
261 activities involved in the production of this organic fertiliser have been excluded from the system  
262 boundaries. Derived emissions from organic fertiliser and agro-chemicals application have been  
263 quantified as well as combustion emissions from diesel use in the machinery. A summary of main  
264 inventory data corresponding to traditional poplar stands is reported in **Table 3**.

265 <**Table 3** around here>

266 Concerning the biomass supply till the power plant, it has been computed in the analysis. In all the  
267 scenarios it has been assumed that the power plant is placed within the Lombardy region. This region  
268 has gained relevance in the last years due to the establishment of several biomass thermoelectric  
269 power plants (Bergante et al., 2010; Lijó et al., 2017). Forestry wood residues are transported by  
270 lorries (16-32 t) an average distance of 800 km (from forestry located in Southern Italy). Poplar and  
271 willow plantations are extended around the Po Valley (Lombardy region). Thus, an average transport  
272 distance of 35 km by lorry (16-32 t) has been assumed in both cases. In the case of wood residues  
273 from traditional poplar stands, 20 km has been considered. Diesel lorries have been used for biomass  
274 transport in all the scenarios.

275 Although primary data should be used whenever possible, it is sometimes necessary to turn to  
276 secondary ones. In this study, information regarding the diesel consumed in the chipping process (Sc1  
277 and Sc4), electricity required in the CHP unit (all scenarios) as well as ashes disposal in a sanitary  
278 landfill, has been taken from the Ecoinvent ® database (Weidema et al., 2013).

279 Moreover, inventory data corresponding to the background system, which involves the production of  
280 utilities (electricity), other inputs to the foreground system (agro-chemicals, water, machinery) and  
281 infrastructure (e.g., the distribution grid) have been taken from a pre-existing database and the  
282 literature as detailed in **Table 4**.

283 <**Table 4** around here>

284  
285 Indirect emissions generated from all the different processes involved have been also included. In this  
286 sense, combustion emission factors corresponding to the biomass burning in the power plant have

287 been taken from the IPCC guidelines (IPCC, 2007) and EMEP/EEA air pollutant emission inventory  
288 guidebook (EMEP/EEA, 2013).

289

## 290 **2.5. Life Cycle Impact Assessment method**

291 Among the steps defined within the life cycle impact assessment stage of the standardised LCA  
292 methodology, only classification and characterisation stages were undertaken (ISO 14040, 2006). The  
293 characterisation factors reported by the ReCiPe Midpoint (H) 1.12 method (Goedkoop et al. 2013a)  
294 were considered to estimate the environmental impacts in this study. According to LCA experts, this  
295 method is the most updated alternative that provides a common framework in which both midpoint  
296 and endpoint indicators can be used, as opposed to similar methodologies to date (PRé Consultants  
297 2017)The implementation of the Life Cycle Inventory data has been performed in the SimaPro v8.2  
298 (PRé Consultants, 2017) software (Goedkoop et al., 2013b). The following impact categories were  
299 selected to evaluate the environmental profile of the different scenarios: climate change (CC),  
300 terrestrial acidification (TA), freshwater eutrophication (FE), marine eutrophication (ME), human  
301 toxicity (HT), photochemical oxidant formation (POF), particulate matter formation (PMF) and fossil  
302 depletion (FD). The choice of these impact categories for the environmental study is based on the fact  
303 that they are the most common categories reported in LCA studies of bioenergy systems (Cespi et al.,  
304 2014; Lijó et al., 2017).

305

## 306 **3. Environmental results and discussion**

307 The scenarios proposed for assessment have been analysed from an environmental perspective in order  
308 to identify their hotspots as well as to compare their profiles with the aim of identifying differences.  
309 The characterisation results are detailed in **Table 5**.

310

<Table 5 around here>

311 **Figure 2** displays the comparative profiles between the scenarios under assessment and the reference  
312 system (i.e., electricity production under the Italian electric profile). According to the results, all of the  
313 evaluated bio-energy scenarios involve environmental benefits in terms of impact categories such as  
314 CC and FD. According to previous studies, the substitution of fossil fuels with biomass sources to

315 produce energy requirements implies a saving of GHG emission as well as fossil fuels depletion  
316 (Caserini et al., 2010; González-García et al., 2014). Although a detailed analysis per scenario is  
317 reported below, the rationale behind these environmental benefits is linked to the avoided process  
318 included within the system boundaries. Regardless the scenario, electricity produced together with  
319 heat subsequently used (~16%) involve the avoidance of producing it from conventional way that is,  
320 from the combustion of natural gas in an domestic boiler.

321 <Figure 2 around here>

322 A discussion for each impact category is presented in the following sections. **Figure 3** depicts the  
323 main activities or processes for each impact category analysed and bio-energy scenario, as resulting  
324 from the contributions analysis. It is important to note that the amount of heat and electricity produced  
325 in all scenarios is exactly the same (see **Table 1**). Therefore, the contribution from the avoided process  
326 is also the same in terms of characterisation results. Thus, differences on the profiles are directly  
327 linked to the differences on the foreground system. Positive values in **Figure 3** are indicative of  
328 environmental burdens, whereas negative values are indicative of environmental credits/benefits  
329 derived from avoided process.

330 <Figure 3 around here>

331

### 332 **3.1. Assessment per impact category**

333 *CC*: In this impact category the CHP unit is considered as an environmental hotspot regardless the  
334 scenario under study. Although in Sc1, it is really important the effect of transport activities from  
335 forest site till the power plant, which could be expected due to the large transport distance (800 km).  
336 The contributions in the remaining scenarios from this process are not remarkable. However, attention  
337 should be paid to the feedstock production in Sc2 and Sc3 (and in Sc4 in a minor extent). In both  
338 cases, the biomass is specifically produced for bio-energy purposes under a VSRF regime involving  
339 numerous forestry activities and diesel requirements. In Sc4, poplar biomass is produced under a  
340 traditional regime, less intensive than in the other two and biomass is cultivated with other uses (e.g.  
341 furniture) being only the residues considered for bio-energy purposes. Production of electricity  
342 requirements in the CHP plant, which are directly taken from the Italian grid, is responsible for more

343 than 85% of total GHG emissions derived from this unit. In Sc2, Sc3 and Sc4, emissions from diesel  
344 combustion in forest machinery are behind the contributions from feedstock production in this impact  
345 category.

346 *TA*: Once again the CHP unit is the key factor responsible for the substances that contribute to this  
347 impact category. In this category, not only the production of electricity requirements is remarkable but  
348 also the emissions produced from diesel combustion in internal machines used in the power plant.  
349 Their contributing ratios add up to 29% and 69% of total effect from CHP unit. Forestry activities  
350 involved in the production of poplar and willow biomass (Sc2 and Sc3) are responsible for 57% and  
351 48% of acidifying substances produced all over the life cycle, respectively. Emissions from diesel use  
352 in forest machines as well as diffuse emissions derived from manure and mineral fertiliser application  
353 dominate the acidifying emissions from that stage.

354 *FE*: In this impact category the hotspot depends on the scenario assessed. In Sc1, transport activities  
355 are responsible for 80% of eutrophying emissions. However, in scenarios based on the use of energy  
356 dedicated crops (Sc2 and Sc3), feedstock production related activities are behind their outstanding  
357 contributing ratio mostly due to the application of manure as organic fertiliser and derived fertilising  
358 emissions. On the contrary, in Sc4 the hotspot is the CHP unit (~63% of total contributing substances)  
359 due to cleaning chemicals used in the plant as well as the manufacturing and maintenance of the ORC  
360 unit.

361 *ME*: Scenarios based on the use of biomass from dedicated crops, i.e., poplar and willow respectively  
362 for Sc2 and Sc3, report the worse profile in terms of this impact category being up to 10 and 7 times  
363 higher than Sc1. The rationale behind these results is the production of feedstock (see **Figure 3**).  
364 According to the cultivation description, stands are managed under very short rotation regime  
365 involving numerous fertilisation activities. Cattle manure together with urea are applied in both crops  
366 according to González-García et al. (2012) and Bacenetti et al.(2016).. Thus, diffuse emissions from  
367 fertilising dominate the contributions to this category mainly due to NH<sub>3</sub> emission derived from  
368 nutrient application. In a minor extent, NO<sub>x</sub> emissions derived from diesel combustion in the  
369 agricultural machines also are responsible substances. Regarding Sc4, the profile is lower than Sc2 and  
370 Sc3 being also the feedstock production related activities the main hotspot. However, the cultivation

371 under low intensive conditions and the considered allocation approach (only residues are managed) are  
372 responsible of the best result. In the case of Sc1, activities involved in the power plant constitute the  
373 key factor (~80% of total contributing substances). Direct N-based emissions derived from the  
374 combustion of the biomass in the boiler are the hotspot being responsible of 82% of contributions from  
375 CHP plant.

376 *HT*: As depicted in Figure 3, scenario focused on bio-energy production from forestry residues (Sc1)  
377 reports the worse profile being Sc2, Sc3 and Sc4 around 59%, 64% and 77% smaller than Sc1. The  
378 rationale behind these results is associated with transport activities of the feedstock and derived  
379 emissions from background processes involved. The distribution of feedstock by diesel lorry up to the  
380 power plant gate is the key issue in Sc1 responsible for 67% of contributing substances. In the remaining  
381 scenarios, activities carried out in the CHP plant can be considered as hotspot with contributing ratios  
382 of 57%, 61% and 80%. Emissions from the biomass combustion in the boiler (such as heavy metals  
383 and nitrogen oxides) are behind the power plant effect.

384 *POF* and *PMF*: Results in these impact categories are directly related as depicted in Figure 3. *POF*  
385 takes into account the emissions into air of substances (e.g. nitrogen dioxide, nitrogen oxides, sulfur  
386 oxides or toluene) that produce photochemical smog. Regarding *PMF*, it considers the emission of  
387 particulates as well as sulfur oxides, nitrogen oxides and ammonia, which can also produce smog.  
388 Therefore, the profiles in both impact categories regardless the scenario analysed are almost identical.  
389 In all scenarios, emissions from biomass combustion (e.g., of particulates and nitrogen oxides) in the  
390 boiler within the power plant can be considered as the hotspot. However, in Sc1 it is also outstanding  
391 the effect from biomass distribution. In the case of Sc2 and Sc3, agricultural activities required to the  
392 biomass production are remarkable in both impact categories mainly due to the use of diesel machines.

393 *FD*: This impact categories represents the consumption of fossil resources all over the life cycle.  
394 Transport activities is the hotspot in Sc1 which could be expected due to the large delivery distance  
395 (800 km), being negligible in the remaining scenarios. Diesel requirements in agricultural activities in  
396 the hotspot in Sc2 and Sc3. Numerous large machines are involved in the cultivation of VSRF poplar  
397 and willow being harvesting and chipping on field (combine harvester) the main responsible ones.

398

### 399 3.2. Comparative assessment between scenarios

400 **Figure 2** displays the comparative profiles per impact category between the scenarios considered for  
401 analysis and the reference system. As expected, improvements are achieved per functional unit (1  
402 kWh) when bio-energy systems are proposed especially in terms of GHG and fossil fuels savings  
403 (CC and FD respectively). In this sense, the use of wood residues from traditional poplar stands  
404 derives on the best profiles not only in terms of CC and FD but also in PMF and TA. The short  
405 transport distance considered for the biomass supply (20 km) to the power plant as well as the low  
406 allocation ratio to share the impact from poplar stands between the residues and the main product (i.e.,  
407 roundwood) are behind these results in spite of producing the largest amount of ashes. According to  
408 the results, effect on the profiles, regardless the scenario, from ashes disposal in a landfill is negligible  
409 (see **Figure 3**). Landfilling is a common practice in Italy, and harmful effects may be caused by the  
410 release of heavy metals (Cespi et al., 2014) as well as unpleasant odors and groundwater pollution  
411 from leachate formation if not well controlled (Calvo et al., 2005).

412 In the remaining impact categories and in general lines, the results do not benefit bio-energy systems,  
413 achieving the reference system (i.e., electricity produced under the Italian electric profile) the best  
414 profiles (specifically in HT, ME and FE) in line with other studies (Caserini et al., 2010). Biomass  
415 combustion is associated with higher impacts than fossil fuels use, due to higher emissions of toxic  
416 substances. Background processes are also implicated in these results due to agricultural activities.

417 Finally, normalisation factors established by ReCiPe Midpoint (H) 1.12 method (Goedkoop et al.  
418 2013a) have been considered in order to obtain an index per scenario and to perform a direct  
419 comparison between scenarios. **Figure 4** depicts the comparative profiles. According to it, the indexes  
420 show that shifting from fossil fuels based energy by renewable one can be or not more environmental  
421 friendly and an specific analysis is mandatory due to the influence of assumptions and bio-energy  
422 system characteristics. The use of dedicated crops (Sc2 and Sc3) contribute to increase the  
423 environmental index as well as the biomass distribution from large distances (Sc1) even though  
424 residues were managed. However and although the use of wood residues for power and heat  
425 production is interesting from environmental and energy perspectives, further analysis should be  
426 focused on the availability of these sources and their ability to meet energy requirements. The results



427 reported in this study support the idea - as also reported in other studies (Caserini et al., 2010; Cespi et  
428 al., 2014; González-García et al., 2014) that the use of agricultural and forest residues could provide a  
429 potential available raw material for bio-energy production. However, more research and technological  
430 development is required to promote their use. Moreover, dedicated crops are interesting due to their  
431 high production yields, guaranteed availability and added benefits such as contributions to rural  
432 development, landscape diversity and reduced erosion potential (Heller et al., 2004). However, more  
433 exploration is necessary to reduce the impacts derived from background processes involved in  
434 agricultural activities (Bacenetti et al., 2018).

435 <Figure 4 around here>

436

### 437 **3.3. Alternative scenarios**

438 In the scenarios considered for analysis, only 16% of total heat produced in the CHP plant is finally  
439 used being the remaining 84% wasted into air. However, it should be interesting the recovery and final  
440 use of the total heat produced (e.g., it could be considered in heating systems in the surrounding  
441 areas). Thus, 14.11MJ should be produced per kWhe, which should avoid the production of that  
442 amount of heat from natural gas. Moreover, electricity requirements in the power plant are directly  
443 taken from the national grid. However, it could be feasible to satisfy its electricity requirements (0.24  
444 kWhe) recycling it from the electricity produced, being 0.76 kWhe sent to the national grid. The  
445 consideration of both hypothesis has been considered for analysis and **Figure 5** displays the  
446 comparative profiles between the bio-energy scenarios and the alternative ones considering a normalised  
447 index. Taking in mind the results, it is demonstrated the environmental benefits of producing both heat  
448 and electricity from wood residues and dedicated crops in comparison with the current national  
449 electric profile. In this sense, environmental credits could be achieved mostly using wood residues  
450 from traditional poplar stands and willow-based biomass.

451 <Figure 5 around here>

452

### 453 **3.4. Transport effect**

454 The effect of feedstock distribution activities have been remarkable in Sc1 where around 800 km have  
455 been assumed as transport distance. It is a reality since forest stands are widespread in Southern Italy.  
456 However, the influence of transport distance on LCA results has just been considered in previous  
457 studies where power production was environmentally analysed (Nussbaumer and Oser, 2004; Caserini  
458 et al., 2010). In these studies, it was reported that large transport distances imply a high consumption  
459 of primary energy, which could be higher than energy produced.

460 According to INFC (2015), in Italy, forestry are widespread also in the Central Italy (Appennino and,  
461 in particular, Tuscany and Umbria regions) as well as in Northern Italy (e.g., Veneto, Trentino).  
462 Therefore, a comparative analysis has been performed to identify the benefits of processing forest  
463 residues from closer areas. Average transport distances of 300-350 km and 350-370 km have been  
464 assumed respectively for forestry residues distribution from Tuscany (ScA) and Northern Italy (ScB).  
465 **Figure 6** displays the comparative profiles considering the normalisation score. According to it,  
466 outstanding reductions of the environmental profile could be achieved of up to 40% in residues are  
467 delivered from Central Italy regions. Thus, transport distance plays a key role on the environmental  
468 profiles and could be decisive in decision making strategies.

469 <Figure 6 around here>

470

471

#### 472 **4. Conclusions and future outlook**

473 The results reported in this study support the idea that wood residues would be an interesting and  
474 potential raw material for bio-energy purposes although further research is required either from  
475 environmental and economic point of views. Wood residues from natural regeneration forest,  
476 industrial activities and traditional poplar stands seem to be favourable to dedicated energy crops in a  
477 global approach. Thus, it must be encouraged the use of forest and wood-processing residues as  
478 feedstock from a circular economy approach not only in the bio-energy sector but also in the latent  
479 bio-based industry.

480 The current efforts performed in recent years have given rise to numerous technological developments  
481 enhancing “closing the loop” strategies under a biorefinery concept through better recycling and re-

482 using the waste streams. Wood-based residues availability and low associated costs in comparison  
483 with dedicated bio-energy crops support also their interest.

484 According to the main findings from this study, LCA methodology can be considered as a valuable  
485 and useful tool to support decision making strategies under an environmental approach, specifically  
486 for systems under development such as the ones reported in this study. However, additional research  
487 should be performed not only in the environmental pillar of the sustainability but also in the social and  
488 economic ones to obtain a full overview. Moreover, attention must be paid in these categories different  
489 than climate change and fossil depletion (the ones that are subject of great public debate), considerably  
490 affected by air pollutant emissions derived from biomass combustion mostly when dedicated energy  
491 crops are considered.

492

#### 493 **Acknowledgements**

494 This research has been partially supported by a project granted by Xunta de Galicia (project ref.  
495 ED431F 2016/001) and by the STAR-ProBio project funded by the European Union's Horizon 2020  
496 Program research and innovation programme under grant agreement No. 727740.

497 S.G-G. would like to express their gratitude to the Spanish Ministry of Economy and Competitiveness  
498 for financial support (Grant references RYC-2014-14984). S.G-G. belongs to the Galician Competitive  
499 Research Group GRC 2013-032 and to CRETUS Strategic Partnership (AGRUP2015/02). All these  
500 programmes are co-funded by Xunta de Galicia and FEDER (EU).

501 Authors give thanks to the European Commission, through the Erasmus+Call 2017-KA1-Mobility of  
502 staff in higher education-Staff mobility for teaching and training activities.

503

#### 504 **References**

505 Aldana, H., Lozano, F. J., Acevedo, J. (2014). Evaluating the potential for producing energy  
506 from agricultural residues in México using MILP optimization. *Biomass and Bioenergy*, 67, 372-389.

507 Asdrubali, F., Baldinelli, G., D'Alessandro, F., & Scrucca, F. (2015). Life cycle assessment of  
508 electricity production from renewable energies: Review and results harmonization. *Renewable and*  
509 *Sustainable Energy Reviews*, 42, 1113-1122.

510 Bacenetti J., Lovarelli D., Facchinetti D., Pessina D. (2018). An environmental comparison of  
511 techniques to reduce pollutants emissions related to agricultural tractors. *Biosystems Engineering*, 171,  
512 30-40

513 Bacenetti, J., Bergante, S., Facciotto, G., Fiala, M. (2016). Woody biofuel production from  
514 short rotation coppice in Italy: Environmental-impact assessment of different species and crop  
515 management. *Biomass and Bioenergy*, 94, 209-219.

516 Benetto E, Popocivi EC, Rousseaux P, Blondin J., 2004. Life cycle assessment of fossil CO<sub>2</sub>  
517 emissions reduction scenarios in coal-biomass based electricity production. *Energy Conversion*  
518 *Management*, 24, 3053–3074.

519 Bergante, S., Facciotto, G., Minotta, G., 2010. Identification of the main site factors and  
520 management intensity affecting the establishment of short-rotationcoppices (SRC) in Northern Italy  
521 through stepwise regression analysis. *Central European Journal of Biology*, 5, 522-530.

522 Bergante, S., Manzone, M., Facciotto, G. (2016). Alternative planting method for short  
523 rotation coppice with poplar and willow. *Biomass and Bioenergy*, 87, 39-45.

524 Buiteveld, J., Vendramin, G. G., Leonardi, S., Kamer, K., Geburek, T. (2007). Genetic  
525 diversity and differentiation in European beech (*Fagus sylvatica* L.) stands varying in management  
526 history. *Forest ecology and management*, 247(1-3), 98-106.

527 Buonocore, E., Franzese, P. P., Ulgiati, S. (2012). Assessing the environmental performance  
528 and sustainability of bioenergy production in Sweden: a life cycle assessment perspective. *Energy*,  
529 37(1), 69-78.

530 Calcante, A., Facchinetti, D., Pessina, D. (2018). Analysis of Hazardous Emissions of Hand-  
531 Operated Forestry Machines Fuelled with Standard Mix or Alkylate Gasoline. *Croatian Journal of*  
532 *Forest Engineering: Journal for Theory and Application of Forestry Engineering*, 39(1), 109-116.

533 Calo, F., Moreno, B., Zamorano, M., Szanto, M., 2005. Environmental diagnosis methodology  
534 for municipial waste landfills. *Waste Management*, 25, 768-779.

535 Cameron, J. B., Kumar, A., Flynn, P. C. (2007). The impact of feedstock cost on technology  
536 selection and optimum size. *Biomass and Bioenergy*, 31(2-3), 137-144.

537 Caserini, S., Livio, S., Giugliano, M., Grosso, M., Rigamonti, L. (2010). LCA of domestic and  
538 centralized biomass combustion: the case of Lombardy (Italy). *Biomass and Bioenergy*, 34(4), 474-  
539 482.

540 Cespi, D., Passarini, F., Ciacci, L., Vassura, I., Castellani, V., Collina, E., Morselli, L. (2014).  
541 Heating systems LCA: comparison of biomass-based appliances. *The International Journal of Life*  
542 *Cycle Assessment*, 19(1), 89-99.

543 Cherubini, F., Strømman, A. H. (2011). Life cycle assessment of bioenergy systems: state of  
544 the art and future challenges. *Bioresource technology*, 102(2), 437-451.

545 Cleary, J., Caspersen, J. P. (2015). Comparing the life cycle impacts of using harvest residue  
546 as feedstock for small-and large-scale bioenergy systems (part I). *Energy*, 88, 917-926.

547 Cleary, J., Wolf, D. P., Caspersen, J. P. (2015). Comparing the life cycle costs of using harvest  
548 residue as feedstock for small-and large-scale bioenergy systems (part II). *Energy*, 86, 539-547.

549 De Meyer, A., Cattrysse, D., Rasinmäki, J., Van Orshoven, J. (2014). Methods to optimise the  
550 design and management of biomass-for-bioenergy supply chains: A review. *Renewable and*  
551 *sustainable energy reviews*, 31, 657-670.

552 Directive 2009/28/EC, 2009. Directive 2009/28/EC of the European Parliament and of the  
553 Council of 23 April 2009 on the promotion of the use of energy from renewable sources and amending  
554 and subsequently repealing Directives 2001/77/EC and 2003/30/EC. *Off. J. Eur. Union*. L140/16-62

555 Djomo, S. N., Ac, A., Zenone, T., De Groot, T., Bergante, S., Faccioto, G., Ceulemans, R.  
556 (2015). Energy performances of intensive and extensive short rotation cropping systems for woody  
557 biomass production in the EU. *Renewable and Sustainable Energy Reviews*, 41, 845-854.

558 Dornburg, V., Faaij, A. P. (2001). Efficiency and economy of wood-fired biomass energy  
559 systems in relation to scale regarding heat and power generation using combustion and gasification  
560 technologies. *Biomass and Bioenergy*, 21(2), 91-108.

561 Eurostat, 2015. SHARES 2015 - Short Assessment of Renewable Energy Sources

562 Eurostat, 2018. [http://ec.europa.eu/eurostat/statistics-](http://ec.europa.eu/eurostat/statistics-explained/index.php/Europe_2020_indicators_-_climate_change_and_energy)  
563 [explained/index.php/Europe\\_2020\\_indicators\\_-\\_climate\\_change\\_and\\_energy](http://ec.europa.eu/eurostat/statistics-explained/index.php/Europe_2020_indicators_-_climate_change_and_energy) (accessed 23 April,  
564 2018)

- 565           Fernandes, U., Costa, M. (2010). Potential of biomass residues for energy production and  
566 utilization in a region of Portugal. *Biomass and Bioenergy*, 34(5), 661-666.
- 567           Ferreira, S., Monteiro, E., Brito, P., Vilarinho, C. (2017). Biomass resources in Portugal:  
568 Current status and prospects. *Renewable and Sustainable Energy Reviews*, 78, 1221-1235.
- 569           Fiala, M., 2012. *Energia da biomasse*, Maggioli Editore. 1 – 437.
- 570           Goedkoop M, Heijungs R, Huijbregts M, De Schryver A, Struijs J. van Zelm R (2013a).  
571 ReCiPe 2008. A life cycle impact assessment method which comprises harmonised category indicators  
572 at the midpoint and the endpoint level. Report I: Characterisation. 1st ed. (version 1.08)
- 573           Goedkoop, M., Oele, M., Leijting, J., Ponsioen, T., Meijer, E., 2013b. Introduction to LCA  
574 with SimaPro 8. PRÉ Consultants. The Netherlands
- 575           González-García, S., Bacenetti, J., Murphy, R. J., Fiala, M. (2012). Present and future  
576 environmental impact of poplar cultivation in the Po Valley (Italy) under different crop management  
577 systems. *Journal of cleaner production*, 26, 56-66.
- 578           González-García, S., Dias, A. C., Clermidy, S., Benoist, A., Maurel, V. B., Gasol, C. M.,  
579 Arroja, L. (2014). Comparative environmental and energy profiles of potential bioenergy production  
580 chains in Southern Europe. *Journal of cleaner production*, 76, 42-54.
- 581           Hagberg, M. B., Pettersson, K., Ahlgren, E. O. (2016). Bioenergy futures in Sweden—  
582 Modeling integration scenarios for biofuel production. *Energy*, 109, 1026-1039.
- 583           INFC - Inventario Nazionale delle Foreste e dei Serbatoi Forestali di Carbonio. (2015).  
584 Estensione e composizione dei boschi.  
585 [https://www.sian.it/inventarioforestale/jsp/01tabelle\\_superficie.jsp](https://www.sian.it/inventarioforestale/jsp/01tabelle_superficie.jsp) (accessed 03 May 2018)
- 586           IPCC, 2007. IPCC Climate Change 2007: The Physical Science Basis. Cambridge University  
587 Press, Cambridge.
- 588           Janssens-Maenhout, G., Dentener, F., Van Aardenne, J., Monni, S., Pagliari, V., Orlandini, L.,  
589 Klimont, Z., Kurokawa, J., Akimoto, H., Ohara, T., Wankmueller, R., Battye, B., Grano, D., Zuber, A.,  
590 Keating, T., 2012. EDGAR-HTAP: A Harmonized Gridded Air Pollution Emission Dataset Based on  
591 National Inventories. European Commission Publications Office, Ispra, Italy, JRC68434, EUR  
592 report No EUR 25 299-2012, ISBN 978-92-79-23122-0, ISSN 1831-9424.

593 Keoleian, G.A., Volk, T.A., 2005. Renewable Energy from Willow Biomass Crops: Life  
594 Cycle Energy, Environmental and Economic Performance. *Critical Reviews in Plant Sciences* 24, 385-  
595 406.

596 Lijó, L., González-García, S., Bacenetti, J., Moreira, M. T. (2017). The environmental effect  
597 of substituting energy crops for food waste as feedstock for biogas production. *Energy*, 137, 1130-  
598 1143.

599 Lijó, L., Lorenzo-Toja, Y., González-García, S., Bacenetti, J., Negri, M., Moreira, M.T., 2017.  
600 Eco-efficiency assessment of farm-scaled biogas plants. *Bioresource Technology*, 237, 146-155.

601 Lourinho, G., Brito, P. (2015). Assessment of biomass energy potential in a region of Portugal  
602 (Alto Alentejo). *Energy*, 81, 189-201.

603 Lovarelli D., Fusi A., Pretolani R., Bacenetti J. 2018. Delving the environmental impact of  
604 roundwood production from poplar plantations. *Science of the Total Environment*, 645: 646-654.

605 Matsumura, Y., Minowa, T., Yamamoto, H. (2005). Amount, availability, and potential use of  
606 rice straw (agricultural residue) biomass as an energy resource in Japan. *Biomass and Bioenergy*,  
607 29(5), 347-354.

608 MISE - Ministero dello Sviluppo Economico (2012). Decreto ministeriale 6 luglio 2012 ed  
609 allegati - Incentivi per energia da fonti rinnovabili elettriche non fotovoltaiche.  
610 ([http://www.sviluppoeconomico.gov.it/images/stories/normativa/DM\\_6\\_luglio\\_2012\\_sf.pdf](http://www.sviluppoeconomico.gov.it/images/stories/normativa/DM_6_luglio_2012_sf.pdf))

611 Monteiro, E., Mantha, V., Rouboa, A. (2012). Portuguese pellets market: Analysis of the  
612 production and utilization constrains. *Energy Policy*, 42, 129-135.

613 Muench, S., Guenther, E. (2013). A systematic review of bioenergy life cycle  
614 assessments. *Applied Energy*, 112, 257-273.

615 Muth Jr, D. J., Bryden, K. M., Nelson, R. G. (2013). Sustainable agricultural residue removal  
616 for bioenergy: A spatially comprehensive US national assessment. *Applied Energy*, 102, 403-417.

617 Nussbaumer T, Oser M. Evaluation of biomass combustion based energy systems by  
618 cumulative energy demand and energy yield coefficient, International Energy Agency IEA bioenergy  
619 Task 32 and Swiss Federal Office of energy. Version 1.0. Zurich: Verenum press; 2004.

620 Okello, C., Pindozi, S., Faugno, S., Boccia, L. (2013). Bioenergy potential of agricultural and  
621 forest residues in Uganda. *Biomass and Bioenergy*, 56, 515-525.

622 Oreggioni, G. D., Singh, B., Cherubini, F., Guest, G., Lausselet, C., Luberti, M., Strømman,  
623 A. H. (2017). Environmental assessment of biomass gasification combined heat and power plants with  
624 absorptive and adsorptive carbon capture units in Norway. *International Journal of Greenhouse Gas*  
625 *Control*, 57, 162-172.

626 Patel, M., Zhang, X., Kumar, A. (2016). Techno-economic and life cycle assessment on  
627 lignocellulosic biomass thermochemical conversion technologies: A review. *Renewable and*  
628 *Sustainable Energy Reviews*, 53, 1486-1499.

629 PRÉ Consultants 2016. *SimaPro Database Manual – Methods library*. The Netherlands

630 Proto, A. R., Bacenetti, J., Macrì, G., Zimbalatti, G. (2017). Roundwood and bioenergy  
631 production from forestry: Environmental impact assessment considering different logging systems.  
632 *Journal of Cleaner Production*, 165, 1485-1498.

633 Sandin, G., Røyne, F., Berlin, J., Peters, G. M., Svanström, M. (2015). Allocation in LCAs of  
634 biorefinery products: implications for results and decision-making. *Journal of Cleaner Production*, 93,  
635 213-221.

636 Sandin, G., Røyne, F., Berlin, J., Peters, G. M., Svanström, M. (2015). Allocation in LCAs of  
637 biorefinery products: implications for results and decision-making. *Journal of Cleaner Production*, 93,  
638 213-221.

639 Scarlat, N., Dallemand, J. F., Motola, V., Monforti-Ferrario, F. (2013). Bioenergy production  
640 and use in Italy: Recent developments, perspectives and potential. *Renewable energy*, 57, 448-461.

641 SFC- WGII, 2008.  
642 [https://ec.europa.eu/agriculture/sites/agriculture/files/fore/publi/sfc\\_wgii\\_final\\_report\\_072008\\_en.pdf](https://ec.europa.eu/agriculture/sites/agriculture/files/fore/publi/sfc_wgii_final_report_072008_en.pdf)  
643 (accessed 23 April, 2018)

644 Sikkema, R., Steiner, M., Junginger, M., Hiegl, W., Hansen, M. T., Faaij, A. (2011). The  
645 European wood pellet markets: current status and prospects for 2020. *Biofuels, Bioproducts and*  
646 *Biorefining*, 5(3), 250-278.

647 Terna, 2016. <http://download.terna.it/terna/0000/0994/85.PDF> (accessed 03 May 2018)



648           Tsupari, E., Arponen, T., Hankalin, V., Kärki, J., Kouri, S. (2017). Feasibility comparison of  
649 bioenergy and CO2 capture and storage in a large combined heat, power and cooling system. *Energy*,  
650 139, 1040-1051.

651           Verani, S., Sperandio, G., Civitarese, V., Spinelli, R. (2017). La meccanizzazione nella  
652 raccolta di impianti di arboricoltura da legno: produttività di lavoro e costi. *Forest@-Journal of*  
653 *Silviculture and Forest Ecology*, 14(1), 237.

654           Viana, H., Cohen, W. B., Lopes, D., Aranha, J. (2010). Assessment of forest biomass for use  
655 as energy. GIS-based analysis of geographical availability and locations of wood-fired power plants in  
656 Portugal. *Applied Energy*, 87(8), 2551-2560.

657           Weidema, B.P., Bauer, C., Hischer, R., Mutel, C., Nemecek, T., Reinhard, J., Vadenbo, C.O.,  
658 Wernet, G., 2013. Overview and methodology. Data quality guideline for the ecoinvent database  
659 version 3. *Ecoinvent Report 1(v3)*. St. Gallen: The Ecoinvent Centre.