



An aggregation method for solving group multi-criteria decision-making problems with single-valued neutrosophic sets

Mariya A. Sodenkamp^a, Madjid Tavana^{b,c,*1}, Debora Di Caprio^{d,e}

^a Business Information Systems, Faculty of Business Information Systems and Applied Computer Sciences, University of Bamberg, Germany

^b Distinguished Chair of Business Analytics, Business Systems and Analytics Department La Salle University, Philadelphia, PA 19141, USA

^c Business Information Systems Department, Faculty of Business Administration and Economics University of Paderborn, D-33098 Paderborn, Germany

^d Department of Mathematics and Statistics, York University, Toronto, M3J 1P3, Canada

^e Polo Tecnologico IISS G. Galilei, Via Cadorna 14, 39100, Bolzano, Italy



ARTICLE INFO

Article history:

Received 17 October 2017

Received in revised form 21 May 2018

Accepted 11 July 2018

Available online 14 August 2018

Keywords:

Group multi-criteria decision-making

Uncertainty modeling

Reliability

Single-valued neutrosophic set

Fuzzy set

ABSTRACT

We develop a novel method that uses single-valued neutrosophic sets (NSs) to handle independent multi-source uncertainty measures affecting the reliability of experts' assessments in group multi-criteria decision-making (GMCDM) problems. NSs are characterized by three independent membership magnitudes (falsity, truth and indeterminacy) and can be employed to model situations characterized by complex uncertainty. In the proposed approach, the neutrosophic indicators are defined to explicitly reflect DMs' credibility (voting power), inconsistencies/errors inherent to the assessing process, and DMs' confidence in their own evaluation abilities. In contrast with most of the existing studies, single-valued NSs are used not only to formalize the uncertainty affecting DMs' priorities, but also to aggregate them into group estimates without the need to define neutrosophic decision matrices or aggregation operators. Group estimates are synthesized into crisp evaluations through a two-step denutrosophication process that converts (1) single-valued NSs in fuzzy sets (FSs) using the standard Euclidean metric and (2) FSs in representative crisp values using defuzzification. Theoretical and practical implications are discussed to highlight the flexibility of the proposed approach. An illustrative example shows how taking into account the uncertainty inherent to the experts' evaluations may deeply affect the results obtained in a standard fuzzy environment even when dealing with very simple ranking problems.

© 2018 Elsevier B.V. All rights reserved.

1. Introduction

Multi-criteria decision-making (MCDM) is a collection of tools and methods used to solve problems with multiple and often conflicting criteria. Group decision-making is the process of making a decision based on feedback from more than one decision maker (DM). Group MCDM (GMCDM) is a complex process involving multiple criteria and multiple DMs. This complexity is amplified when the process involves qualitative and quantitative judgments on the potential alternatives with respect to the relevant criteria. These judgments are often vague and contradictory, and significantly complicate the construction of knowledge-based rules and the establishment of decision support procedures. Vagueness can

occur under the following six circumstances: (1) the words that are used in antecedents and consequents of evaluation rules can mean different things to different people [1,2]; (2) consequences obtained by polling a group of experts are often different for the same rule or statement because the experts are not necessarily in agreement [3,4]; (3) decision groups are often heterogeneous due to the different extent of its members' expertise, knowledge and experience [5,6]; (4) expert estimates of criteria importance or performance of alternatives with respect to intangible parameters are not always consistent [7]; (5) information provided by individuals is usually incomplete or ill-defined [8,9]; and, (6) DMs are not always confident about the correctness of their own reasoning [10].

Fundamentally, uncertainty is an attribute of information [11]. There are two main types of uncertainties: external and internal. The *external (or stochastic) uncertainty* implies that the events or statements are well defined, but the state of the system or environmental conditions lying beyond the control of the DM might not be known completely. The *internal uncertainty (or fuzziness)* refers to the vagueness concerning the description of the semantic meaning

* Corresponding author at: Distinguished Chair of Business Analytics, La Salle University, Philadelphia, PA 19141, USA.

E-mail addresses: Mariya.Sodenkamp@uni-bamberg.de (M.A. Sodenkamp), tavana@lasalle.edu (M. Tavana), dicaper@mathstat.yorku.ca (D. Di Caprio).

¹ Web: <http://tavana.us>.

of events, phenomena, or statements themselves, including uncertainties about DM preferences, imprecise judgments and ambiguity of information [12,13]. In this regard, Zadeh [14, p. 28] wrote: "As the complexity of a system increases, our ability to make precise and yet significant statements about its behavior diminishes until a threshold is reached when precision and significance (relevance) become almost mutually exclusive characteristics." Therefore, precise quantitative analysis is not likely to have much relevance in problems which involve humans either as individuals or in groups.

The presence of multiple vague measures in GMCDM has continued to challenge researchers and the problems associated with finding a comprehensive approach to modeling ambiguous information has still not been adequately resolved. In the sense of Ackoff [15], the problem of having ill-defined goals, ill-defined procedures or ill-defined data is a *mess*. Several theories have emerged during the last 50 years that generalize traditional probability theory and are more appropriate for not-probabilistic information formats in which evidence about uncertainty appears. These include Chiquet's theory of capacities, random set theory, evidence theory, possibility theory, Walley's theory of imprecise probabilities, fuzzy set (FS) theory, rough set theory, intuitionistic fuzzy set (IFS) theory and neutrosophic set (NS) theory, among others [16–21].

The most commonly used methodology for representing and manipulating imprecise and uncertain information in multi-criteria decision systems is the theory of FSs. However, while focusing on the membership grade (i.e., truthfulness or possibility) of vague parameters or events, FSs fail to consider falsity and indeterminacy magnitudes of measured responses. In practical terms, the problem of projecting multi-source and multivariate group decision uncertainty using mathematical models remains intractable in terms of FSs. In the late 90s Atanassov [17] introduced and developed the idea of IFSs, intuitionistic logic and intuitionistic algebra allowing for more complex mental constructs and semantic uncertainties. In addition to the membership grade, IFSs consider non-membership levels. However, IFSs cannot handle all uncertainty cases, particularly paradoxes. NSs are the cutting-edge concept first introduced by Smarandache [20] in the late 90s and developed in the 21st century. NSs generalize FSs and IFSs. NSs and, in particular, single-valued NSs are characterized by three independent membership magnitudes, namely, falsity, truth and indeterminacy. Such a formulation allows to model the most general cases of ambiguity, including paradoxes.

1.1. Contribution

This paper proposes a new approach to represent multi-source uncertainty of estimates provided by various domain experts in MCDM problems, and a methodology to integrate these measures within one decision support procedure.

Most of the existing studies on neutrosophic approaches to GMCDM problems focus on the development of aggregation operators to be applied to neutrosophic decision matrices in order to obtain group estimates of criteria and alternatives. At the same time, the truth, falsity and indeterminacy levels used to represent the uncertainty inherent to DMs' judgments are not given an explicit interpretation. These levels are usually treated as abstract triads of (non-standard) reals without highlighting their role as reliability measures or specifying the variables that they depend on.

The artificiality and routineness deriving from an overuse of aggregation operators together with the tendency to overlook a concrete interpretation for neutrosophic values within a given GMCDM problem represent a gap in the literature that need to be considered in order to investigate ways to effectively improve the applicability of decision-making processes.

The proposed GMCDM approach aims at increasing reliability, coherence and dependability of the final outcome by accounting for three different and independent reliability measures that can affect DMs' estimates, namely, DMs' credibility, inconsistency inherent to DMs' evaluation processes, and DMs' confidence in their own evaluation abilities. In order to do so, an assessment procedure for overall priorities of criteria and alternatives is developed using the technology of single-valued NSs.

More precisely, given a committee of M heterogeneous DMs/experts who must evaluate the performance of a set of I alternatives with respect to J criteria, we deal with the following problem.

Problem:

- **Assumption:** Let experts' estimates of the objects (I alternatives and J criteria) be affected by three diverse and independent factors: first, the experts have different credibility (i.e., voting power); second, the local priorities that are derived using relative comparison judgments are characterized by an inconsistency or an error measure; third, due to the lack of information or scarce experience, some experts do not feel confident about their own judgments.
- **Question:** How can these uncertainty metrics be incorporated into a coherent ranking model to increase dependability of the group decision outcome? That is, how can multi-group multi-person expert judgments affected by these uncertainty metrics be coherently formalized and synthesized to yield reliable overall rankings of the criteria and alternatives?

Until recently, modeling and handling independent multi-source uncertainties inherent to a single information unit was challenging due to the lack of appropriate formal tools. With the development of the NS and single-valued NS concepts, the problem of simultaneously handling different ambiguity indicators of one variable can be resolved by converting the values of the indicators into the truth-, falsity- and indeterminacy-membership grades of the corresponding variable. That is, the reliability of any estimate w provided by one of the expert m (i.e., the importance of a criterion or the performance of an alternative with respect to a criterion) can be expressed by a triad of independent magnitudes, $\langle \delta_w^m, \varepsilon_w^m, \theta_w^m \rangle$, where δ_w^m represents the expert's credibility, ε_w^m the inconsistencies/errors intrinsic to the expert's evaluation process and θ_w^m the expert's confidence in his/her own ability and experience to evaluate the importance of the criteria and the performance of the alternatives.

After interpreting triads of reliability measures as neutrosophic values and group estimates as single-valued NSs, a deneutrosophication process is designed to synthesize crisp values representative of group priorities which are, in turn, used to estimate the overall performance of the alternatives.

It must be noted that the proposed formulation assumes independency among the alternatives' performances, i.e., synergy effects do not occur with respect to the alternatives' joint performance. Moreover, non-linear dependencies among criteria, in terms of their importance for the achievement of the overall problem objective, are not considered.

Finally, an illustrative example is provided to show how taking into account multi-source uncertainty indicators inherent to the experts' evaluations may deeply affect the results obtained in a standard fuzzy environment even in the case of very simple ranking problems.

The remainder of this paper is structured as follows. Section 2 offers a literature review focusing the recent applications of FSs, IFSs and NSs to GMCDM problems. Section 3 outlines the key features of the proposed NS-based GMCDM approach highlighting its differences and advantages with respect to the existing models

as well as some theoretical and practical implications. Section 4 provides the necessary technical preliminaries and notations relative to FSs, IFSs, NSs, and the basic structure of a conventional GMCDM approach. Section 5 presents the aggregation and synthesizing mechanisms proposed for solving GMCDM problems with single-valued NSs. Section 6 presents an illustrative example to demonstrate the applicability of the proposed method. Finally, Section 7 draws the conclusion and some future research directions.

2. Applications of FSs/IFSs/NSs to GMCDM in the current literature

Complex problem solving is associated with the gathering of interest groups or experts to discuss the critical issues, such as for conflict resolution, for planning and design, for policy formation or for plan brainstorming [22,23]. Multi-criteria decision-making methods are an important set of tools for addressing challenging business decisions since they allow managers to better proceed in the face of uncertainty, complexity, and conflicting objectives [24]. Group multi-criteria decision support systems emerged in the late 80s. They rely on the following four elementary stages [25]: (1) an initialization stage, where the general rules of the process to follow are determined; (2) a preference elicitation stage, where the individual DM expresses her/his estimates of the local weights of criteria and alternatives; (3) a group preference aggregation stage, where an analytical and synthesizing mechanism is used in order to derive a tentative collective decision; and, (4) a conflict-resolution stage, where an effort to reach consensus or at least attempt to reduce the amount of conflict is performed.

In most of the existing literature dealing with GMCDM problems under uncertainty, appropriate variants of FSs/IFSs/NSs are adopted to represent characteristics or performance estimates of alternatives with respect to a set of attributes or criteria. The variants used in the specific GMCDM problem depend on the level of uncertainty that is assumed to affect the DMs' evaluation process within the implemented assessment method.

Given their capacity of effectively represent the gradual changes of people's recognition to a concept in a certain context [26], FSs and IFSs have been widely used to describe intangible information. Usually, fuzzy or intuitionistic fuzzy numbers (trapezoidal or triangular) are used to interpret vague or imprecise information, with their linguistic variants employed to better deal with situations characterized by the presence of qualitative indexes. However, interval-valued FSs and IFSs are also widely used.

On the other hand, neutrosophic values (i.e., single-valued NSs, simplified NSs, interval-valued NSs, neutrosophic cubic sets, neutrosophic linguistic numbers) provide an effective tool to formalize independent degrees of indeterminacy, hesitation and/or uncertainty measures characterizing DMs' estimations in many real situations.

During the last two decades, the applications of fuzzy, intuitionistic fuzzy and neutrosophic values to GMCDM have increased exponentially, with dozens of researches and practitioners using them to represent DMs' uncertain preferences and construct aggregation rules based on fuzzy logic and/or neutrosophic inference.

In general, in fuzzy GMCDM environments, fuzzy or intuitionistic fuzzy values are used to formalize the uncertainty affecting the relative weights/priorities of criteria and/or alternatives provided by a group of experts. These values are used to define pairwise comparison decision matrices whose elements are manipulated to extract the DMs' crisp local weights/priorities. These priorities are synthesized in collective ones and, subsequently, aggregated to produce the overall preference values of the alternatives [27–31].

Fuzzy and intuitionistic fuzzy preference programming methods have also been implemented to produce crisp priorities from inconsistent interval and/or fuzzy judgments [32–38].

In NS-based GMCDM approaches, neutrosophic values are used to formalize DMs' estimates and construct neutrosophic decision matrices. These matrices are usually transformed in order to account for the attributes/criteria classification in benefit attributes/maximizing criteria and cost attributes/minimizing criteria. The transformed matrices are aggregated using aggregation operators specifically designed. A collective matrix is obtained and its elements are aggregated again to get the synthesized group priorities of criteria and alternatives. Finally, a score function (often combined with an accuracy function) is computed to rank the alternatives [39–44].

Aggregation operators and score functions have also been used for developing methods to deal with GMCDM problems with fuzzy and intuitionistic fuzzy information [45–52].

Furthermore, many models use the decision matrices to define an ideal alternative against which to compare all the given alternatives. One renowned way to perform these comparisons and identify the best alternative consists in calculating the (weighted) correlation coefficient between each alternative and the ideal alternative [53,54]. Other methods for comparing and ranking alternatives that have become common in FS-, IFS- and NS-based approaches to GMCDM are based on similarity measures [55–62] and cross-entropy measures [63–68].

In general, it must be underlined the key role that aggregation operators have played over the last two decades in solving GMCDM problems with intuitionistic fuzzy and neutrosophic information. However, following the pioneering work of Yager and Xu, who first introduced weighted arithmetic/geometric average operators [69,70] and power (average) operators [71,72], most studies have focused on developing new variants of generalized aggregation operators or improving existing ones instead of investigating ways to effectively increase the intuitive applicability of the entire decision-making process.

3. Key features of the proposed NS-based GMCDM approach: theoretical and practical implications

Our approach differs from those presented in the existing literature mainly in two ways.

- i) Neutrosophic values are not used to construct the comparison matrices. The comparison matrices can be obtained through any crisp relative measurement method [73–76]. Neutrosophic values are introduced only after each DM has evaluated the local priorities to simultaneously handle three key different ambiguity indicators, namely, the credibility of the DM, the inconsistency characterizing/occurring in comparison judgments and the confidence of the DM in his/her own judgments.
- ii) The idea of ideal alternative against which to evaluate all the alternatives is replaced by the geometrical construction of an *ideal neutrosophic reliability point*, R_* , against which it is possible to compare the neutrosophic values characterizing the local priorities of criteria and alternatives.

The theoretical and practical implications of the proposed procedure are strictly related to these two points.

Regarding the first point, the triads of truth, falsity and indeterminacy degrees to associate with the single DM's estimates are defined to explicitly reflect the DM's voting power range, the consistency ratios of the comparison matrices, and the DM's self-confidence range, respectively. As a consequence, the collection of single-valued NSs constructed by collecting together all the

experts' neutrosophic values relative to a given element (criterion or alternative) provides an intuitive but theoretically sound group performance estimates aggregation mechanism, without the need to define an aggregation operator. This is one of the advantages of the proposed procedure, namely, allowing for a natural aggregation of the DMs' judgments while concretely reflecting the three aforementioned reliability measures.

As for the second point, the comparisons with the ideal reliability point, R_* , are purely geometrical: every neutrosophic value is identified with a three-dimensional point and its Euclidean distance from R_* computed. The intuitive and operational simplicity that characterizes these comparisons constitutes another clear advantage of the proposed procedure.

Moreover, these comparisons lead to the definition of a *deneutrosophication* process capable of reducing the level of uncertainty of group estimates from neutrosophic to fuzzy, so as to allow (via defuzzification) for the crisp evaluations of global priorities.

Thus, the use of a geometrical ideal reliability point has the advantage of marking an easy-to-adjust link between the aggregation of uncertain local priorities and the syntheses of crisp global priorities. That is, it could be necessary to use mathematical objects more complex than single-valued NSs in the aggregation stage and/or modify part of the synthesizing (*deneutrosophication*) process. Being able of providing a suitable geometrical interpretation of the ideal reliability point is the key to adjust the proposed method to diverse situations and account for different modelling conditions.

The proposed aggregation and synthesizing mechanisms can be extended so as to allow for more general approaches requiring to formalize higher levels of uncertainty relative to DMs' estimates. For example, trapezoidal or triangular single-valued neutrosophic numbers (NNs) could be employed in place of single-valued NSs to represent DMs' priorities. This variant of the model would require some basic adaptations concerning the interpretation of priorities as trapezoidal or triangular single-valued NNs and the defuzzification method used in the synthesizing phase (see, also, Remark 1 in Section 5). Other relatively simple extensions could be obtained using interval-valued neutrosophic numbers.

One may also want to consider reliability measures for the experts' estimates different from those proposed in the current setting. For example, the truth-membership function could represent a measure of the quantity and quality of data/information available to the single DM instead of his/her credibility (i.e., voting power). At the same time, the indeterminacy of the estimates could be a reflection of the way DMs interpret the available data/information instead of being a measure of their self-confidence. In this case, DMs would be 100% confident in their evaluating abilities; the indeterminacy would follow from DMs' subjective ratings of the relevance, usefulness, completeness and precision of the available data based on their background and technical expertise.

From a more practical viewpoint, the flexibility of the proposed method can prove useful to managers and practitioners. For example, it can be applied to collaborative supplier selection problems with the purpose of incorporating both heterogeneous uncertain data and experts' subjective judgments within a hierarchical decision making structure. Similar applications can be developed in the medical and military sectors, among others, for assisting managers in the organization of human resources or the assessment of projects to be financed.

4. Technical preliminaries and notations

In this section, the foundations and differences among the most significant formal theories dealing with vague and imprecise information (primarily of the "internal" type) in humanistic

decision-making systems are discussed. Afterwards, the conventional GMCDM approach to the problem of ranking a set of alternatives with respect to a set of selected evaluation criteria is outlined.

4.1. Basic notions of fuzzy sets

FS theory was first introduced by Zadeh in 1965 to formalize the gradedness in class membership, in connection with the representation of human knowledge ("linguistic" uncertainty) and uncertainty about facts [77]. Since then, FS have been relevant in the three types of information-driven tasks: decision-making problems, classification and data analysis, and approximate reasoning, for measuring degrees of similarity, preference and uncertainty [78]. FSs generalize ordinary (crisp, non-ambiguous) sets since elements can belong to them only partially according to the degree of "belonging" defined by a membership function.

Definition 1. (FS [11,18]). Let X be a universal space of points (objects) and x be a generic element of X . A FS $\tilde{E} \subset X$ is characterized by a membership function $\mu_{\tilde{E}}(x) : X \rightarrow [0, 1]$, with the real value of $\mu_{\tilde{E}}(x)$ at x representing the "grade of membership" of x in \tilde{E} .

A general continuous FS has the following representation: $\tilde{E} = \{(x|\mu_{\tilde{E}}(x)) : x \in X\}$. A finite FS is represented by a set of ordered pairs: $\tilde{E} = \{(x_1|\mu_{\tilde{E}}(x_1)), (x_2|\mu_{\tilde{E}}(x_2)), \dots, (x_M|\mu_{\tilde{E}}(x_M))\}$, where M denotes the number of elements in X .

Property 1. $\int_{x \in X} \mu_{\tilde{E}}(x)dx$ is non-negative and can be smaller or larger than unity. In the discrete case, $0 \leq \sum_{m=1}^M \mu_{\tilde{E}}(x) \leq M$. Mathematically, this property illustrates the fundamental difference between the membership grade $\mu_{\tilde{E}}(x)$ (sometimes also called possibility) and statistical probability $p_E(x)$ of the element or event $x \in X$, since $\int_{x \in X} p_E(x)dx = 1$.

Property 2. An element $x \in X$ completely belongs (does not belong; partially belongs) to the FS \tilde{E} if and only if $\mu_{\tilde{E}}(x) = 1$ ($\mu_{\tilde{E}}(x) = 0$; $0 < \mu_{\tilde{E}}(x) < 1$). If, $\forall x \in X$, $[\mu_{\tilde{E}}(x) = 0 \text{ or } \mu_{\tilde{E}}(x) = 1]$, then \tilde{E} is an ordinary (crisp) set.

Definition 2. (Defuzzification [11,18]). Defuzzification is a process mapping a FS \tilde{E} into a single crisp output $e_* \in \mathbb{R}^1$. That is, the set of pairs $\{(x|\mu_{\tilde{E}}(x)) : x \in X\}$ is reduced to a single scalar quantity e_* , which is a representative value of \tilde{E} . The non-fuzzy (crisp) value e_* best represents the possibility distribution of an inferred fuzzy action, so that certain concepts become clear, and certain goals and constraints are considered more relevant.

Van Leekwijck and Kerre [18] offer a survey of the existing defuzzification techniques classifying them into the three classes: maxima methods, distribution methods, and area methods. The most commonly applied defuzzification method is given by the center of gravity (COG):

$$\text{COG}(\tilde{E}) = \frac{\int_{x \in X} x \cdot \mu_{\tilde{E}}(x)dx}{\int_{x \in X} \mu_{\tilde{E}}(x)dx}; \text{COG}(\tilde{E}) = \frac{\sum_{x \in X} x \cdot \mu_{\tilde{E}}(x)}{\sum_{x \in X} \mu_{\tilde{E}}(x)} \quad (1)$$

(for continuous sets)(for discrete sets)

4.2. Basic notions of intuitionistic fuzzy sets

IFSs [17] extend FSs, as for each imprecise value, event or function along with a membership grade is defined a corresponding

not-membership one. It is important to mention that both membership and not-membership grades are interconnected and that IFSs cannot handle indeterminate information.

Definition 3. (IFS [17]). Let X be a fixed set. An IFS $\dot{E} \subset X$ is an object of the following form: $\dot{E} = \{(x, \mu_{\dot{E}}(x), \nu_{\dot{E}}(x)) : x \in X\}$, where the functions $\mu_{\dot{E}}(x) : X \rightarrow [0, 1]$ and $\nu_{\dot{E}}(x) : X \rightarrow [0, 1]$ determine the degree of membership and the degree of not-membership of the element $x \in X$, respectively.

Property 3. Given a IFS \dot{E} , $0 \leq \mu_{\dot{E}}(x) + \nu_{\dot{E}}(x) \leq 1$, $\forall x \in X$. Indeterminacy is defined as $1 - \mu_{\dot{E}}(x) - \nu_{\dot{E}}(x)$ by default.

4.3. Basic notions of neutrosophic sets

NS theory is a formal framework proposed by Smarandache in 1999. NSs are part of neutrosophy which studies the origin, nature, and scope of neutralities, as well as their interactions with different ideational spectra [20]. It generalizes the concepts of ordinary set, FS and IFS. In contrast to IFSs, in NSs, indeterminacy is quantified explicitly, while truth-, falsity-and indeterminacy-membership functions are assumed independent. This assumption is very important in information fusion situations where it is necessary to combine data from different, possibly conflicting sources, e.g. sensors [79,80].

Definition 4. (NS). Let X be a universal space of points (objects) and x be a generic element of X . A NS $N \subset X$ is characterized by a truth-membership function $T_N(x) : X \rightarrow]0^-, 1^+[,$ a falsity-membership function $F_N(x) : X \rightarrow]0^-, 1^+[,$ and an indeterminacy-membership function $I_N(x) : X \rightarrow]0^-, 1^+[$. $T_N(x)$, $F_N(x)$ and $I_N(x)$ are real, standard or non-standard subsets of $]0^-, 1^+[$.

The set $I_N(x)$ may represent not only indeterminacy but also vagueness, uncertainty, imprecision, error, contradiction, undefined, unknown, incompleteness, redundancy, etc. [81,82]. Moreover, in order to better reflect vague information [79], the indeterminacy $I_N(x)$ can be split into subcomponents, such as “contradiction”, “uncertainty”, “unknown”, and so on.

Property 4. $T_N(x)$, $F_N(x)$ and $I_N(x)$ are independent and $0^- < \sup T_N(x) + \sup F_N(x) + \sup I_N(x) < 3^+$.

Definition 5. (Single-valued NS [80]). Let X be a universal space of points (objects) and x be a generic element of X . A single-valued NS $\tilde{N} \subset X$ is a NS on X whose truth-, falsity- and indeterminacy-membership functions are such that, $\forall x \in X$, $T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x) \in [0, 1]$.

Property 5. Given a single-valued NS \tilde{N} , $0 < \sup T_{\tilde{N}}(x) + \sup F_{\tilde{N}}(x) + \sup I_{\tilde{N}}(x) < 3$, $\forall x \in X$.

A single-valued NS \tilde{N} can be written as $\tilde{N} = \int_x \langle T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x) \rangle / x$, $\forall x \in X$, when X is continuous, and as $\tilde{N} = \sum_{m=1}^M \langle T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x) \rangle / x$, $\forall x \in X$, when X is discrete.

By analogy with FSs, a general single-valued NS has the following representation: $\tilde{N} = \{(x|T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x)) : x \in X\}$. A finite single-valued NS is represented by a set of ordered tetrads: $\tilde{N} = \{(x_1|T_{\tilde{N}}(x_1), F_{\tilde{N}}(x_1), I_{\tilde{N}}(x_1)), \dots, (x_M|T_{\tilde{N}}(x_M), F_{\tilde{N}}(x_M), I_{\tilde{N}}(x_M))\}$, where M denotes the number of elements in X .

A unique feature of neutrosophy is that it can be used for modelling paradoxes. “The paradox is the only proposition true and false in the same time in the same world, and indeterminate as well” [10, p.13].

Definition 6. (Deneutrosophication). Deneutrosophication of a single-valued NS \tilde{N} is a process mapping \tilde{N} into a single crisp output $\eta_* \in \mathbb{R}^1$. If \tilde{N} is discrete, the vector of tetrads $\{(x|T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x)) : x \in X\}$ is reduced to a single scalar quantity η_* , which is a representative value of \tilde{N} . The crisp value η_* is the one that best represents the aggregate distribution of the three membership measures $\langle T_{\tilde{N}}(x), F_{\tilde{N}}(x), I_{\tilde{N}}(x) \rangle$ relative to an inferred neutrosophic element.

4.4. Conventional group multi-criteria decision-making approach

Let there be I discrete alternatives available for the selection, J intangible evaluation criteria, and M experts responsible for assigning importance weights to the criteria, as well as for estimating the performance of the alternatives with respect to the criteria. More precisely, let:

$DM^1, DM^2, \dots, DM^m, \dots, DM^M$	denote the domain experts involved in the decision process;
$A_1, A_2, \dots, A_i, \dots, A_I$	denote the alternatives under consideration;
$C_1, C_2, \dots, C_j, \dots, C_J$	denote the criteria used for evaluating the alternatives.

Usually, a methodology that relies on a comparison principle, such as the Analytic Hierarchy Process (AHP) [7] or the Analytic Network Process (ANP) [75], is used by the experts in order to estimate the single alternatives with respect to each criterion.

Each expert DM^m constructs $J + 1$ square matrices of pair-wise comparison ratios for the set of criteria ($B_{J \times J}^m$) and the set of alternatives ($B_{I \times I}^{(j,m)}$). The pair-wise comparison matrix $B_{J \times J}^m$ is defined by all ratios of the form $\frac{w_j^m}{w_l^m}$, where w_j^m is the priority of the j -th criterion estimated by the m -th expert, and has dimension $J \times J$. Similarly, for every $j = 1, \dots, J$, $B_{I \times I}^{(j,m)}$ is defined by all ratios of the form $\frac{w_i^{(j,m)}}{w_l^{(j,m)}}$, where $w_i^{(j,m)}$ is the priority of the i -th alternative with respect to the j -th criterion estimated by the m -th expert, and has dimension $I \times I$.

To simplify notation, henceforth, B^m will be used to denote any of these pair-wise comparison matrices while w_k^m ($k = 1, \dots, n$) will stand for the priority of the k -th element (criterion or alternative) with respect to the higher-level element estimated by the m -th expert, with $n = I$ for the set of alternatives and $n = J$ for the set of criteria. That is:

$$B^m = \begin{pmatrix} 1 & \frac{w_1^m}{w_2^m} & \dots & \frac{w_1^m}{w_l^m} & \dots & \frac{w_1^m}{w_n^m} \\ \frac{w_2^m}{w_1^m} & 1 & \dots & \frac{w_2^m}{w_l^m} & \dots & \frac{w_2^m}{w_n^m} \\ \dots & \dots & \dots & \dots & \dots & \dots \\ \frac{w_k^m}{w_1^m} & \frac{w_k^m}{w_2^m} & \dots & \frac{w_k^m}{w_l^m} & \dots & \frac{w_k^m}{w_n^m} \\ \dots & \dots & \dots & \dots & \dots & \dots \\ \frac{w_n^m}{w_1^m} & \frac{w_n^m}{w_2^m} & \dots & \frac{w_n^m}{w_l^m} & \dots & 1 \end{pmatrix} \quad (2)$$

After applying one of the existing relative measurement methods, eigenvectors of ordered elements w_k^m are derived for the matrices B^m . $\hat{W}^m = (w_1^m, w_2^m, \dots, w_k^m, \dots, w_l^m, \dots, w_n^m)^T$ are the transposed vectors of the normalized priorities. $W^m = \{w_k^m : k = 1, \dots, n\}$ are the sets of priorities of the elements for the m -th expert. $W^k = \{w_k^m : m = 1, \dots, M\}$ are the sets of derived experts' priorities of the k -th element. Moreover, each comparison matrix must undergo a consistency check to confirm transitivity and reciprocity of the judgment data. Homogeneity of the compared elements is another sufficient condition needed to assure good consistency [76]. For a

detailed discussion of the relative measurement consistency issues, the interested reader is referred to [74,75,83–85]. Following Saaty [73], the inconsistency measure of the comparison matrices B^m is defined as the consistency ratio (C.R.): $C.R.(B^m) = \frac{C.I.(B^m)}{R.I.(n)}$, where $C.I.(B^m) = \frac{\lambda_{(B^m,\max)} - n}{n-1}$ is the consistency index; $R.I.(n)$ is the random inconsistency; $\lambda_{(B^m,\max)}$ is the largest eigenvalue of B^m . In general, C.R. should be 10% or less. In some cases, the C.R. is required to be less than 8% (for $n = 4$) or 5% (for $n = 3$). Otherwise, the inference quality should be improved. The higher C.R. is, the less consistent and plausible the expert evaluations are.

The set of global priorities of the alternatives, W^G , can be elicited by synthesizing all the individual priorities w_j^m relative to the j -th criterion and all the individual priorities $w_i^{(j,m)}$ of the i -th alternative with respect to the j -th criterion. To accomplish this, the weighted geometric mean method can be applied (see, among others [86]). Once all synthesized values, namely, w_j^m and $w_i^{(j,m)}$, $\forall j = 1, \dots, J$, are revealed, the global priorities of the alternatives ($w_i^G \in W^G$) can be derived using the weighed-sum approach:

$$w_i^G = \sum_{j=1}^J w_j \cdot w_i^{(j,m)}, \forall i = 1, \dots, I \quad (3)$$

The higher the weight w_i^G , the more preferable the alternative A_i . For the best alternative, A_* , it must be valid: $w_{A_*}^G = \max_{\forall i=1, \dots, I} [w_i^G]$.

5. The proposed NS-based GMCDM approach

As highlighted in Subsection 1.1 and Section 3, we focus on defining a procedure that relates the single DM's priorities obtained through any methodology based on a comparison principle to his/her own levels of credibility, inconsistency and confidence. After being interpreted as single-valued NSs, the group levels are reduced to representative crisp values through an ad hoc deneutrosophication process. These values are, in turn, used to estimate the overall performance of the alternatives.

Fig. 1 provides a graphical representation of the proposed NS-based GMCDM method comparing its stages with the typical ones of a crisp GMCDM problem and those generally implemented when solving GMCDM problems with fuzzy, intuitionistic fuzzy or neutrosophic information. The technical details of the proposed method are provided below.

Henceforth, the following additional notations will be adopted.

δ_k^m	the credibility (or voting power) of the m -th expert in assessing the priority of the k -th element (criterion or alternative);
ε_k^m	the measure of inconsistency (or error) of the m -th expert's assessment of the k -th element;
θ_k^m	the level of the m -th expert's confidence in her/his estimates of the k -th element.

For every $m = 1, \dots, M$, these three measures are independent from each other and the triad $\langle \delta_k^m, \varepsilon_k^m, \theta_k^m \rangle$ can be interpreted as the reliability of the m -th expert's estimate relative to the priority w_k^m .

5.1. Defining single-valued NSs of group estimates

A discrete single-valued NSs can be defined for each set $W^k = \{w_k^m : m = 1, \dots, M\}$. This set contains all the experts' priorities derived for the k -th element:

$$\tilde{N}^k = \{(w_k^m | T_{\tilde{N}^k}(w_k^m), F_{\tilde{N}^k}(w_k^m), I_{\tilde{N}^k}(w_k^m)) | w_k^m \in W^k\} \quad (4)$$




Fig. 2. Neutrosophic membership grade cube reflecting reliability areas.

where $\forall w_k^m \in W_k$, $\langle T_{\tilde{N}^k}(w_k^m), F_{\tilde{N}^k}(w_k^m), I_{\tilde{N}^k}(w_k^m) \rangle \in [0, 1]^3$ is the mapping of w_k^m into the neutrosophic space and:

$$\begin{cases} T_{\tilde{N}^k}(w_k^m) = f(\delta_k^m) \\ F_{\tilde{N}^k}(w_k^m) = f(\varepsilon_k^m) \\ I_{\tilde{N}^k}(w_k^m) = f(\theta_k^m) \end{cases} \quad (5)$$

$\varepsilon_k^m = 0$ means that the m -th expert is fully consistent or unerring in her/his judgments regarding the relative weight of the k -th element. For priorities computation based on the right eigenvalue method employed in AHP, the judgments are fully consistent if and only if $C.R.(B^m) = 0$. In this case, the neutrosophic falsity-grade of the corresponding w_k^m is zero: $F_{\tilde{N}^k}(w_k^m) = 0$. In AHP/APN, an inconsistency exceeding 10% is not acceptable, therefore all priority vectors derived from inconsistent matrices are not relevant; that is, if $C.R.(B^m) \geq 0.1$ then the falsity-grade of w_k^m is $F_{\tilde{N}^k}(w_k^m) = 1$. If $0 < C.R.(B^m) < 0.1$, then the corresponding estimates are still considered relevant to the decision-making process, but the closer the inconsistency is to 10%, the less credible the values w_k^m are (i.e., the falsity-grade of the priorities w_k^m grows).

The neutrosophic reliabilities in Eq. (5) can be rewritten as follows:

$$\begin{cases} T_{\tilde{N}^k}(w_k^m) = \frac{VP(w_k^m)}{\max(VP(w_k^m))}, \\ F_{\tilde{N}^k}(w_k^m) = \left(\frac{\varepsilon_k^m}{\varepsilon'^k} \text{ if } \varepsilon_k^m \leq \varepsilon'^k \right) \cup \left(1 \text{ if } \varepsilon_k^m > \varepsilon'^k \right), \\ I_{\tilde{N}^k}(w_k^m) = \frac{\max(SC_k^m) - SC_k^m}{\max(SC_k^m)}, \end{cases} \quad (6)$$

where $VP(w_k^m)$ ($\max(VP(w_k^m))$) is the (maximum possible) expert voting power for estimating the weight of the k -th element; ε'^k is the maximum acceptable inconsistency/error in the assessments of the priority of the k -th element; SC_k^m ($\max(SC_k^m)$) is the (maximum possible) level of the m -th expert's self-confidence degree in estimating the priority of the k -th element.

5.2. Single-valued neutrosophic cube and neutrosophic estimates reliability

Fig. 2 illustrates the single-valued neutrosophic cube (SVNC) $Q = Q_1 Q_2 Q_3 Q_4 Q_5 Q_6 Q_7 Q_8$ for the problem of expert judgment




Fig. 1. Proposed NS-based GMCDM method: a graphical comparison with existing approaches.

reliability estimation in group decision-making. The general neutrosophic cube was first introduced by Dezert [87].

The areas of reliability in Q are: unacceptable, high and tolerable.

Definition 7. (Unacceptable neutrosophic estimates reliability). The area of *unacceptable neutrosophic estimates reliability* χ is represented by the three sides of Q : $\chi_1 = Q_2 Q_6 Q_7 Q_3$, $\chi_2 = Q_5 Q_6 Q_7 Q_8$ and $\chi_3 = Q_3 Q_4 Q_8 Q_7$; $\chi = \chi_1 \cup \chi_2 \cup \chi_3$. In this area, the estimates w_k^m are characterized by 0% truth-, 100% falsity- and 100% indeterminacy-degrees, respectively. w_k^- is a subset of W_k that includes all the estimates w_k^m with zero truth-membership, unit falsity-membership or unit indeterminacy-membership:

$$W_k^- = \{w_k^m \in W_k \mid [T_{N_k}(w_k^m) = 0] \vee [F_{N_k}(w_k^m) = 1] \vee [I_{N_k}(w_k^m) = 1]\} \quad (7)$$

All the elements $w_k^m \in W_k^-$ should be excluded from the decision process.

Definition 8. (High neutrosophic estimates reliability). The sub-cube $R \subset Q$ represents the area of *high neutrosophic estimates reliability*. The vertices of R are defined as $R_1 = (1; 0; 0)$, $R_2 = (0.5; 0; 0.5)$, $R_3 = (0.5; 0; 0.5)$, $R_4 = (1; 0; 0.5)$, $R_5 = (1; 0.5; 0)$, $R_6 = (0.5; 0.5; 0)$, $R_7 = (0.5; 0.5; 0.5)$ and $R_8 = (1; 0.5; 0.5)$. W_k^R is a subset of W_k that includes all the estimates w_k^m with above average truth-membership, below average falsity-membership and below average indeterminacy-membership:

$$\begin{aligned} W_k^R = \{w_k^m \in W_k \mid & [0.5 \leq T_{N_k}(w_k^m) \leq 1] \wedge [0 \leq F_{N_k}(w_k^m) \leq 0.5] \wedge \\ & [0 \leq I_{N_k}(w_k^m) \leq 0.5]\} \end{aligned} \quad (8)$$

All the elements $w_k^m \in W_k^R$ contribute extensively to the group decision.

Definition 9. (Tolerable neutrosophic estimates reliability). $\Theta = Q \cap -R \cap -\chi$ is the area of *tolerable neutrosophic estimates reliability*. W_k^Θ is a subset of W_k that includes all the estimates w_k^m with below

average truth-membership, above average falsity-membership or above average indeterminacy-membership:

$$W_k^\Theta = \{w_k^m \in W_k \mid [0 < T_{N_k}(w_k^m) < 0.5] \vee [0.5 < F_{N_k}(w_k^m) < 1] \vee [0.5 < I_{N_k}(w_k^m) < 1]\} \quad (9)$$

All the elements $w_k^m \in W_k^\Theta$ have a minor impact on the group decision.

Definition 10. (Ideal neutrosophic estimates reliability). The point R_* in the neutrosophic space $\langle T, F, I \rangle$ reflecting 100% truth-, 0% falsity- and 0% indeterminacy-grade of judgments in the decision-making process is called the *ideal neutrosophic estimates reliability*. In the SVNC Q , $R_* = Q_1 = R_1 = (1; 0; 0)$.

Once all single-valued NSs \tilde{N}_k of group estimates are constructed, these values must be aggregated across M individuals to find a compromise priority of the k -th element for the committee. In terms of NSs, all \tilde{N}_k must be denutrosophied, and comparable/operable representative values $\eta_{*k} \in \mathbb{R}^1$ need to be elicited. The proposed denutrosophication procedure includes two steps: first, conversion of all single-valued NSs \tilde{N}_k into FSs \tilde{E}_k , and second, defuzzification of the sets \tilde{E}_k .

5.3. Deneutrosophication of group estimates: step 1 of 2

Single-valued NSs $\tilde{N}_k = \{(w_k^m | T_{\tilde{N}_k}(w_k^m), F_{\tilde{N}_k}(w_k^m), I_{\tilde{N}_k}(w_k^m))\}$ are converted into FSs $\tilde{E}_k = \{(w_k^m | \mu_{\tilde{E}_k}(w_k^m))\}$ as follows. The experts' estimates w_k^m remain invariant. For every $w_k^m \notin W_k^-$, the triads of neutrosophic truth-, falsity- and indeterminacy-membership grades are translated into scalar fuzzy membership grades $\mu_{\tilde{E}_k}(w_k^m) \in [0, 1]^1$ based on the Euclidean distance between the point $\langle T_{\tilde{N}_k}(w_k^m), F_{\tilde{N}_k}(w_k^m), I_{\tilde{N}_k}(w_k^m) \rangle \in [0, 1]^3$ and the ideal neutrosophic estimates reliability $R_* \in [0, 1]^3$. At the same time, since the prior-

ities w_k^m in the set \tilde{W}_k are not reliable, they are assigned a zero-fuzzy membership grade. Hence:

$$\mu_{\tilde{E}_k}(w_k^m) = \begin{cases} 1 - \sqrt{(1 - T_{\tilde{N}_k}(w_k^m))^2 + F_{\tilde{N}_k}(w_k^m)^2 + I_{\tilde{N}_k}(w_k^m)^2}, & \text{if } w_k^m \notin \tilde{W}_k \\ 0, & \text{if } w_k^m \in \tilde{W}_k \end{cases} \quad (10)$$

In particular, for every $w_k^m, w_{k'}^m \in W_k$ and $m = 1, \dots, M$, $\mu_{\tilde{E}_k}(w_k^m) > \mu_{\tilde{E}_k}(w_{k'}^m)$ means that w_k^m is more reliable than $w_{k'}^m$.

5.4. Deneutrosophication of group estimates: step 2 of 2

FSs \tilde{E}_k that represent uncertain group assessments with corresponding reliability grades are defuzzified using the COG method for the discrete case as defined by Eq. (1). Thus, one representative compromise crisp value $e_{*k} = \eta_{*k} \in \mathbb{R}^1$ is obtained for each k :

$$\eta_{*k} = \frac{\sum_{m=1}^M w_k^m \cdot \mu_{\tilde{E}_k}(w_k^m)}{\sum_{m=1}^M \mu_{\tilde{E}_k}(w_k^m)} \quad (11)$$

Normalization of representative opinions η_{*k} is needed to reflect their relative weights within the sets these opinions belong to:

$$\eta'_{*k} = \eta_{*k} / \sum_{k=1}^K \eta_{*k} \quad (12)$$

5.5. Global priorities of alternatives

The overall priorities of the alternatives are derived using the weighted additive aggregation:

$$w_i^G = \sum_{j=1}^J \eta'_{*j} \cdot \eta'_{*i}^j, \forall i = 1, \dots, I \quad (13)$$

where η'_{*j} and η'_{*i}^j are the normalized representative values for the j -th criterion and the i -th alternative with respect to the j -th criterion, respectively. The higher is the value w_i^G , the better A^i meets the collective group objectives.

Finally, note that the proposed method can be implemented using any common software such as Excel or MatLab. The numerical results of the illustrative example below were obtained in Excel.

Remark 1. In the proposed method, trapezoidal or triangular single-valued NNs can be easily employed in place of single-valued NSs to represent DMs' priorities. This variant of the model requires some adjustments in the aggregation and synthesizing phases. We outlined below the changes to be applied in the triangular case. The trapezoidal case is similar. For the sake of completeness, recall that [88] a triangular single-valued NN, $\tilde{a} = \langle (a, b, c); t_{\tilde{a}}, f_{\tilde{a}}, i_{\tilde{a}} \rangle$, is a NS on \mathbb{R}^1 with truth-, falsity-, and indeterminacy-membership functions defined as follows:

$$\mu_{\tilde{a}}(x) = \begin{cases} \frac{(x-a)t_{\tilde{a}}}{(b-a)}, & \text{ifa} \leq x < b \\ \frac{(c-x)t_{\tilde{a}}}{(c-b)}, & \text{if} b \leq x \leq c \\ 0, & \text{otherwise} \end{cases}$$

$$\lambda_{\tilde{a}}(x) = \begin{cases} \frac{(b-x+f_{\tilde{a}}(x-a))}{(b-a)}, & \text{ifa} \leq x < b \\ \frac{(x-b+f_{\tilde{a}}(c-x))}{(c-b)}, & \text{if} b \leq x \leq c \\ 0, & \text{otherwise} \end{cases}$$

$$\nu_{\tilde{a}}(x) = \begin{cases} \frac{(b-x+i_{\tilde{a}}(x-a))}{(b-a)}, & \text{ifa} \leq x < b \\ \frac{(x-b+i_{\tilde{a}}(c-x))}{(c-b)}, & \text{if} b \leq x \leq c \\ 0, & \text{otherwise} \end{cases}$$

The NSs in Eq. (4) should be replaced with sets of triangular single-valued NNs, $\tilde{N}^k = \left\{ \tilde{w}_k^m = \langle (a_k^m, b_k^m, c_k^m); t_{\tilde{w}_k^m}, f_{\tilde{w}_k^m}, i_{\tilde{w}_k^m} \rangle : w_k^m \in W_k \right\}$, where, for $\forall w_k^m \in W_k$, $t_{\tilde{w}_k^m} = T_{\tilde{N}^k}(w_k^m)$, $f_{\tilde{w}_k^m} = F_{\tilde{N}^k}(w_k^m)$ and $i_{\tilde{w}_k^m} = I_{\tilde{N}^k}(w_k^m)$ are computed according to Eq. (6). After mapping all the triads $\langle t_{\tilde{w}_k^m}, f_{\tilde{w}_k^m}, i_{\tilde{w}_k^m} \rangle$ into the SVNC \mathbf{Q} , Eq. (10) can be applied to define the membership functions of the triangular fuzzy numbers $\tilde{w}_k^m = (a_k^m, b_k^m, c_k^m)$. At this point, an appropriate defuzzification method must be implemented to defuzzify these numbers and synthesize the collective crisp priorities η_{*k} to be used in Eqs. (12) and (13).

6. An illustrative example

Let four domain experts with unequal voting powers be responsible for the assessment of three alternatives with respect to five criteria ($M = 4$, $I = 3$, $J = 5$). First, each expert builds pairwise comparison matrices as shown in Eq. (2) and applies the right eigenvalue method to reveal the weights of the criteria ($w_j^{(i,m)}$) and the priorities of the alternatives with respect to each criterion ($w_i^{(j,m)}$). The consistency ratio $C.R.(B_{j \times j}^m)$ (respectively, $C.R.(B_{I \times I}^{(j,m)})$) is calculated for each comparison matrix $B_{j \times j}^m$ (respectively, $B_{I \times I}^{(j,m)}$). The maximum acceptable consistency ratio is 10% ($\varepsilon' = 10\%$ for $\forall i, j, m$). The voting power of each DM ranges from 0 to 100, that is:

$$\begin{aligned} \forall i, j, m, VP(w_j^m), VP(w_i^{(j,m)}) &\in [0, 100], \max(VP_j^m) \\ &= 100, \max(VP_i^{(j,m)}) = 100 \end{aligned} \quad (14)$$

with higher scores standing for greater DMs' influence. We assume that $\forall i, j :$

$$\begin{aligned} VP(w_i^{DM1}) &= VP(w_i^{(j,DM1)}) = 100, VP(w_i^{DM2}) = VP(w_i^{(j,DM2)}) = 50, \\ VP(w_i^{DM3}) &= VP(w_i^{(j,DM3)}) = 85, \text{ and } VP(w_i^{DM4}) = VP(w_i^{(j,DM4)}) = 75 \end{aligned} \quad (15)$$

Moreover, the level of confidence in the correctness of the derived priorities is expressed by each committee member on a scale from 0 to 100, with lower scores designating greater indecision:

$$\begin{aligned} \forall i, j, m, SC_j^m, SC_i^{(j,m)} &\in [0, 100], \max(SC_j^m) \\ &= 100, \max(SC_i^{(j,m)}) = 100 \end{aligned} \quad (16)$$

Tables 1 and 2 presents the derived priorities of decision criteria and alternatives, the respective consistency ratios, as well as the confidence scores.

Table 1

Criteria weights, consistency ratios and confidence scores.

Criteria, C_j	Experts, DM^m							
	DM^1		DM^2		DM^3		DM^4	
	$w_j^{DM^1}$	$SC_j^{DM^1}$	$w_j^{DM^2}$	$SC_j^{DM^2}$	$w_j^{DM^3}$	$SC_j^{DM^3}$	$w_j^{DM^4}$	$SC_j^{DM^4}$
C_1	0.289	75	0.350	90	0.158	95	0.400	65
C_2	0.124	80	0.176	90	0.234	95	0.150	50
C_3	0.204	90	0.150	90	0.015	92	0.200	50
C_4	0.312	60	0.150	90	0.314	90	0.145	50
C_5	0.071	95	0.174	90	0.279	95	0.105	60
Inconsistency, C.R. ($B_{j \times j}^m$)	7.5%		3.01%		1.74%		5.2%	

Table 2

Consistency ratio and confidence score estimates.

Experts, DM^m	Criteria, C_j	Alternatives, A_i						Inconsistency, C.R. ($B_{I \times I}^{(j, DM^m)}$)
		A_1		A_2		A_3		
		$w_{A_1}^{(j, DM^m)}$	$SC_{A_1}^{(j, DM^m)}$	$w_{A_2}^{(j, DM^m)}$	$SC_{A_2}^{(j, DM^m)}$	$w_{A_3}^{(j, DM^m)}$	$SC_{A_3}^{(j, DM^m)}$	
DM^1	C_1	0.289	90	0.524	80	0.187	100	8.50%
	C_2	0.465	50	0.117	60	0.418	50	26.00%
	C_3	0.332	75	0.482	80	0.186	85	4.00%
	C_4	0.049	95	0.385	95	0.566	90	2.00%
	C_5	0.455	70	0.240	90	0.305	80	6.50%
DM^2	C_1	0.349	40	0.341	60	0.310	40	36.50%
	C_2	0.200	60	0.250	75	0.550	80	3.07%
	C_3	0.028	80	0.552	75	0.420	65	2.40%
	C_4	0.266	0	0.333	0	0.401	0	15.00%
	C_5	0.417	70	0.200	80	0.383	75	5.00%
DM^3	C_1	0.090	100	0.097	75	0.813	85	2.60%
	C_2	0.333	95	0.080	80	0.587	60	5.30%
	C_3	0.245	70	0.300	85	0.455	85	1.25%
	C_4	0.300	60	0.500	70	0.200	90	4.00%
	C_5	0.358	100	0.369	100	0.273	100	0.01%
DM^4	C_1	0.208	75	0.515	80	0.277	85	5.80%
	C_2	0.252	33	0.300	50	0.448	33	6.50%
	C_3	0.486	0	0.202	0	0.312	0	36.00%
	C_4	0.568	95	0.252	99	0.180	90	2.40%
	C_5	0.450	0	0.386	0	0.164	0	19.00%

Each set of group assessments w_j^m (respectively, $w_i^{(j, m)}$), and inherent to them, measures of voting power $\delta(w_j^m)$ (respectively, $\delta(w_i^{(j, m)})$), inconsistency ε_j^m (respectively, $\varepsilon_i^{(j, m)}$) and confidence θ_j^m (respectively, $\theta_i^{(j, m)}$) is represented as a single-valued NS \tilde{N}_j (respectively, \tilde{N}_i^j) based on Eqs. (4) and (6).

$$\text{That is, } \tilde{N}_j = \left\{ (w_j^m | T_{\tilde{N}_j}(w_j^m), F_{\tilde{N}_j}(w_j^m), I_{\tilde{N}_j}(w_j^m)) \right\} \text{ where:}$$

$$\left\{ \begin{array}{l} T_{\tilde{N}_j}(w_j^m) = \frac{VP^m}{100} \\ F_{\tilde{N}_j}(w_j^m) = \left(\frac{\text{C.R.} (B_{j \times j}^m)}{10\%} \right) \text{ if C.R.} (B_{j \times j}^m) \leq 10\% \cup (1 \text{ if C.R.} (B_{j \times j}^m) > 10\%) \\ I_{\tilde{N}_j}(w_j^m) = \frac{100 - SC_j^m}{100} \\ w_j^m \in [0, 1], \sum_{j=1}^J w_j^m = 1. \end{array} \right. \quad (17)$$

Also, $\forall j = 1, \dots, J, \tilde{N}_i^j = \left\{ (w_i^{(j, m)} | T_{\tilde{N}_i^j}(w_i^{(j, m)}), F_{\tilde{N}_i^j}(w_i^{(j, m)}), I_{\tilde{N}_i^j}(w_i^{(j, m)})) \right\}$ where:

$$\left\{ \begin{array}{l} T_{\tilde{N}_i^j}(w_i^{(j, m)}) = \frac{VP^m}{100} \\ F_{\tilde{N}_i^j}(w_i^{(j, m)}) = \left(\frac{\text{C.R.} (B_{I \times I}^{(j, m)})}{10\%} \right) \text{ if C.R.} (B_{I \times I}^{(j, m)}) \leq 10\% \cup (1 \text{ if C.R.} (B_{I \times I}^{(j, m)}) > 10\%) \\ I_{\tilde{N}_i^j}(w_i^{(j, m)}) = \frac{100 - SC_i^{(j, m)}}{100} \\ w_i^{(j, m)} \in [0, 1], \sum_{i=1}^I w_i^{(j, m)} = 1. \end{array} \right. \quad (18)$$

The single-valued NSs representing the uncertain group priorities of the alternatives are listed in Table 3.

To fix the ideas, Fig. 3 provides the graphical illustration of the single-valued NS $\tilde{N}_{A_1}^{C_1}$ that is, the space of group performance estimates of the alternative A_1 with respect to the criterion C_1 . Each element in the set $\{w_{A_1}^{(C_1, m)} : m = 1, \dots, M\} \subset [0, 1]$ is mapped into a point of the SVNC Q .

Estimates of all individuals can be classified according to their reliability based on the position within the SVNC Q .

(a) The values with *unacceptable neutrosophic reliability* must be excluded from further decision processes. These values are:

$$w_{A_1}^{(C_2, DM_1)}, w_{A_1}^{(C_1, DM_2)}, w_{A_2}^{(C_2, DM_1)}, w_{A_2}^{(C_1, DM_2)}, w_{A_3}^{(C_2, DM_1)}, w_{A_3}^{(C_1, DM_2)} \in \chi_3 \subset \mathcal{W}_i^j$$

- the estimates characterized by 100% falsity degree;

$$w_{A_1}^{(C_4, DM_2)}, w_{A_1}^{(C_3, DM_4)}, w_{A_2}^{(C_3, DM_4)}, w_{A_2}^{(C_4, DM_2)}, w_{A_3}^{(C_3, DM_4)}, w_{A_3}^{(C_4, DM_2)} \in (\chi_3 \cup \chi_4) \subset \mathcal{W}_i^j$$

- the estimates characterized by 100% falsity- and 100% indeterminacy degrees.

- The estimates with *high neutrosophic reliability* that imply a strong impact on the decision include:

$$\begin{aligned} & w_{A_i}^{(C_3, DM_1)}, w_{A_i}^{(C_4, DM_1)}, w_{A_i}^{(C_2, DM_2)}, w_{A_i}^{(C_3, DM_2)}, \\ & w_{A_i}^{(C_5, DM_2)}, w_{A_i}^{(C_1, DM_3)}, w_{A_i}^{(C_3, DM_3)}, w_{A_i}^{(C_4, DM_3)}, w_{A_i}^{(C_5, DM_3)}, \quad w_{A_i}^{(C_4, DM_4)} \in \\ & W_i^{IR} \text{ for } i = 1, 2, 3. \end{aligned}$$

Table 3

Neutrosophic group estimates of alternatives with respect to criteria.

Alternatives A_i	Criteria C_j	Single-valued NSs of alternative estimates $\tilde{N}_{A_i}^j = \left\{ (w_{A_i}^{(j,m)}) T_{\tilde{N}_i^j}(w_{A_i}^{(j,m)}), F_{\tilde{N}_i^j}(w_{A_i}^{(j,m)}), I_{\tilde{N}_i^j}(w_{A_i}^{(j,m)}) \right\}$
A_1	C_1	$\{(0.289 1, 0.85, 0.1), (0.349 0.5, 1, 0.6), (0.09 0.85, 0.46, 0), (0.208 0.75, 0.58, 0.25)\}$
	C_2	$\{(0.465 1, 1.0, 0.5), (0.2 0.5, 0.31, 0.4), (0.333 0.85, 0.51, 0.05), (0.252 0.75, 0.65, 0.67)\}$
	C_3	$\{(0.332 1, 0.04, 0.25), (0.028 0.5, 0.24, 0.45), (0.245 0.85, 0.13, 0.3), (0.486 0.75, 1, 1)\}$
	C_4	$\{(0.049 1, 0.2, 0.5), (0.266 0.5, 1, 1), (0.3 0.85, 0.4, 0.4), (0.568 0.75, 0.14, 0.05)\}$
	C_5	$\{(0.455 1, 0.55, 0.05), (0.417 0.5, 0.5, 0.1), (0.358 0.85, 0, 0), (0.45 0.75, 1, 1)\}$
A_2	C_1	$\{(0.524 1, 0.85, 0.2), (0.341 0.5, 1, 0.4), (0.097 0.85, 0.46, 0.25), (0.515 0.75, 0.58, 0.45)\}$
	C_2	$\{(0.117 1, 1, 0.4), (0.25 0.5, 0.31, 0.25), (0.08 0.85, 0.51, 0.05), (0.3 0.75, 0.65, 0.5)\}$
	C_3	$\{(0.482 1, 0.04, 0.45), (0.552 0.5, 0.24, 0.45), (0.3 0.85, 0.13, 0.15), (0.202 0.75, 1, 1)\}$
	C_4	$\{(0.385 1, 0.2, 0.35), (0.333 0.5, 1, 1), (0.5 0.85, 0.46, 0.45), (0.252 0.75, 0.14, 0.01)\}$
	C_5	$\{(0.240 1, 0.55, 0.1), (0.2 0.5, 0.5, 0.1), (0.369 0.85, 0, 0.25), (0.386 0.75, 1, 1)\}$
A_3	C_1	$\{(0.187 1, 0.85, 0), (0.31 0.5, 1.0, 0.6), (0.813 0.85, 0.46, 0.15), (0.277 0.75, 0.58, 0.15)\}$
	C_2	$\{(0.418 1, 1, 0.5), (0.55 0.5, 0.31, 0.2), (0.587 0.85, 0.51, 0.4), (0.448 0.75, 0.65, 0.67)\}$
	C_3	$\{(0.186 1, 0.04, 0.15), (0.42 0.5, 0.24, 0.35), (0.455 0.85, 0.13, 0.15), (0.312 0.75, 1, 1)\}$
	C_4	$\{(0.566 1, 0.2, 0.1), (0.401 0.5, 1, 1), (0.2 0.85, 0.4, 0.1), (0.180 0.75, 0.14, 0.1)\}$
	C_5	$\{(0.305 1.0, 0.55, 0.2), (0.383 0.5, 0.5, 0.3), (0.273 0.85, 0, 0), (0.164 0.75, 1, 1)\}$




Fig. 3. Example of single-valued neutrosophic estimate.

- The estimates with *tolerable neutrosophic reliability* that imply a weak to average impact on the decision are:

$$w_{A_i}^{(C_1, DM_1)}, w_{A_i}^{(C_5, DM_1)}, w_{A_i}^{(C_2, DM_3)}, w_{A_i}^{(C_1, DM_4)}, w_{A_i}^{(C_2, DM_4)} \in W_i^{j,\Theta} \text{ for } i = 1, 2, 3.$$

As suggested in Section 4, derivation of the compromise group assessments represented as single-valued NSs can be accomplished using the deneutrosophication process where all triads $\langle T_{\tilde{N}_j}(w_j^m), F_{\tilde{N}_j}(w_j^m), I_{\tilde{N}_j}(w_j^m) \rangle$ and $\langle T_{\tilde{N}_i^j}(w_i^{(j,m)}), F_{\tilde{N}_i^j}(w_i^{(j,m)}), I_{\tilde{N}_i^j}(w_i^{(j,m)}) \rangle$ are first converted into fuzzy membership grades $\mu_{\tilde{E}_j}(w_j^m)$ and $\mu_{\tilde{E}_i^j}(w_i^{(j,m)})$, respectively,

and then the representative crisp values η_j^* and η_i^j are calculated for each obtained FS. The conversion of single-valued NSs into FSs relies upon the Euclidean metric in three-dimensional space for all reliable priorities w_j^m and $w_i^{(j,m)}$, and is performed according to Eq. (10). Tables 4 and 5 contain the resulting FSs for the group estimates of criteria and alternatives.

Table 4
Fuzzy group estimates of criteria weights.

Criteria C_j	FSs of criteria importance weights $\tilde{E}^j = \{(w_j^m \mu_{\tilde{E}_j}(w_j^m))\}$
C_1	$\{(0.289 0.672), (0.35 0.360), (0.158 0.717), (0.4 0.543)\}$
C_2	$\{(0.124 0.718), (0.176 0.369), (0.234 0.717), (0.15 0.493)\}$
C_3	$\{(0.204 0.822), (0.15 0.369), (0.015 0.717), (0.2 0.493)\}$
C_4	$\{(0.312 0.552), (0.15 0.369), (0.314 0.716), (0.145 0.493)\}$
C_5	$\{(0.071 0.888), (0.174 0.369), (0.279 0.717), (0.105 0.527)\}$

The calculations of the representative crisp estimates for each set of group members' uncertain values are enabled by using the centroid method and Eqs. (11) and (12). The relative compromise importance weights of the criteria are: $\eta^*_{C_1} = 0.26$, $\eta^*_{C_2} = 0.195$, $\eta^*_{C_3} = 0.098$, $\eta^*_{C_4} = 0.248$ and $\eta^*_{C_5} = 0.199$. The normalized representative values for the alternatives are given in Table 6. The global priorities of the alternatives are calculated using Eq. (13).

As shown in Table 6, alternative A^3 (Rank 1) has the highest global priority value and, therefore, it is the best one; alternatives A^1 and A^2 have close priority values, although A^1 (Rank 2) is slightly better than A^2 (Rank 3).

Table 5

Fuzzy group estimates of alternatives with respect to criteria.

Alternatives A_i	Criteria C_j	FSs of alternative estimates $\tilde{E}_i^j = \{(w_i^{(j,m)} \mu_{\tilde{E}_i^j}(w_i^{(j,m)})\}$
A_1	C_1	$\{(0.289 0.1), (0.349 0), (0.09 0.55), (0.208 0.23)\}$
	C_2	$\{(0.465 0), (0.2 0.2), (0.333 0.34), (0.252 0.02)\}$
	C_3	$\{(0.332 0.6), (0.028 0.2), (0.245 0.5), (0.486 0)\}$
	C_4	$\{(0.049 0.34), (0.266 0), (0.3 0.27), (0.568 0.56)\}$
	C_5	$\{(0.455 0.33), (0.417 0.2), (0.358 0.72), (0.45 0)\}$
A_2	C_1	$\{(0.524 0.09), (0.341 0), (0.097 0.47), (0.515 0.16)\}$
	C_2	$\{(0.117 0), (0.25 0.26), (0.08 0.34), (0.3 0.1)\}$
	C_3	$\{(0.482 0.41), (0.552 0.2), (0.3 0.61), (0.202 0)\}$
	C_4	$\{(0.385 0.45), (0.333 0), (0.5 0.24), (0.252 0.57)\}$
	C_5	$\{(0.240 0.32), (0.2 0.2), (0.369 0.56), (0.386 0)\}$
A_3	C_1	$\{(0.187 0.103), (0.31 0), (0.813 0.52), (0.277 0.25)\}$
	C_2	$\{(0.418 0), (0.55 0.27), (0.587 0.24), (0.448 0.02)\}$
	C_3	$\{(0.186 0.711), (0.42 0.25), (0.455 0.61), (0.312 0)\}$
	C_4	$\{(0.566 0.632), (0.401 0), (0.2 0.38), (0.18 0.55)\}$
	C_5	$\{(0.305 0.3), (0.383 0.17), (0.273 0.72), (0.164 0)\}$

Table 6

Relative representative priorities of alternatives and the overall rankings.

Criteria C_j	Alternatives A_i		
	A_1	A_2	A_3
C_1	0.143	0.241	0.585
C_2	0.282	0.174	0.562
C_3	0.252	0.403	0.327
C_4	0.356	0.348	0.341
C_5	0.393	0.299	0.297
Overall priorities w_i^G	0.2834	0.2819	0.4376
Rankings	2	3	1

For a comparison, the global priorities of the alternatives under consideration for the same experts' estimates w_j^m and $w_i^{(j,m)}$ ($\forall i = 1, \dots, 3; \forall j = 1, \dots, 5; \forall m = 1, \dots, 4$) but calculated using the geometric mean of group members' opinions and without taking into consideration the uncertainty measures δ , ε and θ . The obtained values are: $w_{A_1}^G = 0.2823$ (Rank 3), $w_{A_2}^G = 0.3321$ (Rank 2) and $w_{A_3}^G = 0.3856$ (Rank 1). It is evident from these comparative results that the uncertainty of the data is sufficient to affect the decision outcome.

For a more precise analysis, sensitivity of the results to changes in the experts' opinions can be tested. Special attention should be paid to the estimates that fall into the area of unacceptable neutrosophic reliability.

7. Conclusion and future research directions

We have proposed a novel method to handle multi-source uncertainty measures reflecting the reliability of experts' assessments in GMCDM problems based on single-valued NSs.

NSs are characterized by three independent membership magnitudes (falsity, truth and indeterminacy) and can be applied to model situations characterized by complex uncertainty, including those leading to paradoxical results.

Most of the studies on neutrosophic approaches to GMCDM problems that have been presented over the last two decades focus on the development of generalized aggregation operators to be applied to neutrosophic decision matrices in order to synthesize group estimates of criteria and alternatives. Furthermore, the truth, falsity and indeterminacy levels representing the uncertainty inherent to DMs' judgments are not usually given any explicit interpretation, nor are the variables that they depend on explicitly defined.

The artificiality and routineness deriving from an overuse of aggregation operators together with the tendency to overlook a concrete interpretation for neutrosophic values within a given

GMCDM problem represent a gap in the literature that need to be considered in order to investigate ways to effectively improve the applicability of decision-making processes.

In the proposed approach, DMs' estimates have been characterized by independent tangible and intangible measures defined in a way to explicitly reflect DMs' voting powers, inconsistencies/errors inherent to the judgment process, and DMs' confidence in their own evaluation abilities.

At the same time, single-valued NSs have been used to formalize the uncertainty affecting DMs' priorities and aggregate them into group estimates without the need to define neutrosophic decision matrices or aggregation operators. The group estimates have been synthesized into crisp evaluations through a two-step defuzzification process that converts single-valued NSs in FSs using the standard Euclidean metric and, subsequently, FSs in representative crisp values through defuzzification.

An illustrative example has been provided to show how taking into account multi-source uncertainty indicators inherent to the experts' evaluations may deeply affect the results obtained in a standard fuzzy environment even in the case of simple ranking problems.

The proposed aggregation and synthesizing mechanisms can be extended so as to allow for more general approaches requiring to formalize higher levels of uncertainty relative to the DMs' estimates. In particular, a variant of the proposed method has been outlined where trapezoidal or triangular single-valued neutrosophic numbers (NNs) are employed in place of single-valued NSs to represent DMs' priorities.

Future research could focus on more complex extensions involving for instance interval-valued NSs, multi-valued NSs or linguistic variables. It could be also interesting to investigate reliability measures leading to algebraic definitions for the neutrosophic membership functions different from those proposed in the current setting.

From a practical viewpoint, the proposed method allows for applications to a wide range real-life situations. For example, it could be applied to collaborative supplier selection problems with the purpose of incorporating both heterogeneous uncertain/unknown data and experts' subjective judgments within a hierarchical decision making structure.

Similar applications could be developed in the medical and military sectors, among others, for assisting managers in assessing human resources or project proposals. Regarding, in particular, the medical sector, the proposed indeterminacy-membership function could be directly related to recent studies on judgment confidence and decision tendencies [89–91], where individual differences in decision-making are analyzed based on the idea that decision optimality is a function of judgment accuracy and tests are designed in

the attempt to profile individuals' decision tendencies (i.e., optimal, realistic, incompetent, hesitant and congruent).

Acknowledgement

The authors would like to thank the anonymous reviewers, the associate editor and the editor for their insightful comments and suggestions.

References

- [1] J.M. Mendel, Computing with words, when words can mean different things to different people, in: Proceedings of Third International ICSC Symposium on Fuzzy Logic and Applications, Rochester, NY, June 1999, 1999, pp. 158–164.
- [2] J.M. Mendel, Computing with words and its relationships with fuzzistics, *Inf. Sci.* 177 (4) (2007) 988–1006.
- [3] Q. Liang, J.M. Mendel, Interval type-2 fuzzy logic systems: theory and design, *IEEE Trans. Fuzzy Syst.* 8 (2000) 535–550.
- [4] T. Jelassi, G. Kersten, S. Zions, An introduction to group decision and negotiation support, in: C. Bana Costa (Ed.), *Readings in Multiple Criteria Decision Aid*, Springer, Berlin, 1990, pp. 537–568.
- [5] A.I. Ölcer, A.Y. Odabasi, A new fuzzy multiple attribute group decision methodology and its application to propulsion/manoeuvring system selection problem, *Eur. J. Oper. Res.* 166 (2005) 93–114.
- [6] M.A. Sodenkamp, M. Tavana, D. Di Caprio, Modeling synergies in multi-criteria supplier selection and order allocation: an application to commodity trading, *Eur. J. Oper. Res.* 254 (3) (2016) 859–874.
- [7] T.L. Saaty, L.G. Vargas, Inconsistency and rank preservation, *J. Math. Psychol.* 28 (1984) 205–214.
- [8] R. Jain, A procedure for multiple-aspect decision making using fuzzy sets, *Int. J. Syst. Sci.* 8 (1977) 1–7.
- [9] K. Anagnostopoulos, H. Doukas, J. Psarras, A linguistic multicriteria analysis system combining fuzzy sets theory, ideal and anti-ideal points for location site selection, *Expert Syst. Appl.* 35 (2008) 2041–2048.
- [10] A. Schumann, F. Smarandache, American research press, in: *Neutrality and Many-Valued Logics*, 2007.
- [11] L. Zadeh, Fuzzy sets, *Information and Control* 8 (1965) 338–353.
- [12] H.J. Zimmermann, *Fuzzy Set Theory and Its Applications*, 4th ed., Kluwer Academic Publishers, 2001.
- [13] I.N. Durbach, T.J. Stewart, Modeling uncertainty in multi-criteria decision analysis, *Eur. J. Oper. Res.* 223 (2012) 1–14.
- [14] L. Zadeh, Outline of a new approach to the analysis of complex systems and decision processes, *IEEE Transactions on Systems, Man, and Cybernetics* 3 (1973) 28–44.
- [15] R.L. Ackoff, *Redesigning the Future*, Wiley, New York, 1974.
- [16] Z. Pawlak, Rough sets, *Int. J. Parallel Programm.* 11 (1982) 341–356.
- [17] K. Atanassov, *Intuitionistic Fuzzy Sets*, Springer Physica-Verlag, Berlin, 1999.
- [18] W. Van Leekwijck, E.E. Kerre, Defuzzification: criteria and classification, *Fuzzy Sets Syst.* 108 (1999) 159–178.
- [19] J. Hall, M. Anderson, Handling uncertainty in extreme or unrepeatable hydrological processes – the need for an alternative paradigm, *Hydrol. Processes* 16 (2002) 1867–1870.
- [20] F. Smarandache, *A Unifying Field in Logics, Neutrosophy: Neutrosophic Probability, Set and Logic*, American Research Press, Rehoboth, 1999.
- [21] F. Smarandache, Neutrosophic set – a generalization of the intuitionistic fuzzy set, *Int. J. Pure Appl. Math.* 24 (2005) 287–297.
- [22] R.K. Ragade, Fuzzy sets in communication systems and in consensus formation systems, *Journal of Cybernetics* 6 (1976) 21–38.
- [23] E. Turban, *Decision Support Systems and Expert Systems: Managerial Perspectives*, Macmillan, New York, 1988.
- [24] E.D. Hahn, Decision making with uncertain judgments: a stochastic formulation of the analytic hierarchy process, *Decis. Sci.* 34 (2003) 443–466.
- [25] N.F. Matsatsinis, A.P. Samaras, MCDA and preference disaggregation in group decision support systems, *Eur. J. Oper. Res.* 130 (2001) 414–429.
- [26] D. Dalalah, M. Hayajneh, F. Natieha, A fuzzy multi-criteria decision making model for supplier selection, *Expert Syst. Appl.* 38 (2011) 8384–8391.
- [27] M. Tavana, M.A. Sodenkamp, A fuzzy multi-criteria decision analysis model for advanced technology assessment at kennedy space center, *J. Oper. Res. Soc.* 61 (2010) 1459–1470.
- [28] A. Mardani, A. Jusoh, E.K. Zavadskas, Fuzzy multiple criteria decision-making techniques and applications—Two decades review from 1994 to 2014, *Expert Syst. Appl.* 42 (8) (2015) 4126–4148.
- [29] S. Kubler, J. Robert, W. Derigent, A. Voisin, Y. Le Traon, A state-of-the-art survey & testbed of fuzzy AHP (FAHP) applications, *Expert Syst. Appl.* 65 (2016) 398–422.
- [30] X. Tang, N. Feng, M. Xue, S. Yang, J. Wu, The expert reliability and evidential reasoning rule based intuitionistic fuzzy multiple attribute group decision making, *J. Intell. Fuzzy Syst.* 33 (2) (2017) 1067–1082.
- [31] H.Y. Zhang, H.G. Peng, J. Wang, J.Q. Wang, An extended outranking approach for multi-criteria decision-making problems with linguistic intuitionistic fuzzy numbers, *Appl. Soft Comput.* 59 (2017) 462–474.
- [32] L. Mikhailov, M.G. Singh, Fuzzy analytic network process and its application to the development of decision support systems, *IEEE Trans. Syst. Man Cybernet. C (Appl. Rev.)* 33 (1) (2003) 33–41.
- [33] J.J. Liao, G.H. Tzeng, C.Y. Tsai, C.C. Hsu, A hybrid ANP model in fuzzy environments for strategic alliance partner selection in the airline industry, *Appl. Soft Comput.* 11 (4) (2011) 3515–3524.
- [34] Z. Xu, H. Liao, A survey of approaches to decision making with intuitionistic fuzzy preference relations, *Knowl.-Based Syst.* 80 (2015) 131–142.
- [35] F. Meng, X. Chen, Y. Zhang, Consistency-based linear programming models for generating the priority vector from interval fuzzy preference relations, *Appl. Soft Comput.* 41 (2016) 247–264.
- [36] J. Razmi, E. Jafarian, S.H. Amin, An intuitionistic fuzzy goal programming approach for finding pareto-optimal solutions to multi-objective programming problems, *Expert Syst. Appl.* 65 (2016) 181–193.
- [37] M. Tavana, M. Zareinejad, D. Di Caprio, M.A. Kaviani, An integrated intuitionistic fuzzy AHP and SWOT method for outsourcing reverse logistics, *Appl. Soft Comput.* 40 (2016) 544–557.
- [38] F. Meng, C. Tan, X. Chen, Multiplicative consistency analysis for interval fuzzy preference relations: a comparative study, *Omega* 68 (2017) 17–38.
- [39] J.J. Peng, J.Q. Wang, X.H. Wu, J. Wang, X.H. Chen, Multi-valued neutrosophic sets and power aggregation operators with their applications in multi-criteria group decision-making problems, *Int. J. Comput. Intell. Syst.* 8 (2) (2015) 345–363.
- [40] J.J. Peng, J.Q. Wang, J. Wang, H.Y. Zhang, X.H. Chen, Simplified neutrosophic sets and their applications in multi-criteria group decision-making problems, *Int. J. Syst. Sci.* 47 (10) (2016) 2342–2358.
- [41] C. Liu, Y. Luo, Power aggregation operators of simplified neutrosophic sets and their use in multi-attribute group decision making, *IEEE/CAA J. Autom. Sin.* (2017), <http://dx.doi.org/10.1109/JAS.2017.7510424>.
- [42] Z.P. Tian, J. Wang, J.Q. Wang, H.Y. Zhang, Simplified neutrosophic linguistic multi-criteria group decision-making approach to green product development, *Group Decis. Negotiat.* 26 (3) (2017) 597–627.
- [43] F. Karaaslan, Possibility neutrosophic soft sets and PNS-decision making method, *Appl. Soft Comput.* 54 (2017) 403–414.
- [44] P. Liu, X. Liu, The neutrosophic number generalized weighted power averaging operator and its application in multiple attribute group decision making, *Int. J. Mach. Learn. Cybernet.* 9 (2) (2018) 347–358.
- [45] L. Zhou, H. Chen, A generalization of the power aggregation operators for linguistic environment and its application in group decision making, *Knowl.-Based Syst.* 26 (2012) 216–224.
- [46] Z. Chen, P. Liu, Z. Pei, An approach to multiple attribute group decision making based on linguistic intuitionistic fuzzy numbers, *Int. J. Comput. Intell. Syst.* 8 (4) (2015) 747–760.
- [47] S.P. Wan, J.Y. Dong, Power geometric operators of trapezoidal intuitionistic fuzzy numbers and application to multi-attribute group decision making, *Appl. Soft Comput.* 29 (2015) 153–168.
- [48] J. Wang, J.Q. Wang, H.Y. Zhang, X.H. Chen, Multi-criteria group decision-making approach based on 2-tuple linguistic aggregation operators with multi-hesitant fuzzy linguistic information, *Int. J. Fuzzy Syst.* 18 (1) (2016) 81–97.
- [49] W. Jiang, B. Wei, X. Liu, X. Li, H. Zheng, Intuitionistic fuzzy power aggregation operator based on entropy and its application in decision making, *Int. J. Intell. Syst.* 33 (1) (2018) 49–67.
- [50] M.S.A. Khan, S. Abdullah, A. Ali, F. Amin, Pythagorean fuzzy prioritized aggregation operators and their application to multi-attribute group decision making, *Granular Comput.* (2018), <http://dx.doi.org/10.1007/s41066-018-0093-6>.
- [51] P. Liu, J. Liu, J.M. Merigó, Partitioned heronian means based on linguistic intuitionistic fuzzy numbers for dealing with multi-attribute group decision making, *Appl. Soft Comput.* 62 (2018) 395–422.
- [52] K. Rahman, S. Abdullah, A. Ali, Some induced aggregation operators based on interval-valued pythagorean fuzzy numbers, *Granular Comput.* (2018), <http://dx.doi.org/10.1007/s41066-018-0091-8>.
- [53] J. Ye, Multicriteria decision-making method using the correlation coefficient under single-valued neutrosophic environment, *Int. J. Gen. Syst.* 42 (4) (2013) 386–394.
- [54] J. Ye, Another form of correlation coefficient between single valued neutrosophic sets and its multiple attribute decision-making method, *Neutrosophic Sets Syst.* 1 (1) (2013) 8–12.
- [55] J. Ye, Similarity measures between interval neutrosophic sets and their applications in multicriteria decision-making, *J. Intell. Fuzzy Syst.* 26 (1) (2014) 165–172.
- [56] J. Ye, A multicriteria decision-making method using aggregation operators for simplified neutrosophic sets, *J. Intell. Fuzzy Syst.* 26 (5) (2014) 2459–2466.
- [57] L. Yang, B. Li, A multi-criteria decision-making method using power aggregation operators for single-valued neutrosophic sets, *Int. J. Database Theory Appl.* 9 (2) (2016) 23–32.
- [58] V.L.G. Nayagam, S. Jeevaraj, P. Dhanasekaran, An intuitionistic fuzzy multi-criteria decision-making method based on non-hesitance score for interval-valued intuitionistic fuzzy sets, *Soft Comput.* 21 (23) (2017) 7077–7082.
- [59] P. Biswas, S. Pramanik, B.C. Giri, TOPSIS method for multi-attribute group decision-making under single-valued neutrosophic environment, *Neural Comput. Appl.* 27 (3) (2016) 727–737.

- [60] S. Pramanik, P. Biswas, B.C. Giri, Hybrid vector similarity measures and their applications to multi-attribute decision making under neutrosophic environment, *Neural Comput. Appl.* 28 (5) (2017) 1163–1176.
- [61] E. Bolturk, C. Kahraman, A novel interval-valued neutrosophic AHP with cosine similarity measure, *Soft Comput.* (2018), <http://dx.doi.org/10.1007/s00500-018-3140-y>.
- [62] H. Garg, K. Kumar, An advanced study on the similarity measures of intuitionistic fuzzy sets based on the set pair analysis theory and their application in decision making, *Soft Comput.* (2018), <http://dx.doi.org/10.1007/s00500-018-3202-1>.
- [63] J. Ye, Single valued neutrosophic cross-entropy for multi criteria decision making problems, *Appl. Math. Model.* 38 (2014) 1170–1175.
- [64] X. Qi, C. Liang, J. Zhang, Generalized cross-entropy based group decision making with unknown expert and attribute weights under interval-valued intuitionistic fuzzy environment, *Comput. Ind. Eng.* 79 (2015) 52–64.
- [65] Z.P. Tian, H.Y. Zhang, J. Wang, J.Q. Wang, X.H. Chen, Multi-criteria decision-making method based on a cross-entropy with interval-valued neutrosophic sets, *Int. J. Syst. Sci.* 47 (15) (2016) 3598–3608.
- [66] X.H. Wu, J.Q. Wang, J.J. Peng, X.H. Chen, Cross-entropy and prioritized aggregation operator with simplified neutrosophic sets and their application in multi-criteria decision-making problems, *Int. J. Fuzzy Syst.* 18 (6) (2016) 1104–1116.
- [67] X. Gou, Z.-S. Xu, H. Liao, Hesitant fuzzy linguistic entropy and cross-entropy measures and alternative queuing method for multiple criteria decision making, *Inf. Sci.* 388–389 (2017) 225–246.
- [68] S. Das, S. Kumar, S. Kar, T. Pal, Group decision making using neutrosophic soft matrix: an algorithmic approach, *J. King Saud Univ.-Comput. Inf. Sci.* (2017), <http://dx.doi.org/10.1016/j.jksuci.2017.05.001>.
- [69] R.R. Yager, On ordered weighted averaging aggregation operators in multi-criteria decision making, *IEEE Trans. Syst. Man Cybernet.* 18 (1) (1988) 183–190.
- [70] Z.S. Xu, R.R. Yager, Some geometric aggregation operators based on intuitionistic fuzzy sets, *Int. J. Gen. Syst.* 35 (4) (2006) 417–433.
- [71] R.R. Yager, The power average operator, *IEEE Trans. Syst. Man Cybernet A Syst. Hum.* 31 (2001) 724–731.
- [72] Z.S. Xu, R.R. Yager, Power-geometric operators and their use in group decision making, *IEEE Trans. Fuzzy Syst.* 18 (2010) 94–105.
- [73] T.L. Saaty, *Multicriteria Decision Making: the Analytic Hierarchy Process*, McGraw-Hill, New York, 1980.
- [74] T.L. Saaty, Decision-making with the AHP: why is the principal eigenvector necessary? *Eur. J. Oper. Res.* 145 (2003) 85–91.
- [75] T.L. Saaty, Decision making with the analytic network process, *Int. Ser. Oper. Res. Manage. Sci.* 95 (2006) 1–26.
- [76] T.L. Saaty, M.A. Sodenkamp, Making decisions in hierarchic and network systems, *Int. J. Appl. Decis. Sci.* 1 (2009) 24–79.
- [77] G. Coletti, R. Scozzafava, Conditional probability, fuzzy sets, and possibility: a unifying view, *Fuzzy Sets Syst.* 144 (2004) 227–249.
- [78] D. Dubois, H. Prade, The three semantics on fuzzy sets, *Fuzzy Sets Syst.* 90 (1997) 141–150.
- [79] F. Smarandache, R. Sunderraman, H. Wang, Y. Zhang, Interval neutrosophic sets and logic: theory and applications in computing, in: *HEXIS Neutrosophic Book Series*, 5. Books on Demand, Ann Arbor, MI, 2005.
- [80] H. Wang, F. Smarandache, Y. Zhang, R. Sunderraman, Single valued neutrosophic sets, *Rev. Air Force Acad.: Sci. Inf. Rev.* 1 (2010) 10–15.
- [81] U. Rivieccio, Neutrosophic logics: prospects and problems, *Fuzzy Sets Syst.* 159 (2008) 1860–1868.
- [82] S.F. Ghaderi, A. Azadeh, B. Pourvalikhah Nokhandan, E. Fathi, Behavioral simulation and optimization of generation companies in electrical markets by fuzzy cognitive map, *Expert Syst. Appl.* 39 (2012) 4635–4646.
- [83] B. Cavallo, L.D. D'Apuzzo, A general unified framework for pairwise comparison matrices in multicriterial methods, *Int. J. Intell. Syst.* 24 (2009) 377–398.
- [84] P. Grošelj, L.Z. Stirk, Acceptable consistency of aggregated comparison matrices in analytic hierarchy process, *Eur. J. Oper. Res.* 223 (2012) 417–420.
- [85] A.Z. Grzybowski, Note on a new optimization based approach for estimating priority weights and related consistency index, *Expert Syst. Appl.* 39 (2012) 11699–11708.
- [86] J. Aczel, C. Alsina, On synthesis of judgments, *Socio-Econ. Plann. Sci.* 20 (1986) 333–339.
- [87] J. Dezert, Open questions in neutrosophic inferences, *Multip.-Valued Logic/ Int. J.* 8 (2002) 439–472.
- [88] I. Deli, Y. Şubaş, A ranking method of single valued neutrosophic numbers and its applications to multi-attribute decision making problems, *Int. J. Mach. Learn. Cybernet.* 8 (4) (2017) 1309–1322.
- [89] S.A. Jackson, S. Kleitman, Individual differences in decision-making and confidence: capturing decision tendencies in a fictitious medical test, *Metacogn. Learn.* 9 (1) (2014) 25–49.
- [90] P. Iannello, V. Perucca, S. Riva, A. Antonietti, G. Pravettoni, What do physicians believe about the way decisions are made? A pilot study on metacognitive knowledge in the medical context, *Eur. J. Psychol.* 11 (4) (2015) 691.
- [91] S.A. Jackson, S. Kleitman, L. Stankov, P. Howie, Individual differences in decision making depend on cognitive abilities, monitoring and control, *J. Behav. Decis. Mak.* 30 (2) (2017) 209–223.