BRUSSELS
SCHOOL
OF ENGINEERING

edcSMOKE: A new combustion solver for stiff chemistry based on OpenFOAM®

Zhiyi Li, Mohammad Rafi Malik, Alberto Cuoci and Alessandro Parente

Symposium Multiscale-Multiphysics approaches for engineering applications

Contents

- Introduction
- EDC model and edcSMOKE
- Validation test cases
- Conclusions
- Prospects

Contents

- Introduction
- EDC model and edcSMOKE
- Validation test cases
- Conclusions
- Prospects

Combustion processes

- Laminar flame

Source: www.guilford.eng.yale.edu

- Turbulent flame

Source: crf.sandia.gov

Most combustions in applications are turbulent combustions.

- Pollution

Problems of combustion

- Dilemma

NO_x formation trend with increased energy savings

Combustions modelling helps to find a solution to these issues with low cost.

Challenges of turbulent combustion modelling

Multi-scale (decades of scales) and **multi-physics** (fluid dynamics, chemical kinetics): detailed chemistry

Prohibitive number of tightly coupled **equations** for real fuels and systems ($5 + N_{sp}$): high demand of computational resources

Turbulent combustion modelling approaches

Currently popular combustion models:

Model selected: EDC

- Accuracy and cost are acceptable
- Detailed chemistry can be applied in EDC model

Turbulent combustion modelling approaches

Currently popular combustion models:

Model selected: EDC

- Accuracy and cost are acceptable
- Detailed chemistry can be applied in EDC model

Contents

- Introduction
- EDC model and edcSMOKE
- Validation test cases
- Conclusions
- Prospects

Eddy Dissipation Concept can be coupled to finite rate chemistry

- Mean reaction rate

$$\bar{\omega}_k = -\frac{\bar{\rho}\gamma_\lambda^2}{\tau^*(1-\gamma_\lambda^3)}(\tilde{y}_k - y_k^*) \quad \tilde{y}_k = \gamma_\lambda^3 y_k^* + (1 - \gamma_\lambda^3) y_k^0 \quad (\text{'EDC1996'})$$

- Model parameters come from an energy cascade model
- Model constants

$$C_\gamma = 2.1377 \quad C_\tau = 0.4083$$

(Magnussen, 1996)

EDC model formulations

Different versions of EDC model are proposed by Magnussen et al.

$$\overline{\dot{\omega}}_k = -\frac{\bar{\rho} \gamma_\lambda^3}{\tau^* (1 - \gamma_\lambda^3)} (\tilde{y}_k - y_k^*) \quad \tilde{y}_k = \gamma_\lambda^3 y_k^* + (1 - \gamma_\lambda^3) y_k^0 \quad (\text{'EDC1981'})$$

$$\overline{\dot{\omega}}_k = -\frac{\bar{\rho} \gamma_\lambda^2}{\tau^* (1 - \gamma_\lambda^3)} (\tilde{y}_k - y_k^*) \quad \tilde{y}_k = \gamma_\lambda^3 y_k^* + (1 - \gamma_\lambda^3) y_k^0 \quad (\text{'EDC1996'})$$

$$\overline{\dot{\omega}}_k = -\frac{\bar{\rho} \gamma_\lambda^2}{\tau^* (1 - \gamma_\lambda^2)} (\tilde{y}_k - y_k^*) \quad \tilde{y}_k = \gamma_\lambda^2 y_k^* + (1 - \gamma_\lambda^2) y_k^0 \quad (\text{'EDC2005'})$$

Coupling of EDC model and OpenFOAM

Contents

- Introduction
- EDC model and edcSMOKE
- **Validation test cases**
- Conclusions
- Prospects

Validation on flame combustion case:

Sandia flame D

Sandia flame D: experimental and numerical set-up

Flame details

Fuel: CH₄/Air (25%, 75% mass)

Pilot: mixture of C₂H₂/H₂ /air/CO₂ /N₂

Reynolds number: 22,400

Geometry

Fuel nozzle diameter: 7.2 mm

Coflow diameter: 18.2 mm

Computational details

Domain: 2D axisymmetric (150 x 650 mm)

Computational grid: ~4600 cells

Solver: steady edcSimpleSMOKE

Turbulent model: RANS k-epsilon

Kinetic schemes

GRI3.0: 53 species, 325 reactions

PolimiC1C3HTNOX: 114 species, 2,105 reactions

Sandia flame D: modelling results of mean temperature profiles

Validation on flame combustion case:

DLR flame A

DLR flame A: experimental and numerical set-up

Flame details

Fuel: CH₄/Air/N₂ (22.1%, 33.2%, 44.7% volume)

Co-flow: air and 0.8% mole fraction H₂O

Reynolds number: 15,200

Geometry

Fuel nozzle diameter: 8.0 mm

Coflow diameter: 140 mm

Computational details

Domain: 2D axisymmetric (190 x 1000 mm)

Computational grid: ~3500 cells

Solver: steady edcSimpleSMOKE

Turbulent model: RANS k-epsilon

Kinetic schemes

GRI3.0: 53 species, 325 reactions

$x/d = n$

DLR flame A: modelling results of mean CO_2 mass fraction profiles

Validation on flameless (MILD) combustion case:

Adelaide Jet in Hot Co-flow (JHC) burner

MILD (flameless) combustion

The Moderate or Intense Low oxygen Dilution (MILD) combustion:

- Preheated oxidizer stream
- Distributed reaction zone
- No visible flame

Advantages :

- High efficiency
- Low NO_x and CO emissions

Adelaide Jet in Hot Co-flow (JHC) burner

JHC burner: experimental and numerical set-up

Flame details

Fuel: CH₄/H₂ (50%, 50% volume)

Co-flow: mixture of CH₄/H₂ /air/CO₂ /H₂O/CO/N₂/O₂

Co-flow Temperature: 1300 K

Reynolds number: 10,000

Geometry

Fuel nozzle diameter: 4.25 mm

Coflow diameter: 82.0 mm

Computational details

Domain: 2D axisymmetric (254 x 1000 mm)

Computational grid: ~30,000 cells

Solver: unsteady edcPimpleSMOKE

Turbulent model: RANS k-epsilon

Kinetic schemes (Nox free)

KEE: 17 species, 58 reactions

GR13.0: 36 species, 219 reactions

SAN_DIEGO: 50 species, 247 reactions

Modelling results: Comparison of mean Temperature profiles from different EDC model formulations

K-epsilon model constant $C_{1\epsilon} = 1.60$.

Modelling results: Comparison of mean Temperature profiles from different detailed chemistry mechanisms

Contents

- Introduction
- EDC model and edcSMOKE
- Validation test cases
- **Conclusions**
- Prospects

Conclusions

- Satisfactory prediction results can be obtained with the edcSMOKE solvers;
- Both the steady and unsteady solvers give relative good results in prediction;
- The EDC combustion model can be adopted in flame and flameless combustion;
- Large mechanisms can be used in combination with this solver.

Contents

- Introduction
- EDC model and edcSMOKE
- Validation test cases
- Conclusions
- **Prospects**

Prospects

- Chemistry reduction method is supposed to be implemented to save the computational time;
- Using Large Eddy Simulation to solve part of the turbulence;
- Compare the EDC model with Partially Stirred Reactor (PaSR) combustion model.

Acknowledgements

“This project has received funding from the European Union’s Horizon 2020 research and innovation program under the Marie Skłodowska-Curie grant agreement No 643134”.

And from the Fédération Wallonie-Bruxelles, via ‘Les Actions de Recherche Concertée (ARC)’ call for 2014 - 2019, to support fundamental research.

Thank you

Questions?

zhiyi.li@ulb.ac.be