See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/325852392>

Enhancement of hydrogen production rate by high biomass concentrations of *Thermotoga neapolitana*

Article in *International Journal of Hydrogen Energy* · June 2018

DOI: 10.1016/j.ijhydene.2018.05.072

CITATIONS

11

READS

176

6 authors, including:

Gilbert Dreschke

Università degli studi di Cassino e del Lazio Meridionale

8 PUBLICATIONS 93 CITATIONS

[SEE PROFILE](#)

Giuliana d'Ippolito

Italian National Research Council

113 PUBLICATIONS 2,494 CITATIONS

[SEE PROFILE](#)

Antonio Panico

Università degli Studi della Campania "Luigi Vanvitelli

68 PUBLICATIONS 2,425 CITATIONS

[SEE PROFILE](#)

P.N.L. Lens

IHE Delft Institute for Water Education

986 PUBLICATIONS 26,765 CITATIONS

[SEE PROFILE](#)

Some of the authors of this publication are also working on these related projects:

Effect of nitrate and sulfate on selenate bioreduction and influence of pH on reactor operation [View project](#)

Total Synthesis of Natural products [View project](#)

Available online at www.sciencedirect.com

ScienceDirect

journal homepage: www.elsevier.com/locate/hydro

Enhancement of hydrogen production rate by high biomass concentrations of *Thermotoga neapolitana*

Gilbert Dreschke^{a,b,*}, Giuliana d'Ippolito^b, Antonio Panico^c,
Piet N.L. Lens^d, Giovanni Esposito^a, Angelo Fontana^b

^a Department of Civil and Mechanical Engineering, University of Cassino and Southern Lazio, Via Di Biasio, 43, 03043, Cassino, FR, Italy

^b Bio-Organic Chemistry Unit, Institute of Biomolecular Chemistry, Italian National Council of Research, Via Campi Flegrei 34, 80078, Pozzuoli, Napoli, Italy

^c Telematic University Pegaso, Piazza Trieste e Trento, 48, 80132, Naples, Italy

^d UNESCO – IHE Institute for Water Education, Westvest 7, 2611-AX Delft, The Netherlands

ARTICLE INFO

Article history:

Received 23 February 2018

Received in revised form

28 April 2018

Accepted 13 May 2018

Available online 19 June 2018

Keywords:

Hydrogen

Thermotoga neapolitana

Biomass concentration

Dark fermentation

Hyperthermophilic

ABSTRACT

The objective of this study was to enhance the hydrogen production rate of dark fermentation in batch operation. For the first time, the hyperthermophilic pure culture of *Thermotoga neapolitana* cf. *Capnolactica* was applied at elevated biomass concentrations. The increase of the initial biomass concentration from 0.46 to 1.74 g cell dry weight/L led to a general acceleration of the fermentation process, reducing the fermentation time of 5 g glucose/L down to 3 h with a lag phase of 0.4 h. The volumetric hydrogen production rate increased from 323 (± 11) to 654 (± 30) mL/L/h with a concomitant enhancement of the biomass growth and glucose consumption rate. The hydrogen yield of 2.45 (± 0.09) mol H₂/mol glucose, the hydrogen concentration of 68% in the produced gas and the composition of the end products in the digestate, i.e. 62.3 (± 2.5)% acetic acid, 23.5 (± 2.9)% lactic acid and 2.3 (± 0.1)% alanine, remained unaffected at increasing biomass concentrations.

© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.

Introduction

Hydrogen (H₂) is a non-polluting and clean fuel of the future with a wide range of applications [1,2]. The demand for hydrogen is continuously increasing and expected to contribute 8–10% to the energy market by 2025 [1].

Biotechnological hydrogen production processes have advanced in recent years and revealed promising results for an environmentally friendly production route [1,3]. Dark fermentation is thereby considered as the most attractive process due to its simplicity, independence of light and the potential to use substrates from renewable sources. However, the low H₂ production rate observed in dark fermentation still

Abbreviations: CDW, Cell dry weight [g/L]; HPR, Hydrogen production rate; AA, Acetic acid; LA, Lactic acid.

* Corresponding author. Department of Civil and Mechanical Engineering, University of Cassino and Southern Lazio, Via Di Biasio, 43, 03043, Cassino, FR, Italy.

E-mail addresses: gilbert.dreschke@icb.cnr.it (G. Dreschke), gdippolito@icb.cnr.it (G. d'Ippolito), antonio.panico@unipegaso.it (A. Panico), p.lens@unesco-ihe.org (P.N.L. Lens), giovanni.esposito@unicas.it (G. Esposito), afontana@icb.cnr.it (A. Fontana).

<https://doi.org/10.1016/j.ijhydene.2018.05.072>

0360-3199/© 2018 Hydrogen Energy Publications LLC. Published by Elsevier Ltd. All rights reserved.

remains a fundamental challenge [4–6]. The hydrogen production rate (HPR) is crucial for the production at industrial scale [7] and a considerable increase is required for the establishment of an economically viable process [8,9].

Thermotoga neapolitana is a hyperthermophilic organism with a great potential for hydrogen production through dark fermentation [10]. This bacterium grows on a wide range of substrates including glucose, fructose, xylose, maltose, starch, glycogen, glycerol, molasses, cheese whey, algal biomass and carrot pulp [11–15]. The microorganism has fast growth kinetics [16], oxygen tolerance [14] and low contamination risks due to the extreme culture conditions at 80 °C [17]. Previous studies using *Thermotoga neapolitana* have primarily focused on the optimization of the hydrogen yield in batch fermentation [14,18–20]. Yields approaching the theoretical 4 mol H₂/mol glucose have been reached when applying 5–10% of inoculum (v/v) [2,14,21]. Promising results of *Thermotoga neapolitana* in attached growth [22–24] further emphasize the potential of the organism, indicating towards a possible use in a biofilm reactor system. However, low HPRs between 23 and 50 mL/L/h observed in simple batch cultivation using *Thermotoga neapolitana* [14] demonstrate the need for further development.

Despite the lower H₂ yields, the highest HPRs are currently reached under mesophilic conditions due to their capability to grow in high biomass concentrations [25]. A positive correlation was demonstrated between the HPR and the biomass concentration in the reactor in continuous dark fermentations [6]. Hyperthermophilic cultures reach much higher hydrogen yields [26], but they commonly grow in low cell densities [5] leading to low H₂ production rates. A substantial improvement of the HPR is expected if hyperthermophilic cultures are cultivated at high biomass concentrations [25,27]. In batch cultivation of suspended cell, high biomass concentrations are generally implemented by the recycling of biomass, which enables a faster and more robust process [27].

In the present study, a suspended culture of pure *Thermotoga neapolitana* biomass was used at different concentrations ranging from 0.46 to 1.74 g/L to mimic a sequential batch fermentation described by Basso et al. [28]. The main objective was to induce an acceleration of the dark fermentation process, in particular the HPR. Simultaneously, the effect of elevated biomass concentrations on the efficiency of the process and the kinetics of hydrogen production, glucose consumption and biomass growth were evaluated.

Material and methods

Culture medium

A modified ATCC 1977 culture medium as described by d'Ippolito et al. [19] was used for the cultivation of *Thermotoga neapolitana* containing the following components (in g/L): 10 NaCl; 5 glucose; 2 yeast extract; 2 tryptone; 1 cysteine; 1 NH₄Cl; 0.3 K₂HPO₄; 0.3 KH₂PO₄; 0.2 MgCl₂·6H₂O; 0.1 KCl; 0.1 CaCl₂·2H₂O; 0.001 resazurin dissolved in distilled water, supplemented with 10 mL/L of vitamin and 10 mL/L of trace element solutions (DSM medium 141).

Bacterial strain – cultivation and storage

A pure culture of *Thermotoga neapolitana* cf. *Capnolactica* [29] (hereafter briefly *Thermotoga neapolitana*) was used in all experiments. For the conservation of the culture, 120 mL serum bottles containing 25 mL of culture medium were prepared. Prior to the inoculation, the medium was heated to remove excess oxygen until losing the characteristic resazurin color, sealed immediately with butyl rubber stoppers and sterilized by autoclaving for 5 min at 110 °C [19]. The medium was inoculated using 6% (v/v) of stored cell cultures. After the cultivation at 80 °C without agitation overnight, the grown culture was stored at 4 °C [30].

Preparation of inoculum

The inoculum was produced in two 3 L continuously stirred tank reactors (Applikon Biotechnology, The Netherlands) each containing 2000 mL of culture medium. The medium was heated to 80 °C and sparged with CO₂ for 5 min to remove the dissolved oxygen. Subsequently, the pH was adjusted to 7 by addition of 1 M NaOH and the reactors were inoculated using 6% v/v of stored culture (described in 2.2). The cultivation was performed at 80 °C and 200 rpm for 14.5 h to obtain a culture at the end of the stationary phase where the amount of active biomass reaches its maximum. The biomass was harvested by centrifugation at 3750 rpm for 15 min and resuspended in an isotonic solution (10 g/L NaCl in distilled water) to produce a highly concentrated inoculum (1 mL of inoculum contains biomass of 50 mL of grown culture). The biomass concentration in g CDW/L of each sampling point was estimated from the optical density at 540 nm (OD₅₄₀) using the relation CDW [g/L] = 0.269 × OD₅₄₀ – 0.061 (R² = 0,98) [20,31].

Experimental design

Eight 250 mL Schott flasks, each containing 200 mL of culture medium were used to investigate the hydrogen production from a *Thermotoga neapolitana* culture at increasing biomass concentrations. Prior to inoculation, the medium was heated to 80 °C, sparged with CO₂ for 5 min to remove oxygen and the pH adjusted to 7 by addition of 1 M NaOH, being the optimum pH for hydrogen production by *Thermotoga neapolitana* [32]. A volumetric ratio of inoculum to culture medium (v/v) is commonly used to describe the amount of inoculum applied. Considering this ratio, the concentrated inoculum (described in 2.3) was used to inoculate the reactors between 100 and 400% v/v (100% corresponding to biomass harvested from 200 ml of grown culture in 200 ml of fresh medium): C1 - 100% (= 0.46 g CDW/L), C2 - 200% (= 0.91 g CDW/L), C3 - 300% (= 1.33 g CDW/L) and C4 - 400% (= 1.74 g CDW/L). The medium was maintained at 80 °C applying 300 rpm agitation by magnetic stirring (STIRRING DRYBATH 15–250, 2 mag AG, Germany). 1.5 mL of liquid samples were taken at 1 h (C3, C4) and 30 min (C1, C2) intervals. The pH was manually adjusted to 7 by after each sampling. The produced gas was released continuously and quantified with 500 mL water displacement systems. The fermentation was completed when the gas production stopped, and the pH remained constant. Each experimental condition was conducted in duplicate.

Analytical methods

Liquid samples were centrifuged at 10000 rpm for 5 min to collect the supernatant for the determination of glucose, acetic acid (AA), lactic acid (LA) and alanine concentrations. The glucose concentration was measured by the dinitrosalicylic acid method calibrated on a standard solution of 1 g/L [33]. AA, LA and alanine were quantified by ^1H Nuclear Magnetic Resonance (NMR) on a 600 MHz spectrometer (Bruker Avance 400) equipped with a Cryoprobe using 3.8 mM trimethylamine hydrochloride (TMA) as internal standard [34]. The biomass concentration was determined by measuring optical density at 540 nm (OD_{540}) (UV/Vis spectrophotometer DU 730, Beckman Coulter Inc, Brea, USA) of the liquid samples and the CDW via lyophilization after the completion of the fermentation. For this purpose, 200 mL of culture broth was centrifuged at 3750 rpm for 20 min. The pellet was subsequently resuspended in 25 mL of 10 g/L NaCl in distilled water and centrifuged at 6000 rpm for 20 min to remove remaining media components. The pellet was stored at -20°C and lyophilized overnight.

Produced gas was quantified by water displacement using 500 mL glass containers. At the end of each experiment, the H_2 -containing gas was sampled and analyzed by gas chromatography as described by Dipasquale et al. [13]. The molar H_2 production was calculated using the ideal gas law [7]. The hydrogen concentration in the produced gas was calculated considering a dilution of the measured gas with the CO_2 initially in the headspace of the reactor.

Kinetic study of glucose consumption, biomass growth and biohydrogen production

To evaluate and compare glucose consumption, biomass growth and hydrogen production at the different biomass concentrations investigated, models based on the Gompertz equation [14,35] were applied to fit the experimental data and calculate the kinetic rates and lag phases. To validate the suitability of the modified Gompertz model, the models of glucose consumption, biomass growth and hydrogen production were plotted against the experimental data. The quality of the fitting was determined by calculating the coefficients of determination (R^2). The specific rates were calculated referring the volumetric rates to the initial biomass concentration of each experimental condition.

For glucose consumption, Eq. (1) was applied, where G [g/L] is the glucose concentration at fermentation time t [h]; G_0 [g/L] is the glucose concentration at time 0 h; G_m [g/L] is the glucose consumed throughout the fermentation; R_G is the volumetric

glucose consumption rate [g/L/h]; λ_G is the lag phase of glucose consumption [h]; and e is the Euler's number, i.e. 2.7183.

For biomass growth, Eq. (2) was applied, where B [g CDW/L] is the biomass concentration at fermentation time t [h]; B_0 [g CDW/L] is the biomass concentration at time 0 h; G_m [g CDW/L] is the gain of biomass concentration throughout the fermentation; R_B is the volumetric growth rate [g CDW/L/h]; and λ_B is the lag phase of biomass growth [h].

Eq. (3) was applied for hydrogen production, with H [mL/L] being the cumulative hydrogen at time t [h]; H_m [mL/L] the hydrogen produced throughout the fermentation; R_H [mL/L/h] the volumetric HPR; and λ_H the lag phase of hydrogen production [h]. For the calculation of the HPR, the gas remaining in the headspace of the reactor at the end of the fermentation was equally distributed throughout the length of the batch experiment.

$$G = G_0 - G_m \exp \left\{ -\exp \left[\frac{R_G}{G_m} e (\lambda_G - t) + 1 \right] \right\} \quad (1)$$

$$B = B_0 + B_m \exp \left\{ -\exp \left[\frac{R_B}{B_m} e (\lambda_B - t) + 1 \right] \right\} \quad (2)$$

$$H = H_m \exp \left\{ -\exp \left[\frac{R_H}{H_m} e (\lambda_H - t) + 1 \right] \right\} \quad (3)$$

Results and discussion

Hydrogen yield and production rate

A change of the initial biomass concentration between 0.46 and 1.74 g/L did not affect the hydrogen yield i.e. $2.45 (\pm 0.09)$ mol H_2 /mol glucose (Table 1) or the composition of the biogas that maintained a constant level of hydrogen at $67.6 (\pm 2.4)\%$ (data not shown). The HPR observed at the lowest initial biomass concentration of 0.46 g CDW/L (C1) reached $323 (\pm 11)$ mL/L/h (Table 2). A further increment of the biomass concentration to 0.91 (C2), 1.33 (C3) and 1.74 g CDW/L (C4) increasingly enhanced the volumetric HPR to $448 (\pm 18)$, $608 (\pm 18)$ and $654 (\pm 30)$ mL/L/h (Fig. 1 B; Table 2), respectively. On the whole, a fourfold expansion of the biomass concentration caused an approximately twofold increase of the volumetric production rate. This is consistent with previous studies on dark fermentation by anaerobic sludge in closed serum bottles, where a general increase of HPR was obtained by raising the biomass concentrations [36,37]. On the other hand, Ngo and coworkers reported a reverse correlation between the two parameters in a fed batch process using *T. neapolitana*. In 4

Table 1 – Hydrogen yield, cumulative hydrogen, final biomass and biomass yield fermenting 5 g/L glucose at different initial biomass concentrations of *Thermotoga neapolitana*.

	Initial biomass [g CDW/L]	Hydrogen yield [mol H_2 /mol glucose]	Cumulative hydrogen [mL/L]	Final biomass [g CDW/L]	Biomass yield [g CDW/g glucose]
C1	0.46	2.39	1462 (± 12)	1.10 (± 0.03)	0.14
C2	0.91	2.44	1477 (± 3)	1.43 (± 0.09)	0.12
C3	1.33	2.58	1516 (± 10)	1.89 (± 0.06)	0.13
C4	1.74	2.37	1456 (± 5)	2.10 (± 0.15)	0.08

Table 2 – *Thermotoga neapolitana* cultivated on 5 g/L of glucose as a main substrate using different initial biomass concentrations. Rates and lag phase determined through curve fitting to a modified Gompertz model. Fit quality illustrated through coefficient of determination (R^2).

	Initial biomass	Volumetric rate	Specific rate	Lag phase	R^2
Hydrogen production					
	[g CDW/L]	[mL/L/h]	[mL/h/g initial CDW]	[h]	
C1	0.46	323 (± 11)	699 (± 23)	1.50 (± 0.07)	0.99
C2	0.91	448 (± 18)	494 (± 20)	0.79 (± 0.01)	0.99
C3	1.33	608 (± 18)	456 (± 13)	0.52 (± 0.01)	0.99
C4	1.74	654 (± 30)	375 (± 17)	0.40 (± 0.02)	0.99
Biomass growth					
	[g CDW/L]	[mg CDW/L/h]	[mg CDW/h/g initial CDW]		
C1	0.46	190 (± 0)	412 (± 0)		0.99
C2	0.91	230 (± 0)	254 (± 0)		0.98
C3	1.33	320 (± 0)	240 (± 0)		0.96
C4	1.74	400 (± 28)	229 (± 16)		0.98
Glucose consumption					
	[g CDW/L]	[g Glucose/L/h]	[g Glucose/h/g initial CDW]		
C1	0.46	1.08 (± 0.04)	2.33 (± 0.08)		0.99
C2	0.91	1.40 (± 0.00)	1.55 (± 0.00)		0.98
C3	1.33	1.98 (± 0.04)	1.48 (± 0.03)		0.98
C4	1.74	2.35 (± 0.07)	1.35 (± 0.04)		0.99

feeding cycles, the authors observed an increase of the initial biomass from 1.3 ± 0.1 to 2.4 ± 0.1 g/L yielding a mild reduction of HPR from 114 to 106 mL/L/h [32]. Simultaneously, acetic acid and lactic acid accumulated in the fermentation broth up to 123 ± 7 and 28 ± 1 mM, respectively, which could potentially have caused an inhibitory effect.

While hyperthermophilic cultures are capable to achieve even higher hydrogen yields (Table 3) the volumetric HPR observed in this work exceeds those achieved in similar studies using pure hyperthermophilic cultures at low biomass concentrations (Table 3).

The highest production rate of $654 (\pm 30)$ mL/L/h (C4) (Table 2) depicts a roughly 13-fold increase to the maximum

production rate of 50 mL/L/h achieved in similar experiments using *Thermotoga neapolitana* in batch cultures with 6% (v/v) of inoculum and 5 g/L of glucose as a substrate [19]. Only two studies achieved HPRs in a similar range. Mars et al. [31] and de Vrije et al. [11] reached production rates of 269 and 304 mL/L/h, respectively, by continuously flushing the reactor head-space with N_2 gas at 7 L/h both using 10% (v/v) of preculture as inoculum and 10 g glucose/L as a substrate. While gas sparging is a common method to counteract hydrogen inhibition [25,44], it is an unsatisfying solution due to a manifold dilution of the produced hydrogen gas. The resulting need to separate the sparging gas from the hydrogen creates additional operating cost [45].

Fig. 1 – A - Volumetric and specific growth rate; B - Volumetric as well as specific glucose consumption and hydrogen production rate at different initial biomass concentrations (C1 = 0.46; C2 = 0.91; C3 = 1.33; C4 = 1.74 g CDW/L) of *Thermotoga neapolitana* fermenting 5 g/L of glucose. Specific rates were calculated per g initial cell dry weight. (GR – Growth rate; HPR – Hydrogen production rate; GCR – Glucose consumption rate).

Table 3 – Hydrogen production rate and hydrogen yield of selected studies of batch fermentations by various hyperthermophilic pure cultures using glucose as a substrate.

Microorganism	Hydrogen production rate [mL/L/h]	Hydrogen yield [mol H ₂ /mol glucose]	Reference
<i>Caldicellulosiruptor saccharolyticus</i>	264	2.5	[38]
	296	3.4	[31]
	277	3.2	[11]
<i>Thermotoga elfi</i>	200	3.3	[39]
<i>Thermotoga maritima</i>	170	4	[40]
<i>Thermotoga neapolitana</i>	304	2.9	[31]
	269	3.5	[11]
	21	3.9	[18]
	252	1.8	[20]
	50	3.9	[19]
<i>Thermoanaerobacter mathranii</i> A3N	100	2.6	[41]
<i>Thermoanaerobacterium thermosaccharolyticum</i> PSU-2	287	2.4	[42]
<i>Thermoanaerobacterium thermosaccharolyticum</i> W16	309	2.4	[43]
<i>Thermotoga neapolitana</i>	654	2.5	Present study

Volumetric and specific rates of glucose consumption, biomass growth and hydrogen production

Volumetric (per L of working volume) and specific (per g CDW) glucose consumption, biomass growth and HPRs (Fig. 1, Table 2) were calculated via the Gompertz model (described in 2.6) (Fig. 2). The increase of the volumetric HPR with increasing biomass concentrations was coupled to a general acceleration of the process, indicated by an increase of the volumetric biomass growth and glucose consumption rate (Table 2). The calculation of the Pearson correlation coefficient, confirmed a positive linear correlation of volumetric glucose consumption rate and volumetric growth rate ($r = 0.99$) as well as volumetric HPR ($r = 0.99$). In contrast, all specific rates (Fig. 1, Table 2) exhibited a decreasing trend with increasing biomass concentrations. This suggests that the overall process was considerably accelerated, while the individual cells were partially repressed at increased biomass concentration. The decrease in specific rates was particularly distinct between C1 and C2. The specific glucose consumption rate (g glucose/h/g CDW) dropped by 34% from 2.33 (± 0.08) of C1 to 1.55 (± 0) of C2 and by 9% to 1.35 (± 0.04) of C4 (Table 2). The specific growth rate (mg CDW/h/g CDW) decreased by 38% from 412 (± 0) of C1 to 254 (± 0) of C2 and merely by 6%–229 (± 16) of C4 (Table 2). The specific HPR (mL/h/g CDW) decreased by 29% from 699 (± 23) of C1 to 494 (± 20) of C2 and by 17%–375 (± 17) of C4 (Table 2). A similar trend of decreasing specific HPR was observed in previous studies when the initial biomass was increased using mixed cultures [36,37]. Kargi et al. [37] observed a drop of the specific HPR from 48 to approximately 3 mL/h/g when the biomass concentration was increased from 0.48 to 2.88 g/L. Substrate limitation caused by flock formation [37] and hydrogen consuming homo-acetogenic bacteria [36] were presumed to be responsible for the decrease of specific HPR at higher initial biomass concentrations.

In the present study, the formation of flocks was not hydrogen was not consumed, indicated by the ratio of hydrogen to acetic acid being consistent with the dark fermentation model (Eq. (4)). However, an increase of HPR induces the accumulation of hydrogen in the liquid phase

which mainly depends on the HPR and the mass transfer rate of system [46]. The concentration of liquid phase hydrogen can reach multiple fold the equilibrium concentration suggested by Henry's Law even in hyperthermophilic stirred reactor systems [46,47], acting as a potent inhibitor of hydrogen production by dark fermentation [44,48]. In the present study, the accumulation of hydrogen was observed at the highest biomass concentration (C4) where the highest HPR was obtained. After 3 h of fermentation, the glucose consumption of C4 was completed (Fig. 2C), while hydrogen continued to be produced by the reactor (Fig. 2B), due to the transport of accumulated hydrogen from the liquid to the gas phase. According to Ljunggren et al. [46], cultures of *Caldicellulosiruptor saccharolyticus* respond to increasing concentrations of liquid phase hydrogen by adjusting the specific growth rate to reduce the HPR and prevent hydrogen from reaching inhibitory concentrations. Similarly, a reduction of specific HPRs was observed in the presented study when the volumetric production rates increased. This is supported by the results obtained in dark fermentation by *Thermotoga neapolitana*, achieving the highest hydrogen yields and production rates, when hydrogen was removed through headspace sparging with N₂ continuously [11,31] or in regular intervals [19].

Fermentation time and lag phase

The lag phase was determined via the Gompertz model, while the fermentation time was estimated from the moment of inoculation to the completion of the fermentation. An initial biomass concentration of 0.46 g CDW/L (C1) induced a lag phase of 1.50 (± 0.07) h (Table 2) and the completion of the fermentation within approximately 7 h (Fig. 2). In previous studies, the duration of the batch fermentation with *Thermotoga neapolitana* was longer than 18 h [11,23,31] when applying a 5–10% (v/v) inoculum. By increasing the initial biomass concentration to 1.74 g CDW/L (C4), the fermentation time and the lag phase were reduced to approximately 3 h (Figs. 2) and 0.4 (± 0.02) h (Table 2), respectively. This is in agreement with observations made in bioethanol production plants [28],

Fig. 2 – A – Biomass growth; B – Cumulative hydrogen and C – Glucose consumption production at different initial biomass concentrations (C1 = 0.46; C2 = 0.91; C3 = 1.33; C4 = 1.74 g CDW/L) of *Thermotoga neapolitana* fermenting 5 g/L of glucose. The solid line represents the fitting to the Gompertz model.

where yeast cultures were recycled at high densities in sequential batch fermentations resulting in the reduction of the fermentation time and the unproductive lag phase [27]. In all conditions, independent from the initial biomass concentration a substrate consumption of 88.8 (±0.9)% (data not shown) was reached at the end of the fermentation.

Biomass production

The biomass concentration at the end of a batch fermentation is defined by the initial biomass concentration, the biomass yield (g CDW/g glucose) and the amount of glucose converted. A similar formation of biomass was observed using initial biomass concentrations between 0.46 (C1) and 1.33 (C3), with a biomass yield ranging between 0.12 and 0.14 g CDW/g glucose (Table 1). In contrast, at the highest biomass concentration of 1.74 g CDW/L (C4) the biomass production was lower, corresponding to a biomass yield of 0.08 g CDW/g glucose (Table 1), similar to what observed in previous studies with lower inoculum concentrations of *Thermotoga neapolitana*. De Vrije et al. [11] and Mars et al. [31] reported biomass yields of 81.6 and 87.1 mg CDW/g glucose, respectively, using 10% inoculum (v/v) with additional headspace sparging. Ngo et al. [23] obtained 0.71 (±0.04) g CDW/L with 10 g/L pure glycerol as main substrate and 10% of inoculum (v/v). Van Niel et al. [39] reached 0.89 g CDW/L by fermenting 10 g/L glucose with 10% inoculum of *Thermotoga elfi*. At the end of each fermentation *Thermotoga neapolitana* is morphologically adapting to the nutrient limitation causing the OD₅₄₀ to decrease (Fig. 2) [49], while the CDW remains high (Table 1). Consequently, the curve fitting to the Gompertz model for biomass growth was done exclusively until the highest value of turbidity was reached (Fig. 2).

Production of fermentation products

The distribution of end products obtained in the digestate (62.3 (±2.5)% AA; 23.5 (±2.9)% LA; 2.3 (±0.1)% alanine) was similar in the range of biomass concentrations investigated (Table 4), corresponding to yields of 1.33 (±0.05) mol/mol glucose for AA, 0.50 (±0.06) mol/mol glucose for LA and 0.05 (±0.001) mol/mol glucose for alanine (Table 4). As observed in previous studies [14], *Thermotoga neapolitana* primarily ferments glucose via the hydrogen producing acetic acid (Eq. (4)) or the lactic acid pathway (Eq. (5)).

Considering a production of 2 mol of end product per mol of glucose (Eqs. (4) and (5)), an average of 95 (±1)% (data not shown) of the initial substrate could be accounted for in the fermentation broth (Table 4). Similar results were obtained by Mars et al. [31] and de Vrije et al. [11] when low inoculum concentrations were used, reporting AA yields of 1.6 and 1.4 mol/mol glucose and LA yields of <0.1 and 0.03 mol/mol glucose, respectively. The highest initial biomass concentration (C4) showed a slightly higher LA/AA ratio (Table 4) coupled with a slightly lower hydrogen yield (Table 1). This is in accordance to the dark fermentation model suggesting a negative correlation between hydrogen yield and LA/AA ratio [48].

Additionally, an impact of capnophilic lactic acid fermentation caused by sparging with CO₂ needs to be considered

Table 4 – Composition of broth after completed fermentation of 5 g/L glucose by different initial biomass concentrations (C1 = 0.46; C2 = 0.91; C3 = 1.33; C4 = 1.74 g cell dry weight/L) of *Thermotoga neapolitana*.

	AA [mM] {yield [mol/mol glu]}	LA [mM] {yield [mol/mol glu]}	Ratio LA/AA	Alanine [μM] {yield [mol/mol glu]}	Glucose [mM]
C1	34.3 (±0.6) {1.39}	10.9 (±0.4) {0.44}	0.32	1190 (±27) {0.05}	3.2 (±0.04)
C2	32.9 (±0.8) {1.32}	12.2 (±0.8) {0.49}	0.37	1260 (±1) {0.05}	2.9 (±0.06)
C3	32.3 (±0.2) {1.33}	11.5 (±0.5) {0.47}	0.36	1220 (±18) {0.05}	3.4 (±0.01)
C4	31.4 (±1.1) {1.27}	14.7 (±0.7) {0.59}	0.47	1260 (±43) {0.05}	3.0 (±0.04)

AA - acetic acid; LA - lactic acid; glu – glucose.

resulting in elevated amounts of LA without significant loss in hydrogen yield [30,34]. Dipasquale et al. [30] observed LA/AA ratio of 0.28 by N₂ sparging and 0.56 by CO₂ sparging twice throughout the batch experiment. LA/AA ratios between 0.32 and 0.47 observed in this study suggest a similar influence of capnophilic lactic acid fermentation.

Conclusion

This study identified the use of high initial biomass concentrations of *Thermotoga neapolitana* (from 0.46 to 1.74 g cell dry weight/L) as a suitable method to accelerate the dark fermentation process and increase the HPR. The four-fold increase in biomass concentration led to the consumption of 5 g/L of glucose within 3 h and accelerated the hydrogen production rate by approximately 50% reaching a maximum of 654 (±30) mL/L/h. The variation of the biomass concentration had no effect on the yield (2.45 (±0.09) mol H₂/mol glucose), the concentration of hydrogen in the produced gas (68%) or the composition of fermentation end products (i.e. 62.3 (±2.5)% AA, 23.5 (±2.9)% LA and 2.3 (±0.1)% alanine). To continue optimizing the rate of dark fermentation processes more research is required to understand the role of hydrogen in the liquid phase as an inhibitor at elevated hydrogen production rates. Furthermore, economical and environmentally friendly substrates like organic waste streams need to be investigated for their suitability in large-scale applications of the proposed process.

Acknowledgements

This work was supported by the Marie Skłodowska-Curie European Joint Doctorate (EJD) in Advanced Biological Waste-To-Energy Technologies (ABWET) funded from Horizon 2020 under grant agreement no. 643071. Angelo Fontana and Giuliana d'Ippolito thank the support from the EU Horizon 2020 Research and Innovation Program under the Grant Agreement No. 760431 (BioRECO2VER). The authors also express their appreciation to the staff of CNR-ICB for the consistent help throughout this study.

REFERENCES

- [1] Gupta SK, Kumari S, Reddy K, Bux F. Trends in biohydrogen production: major challenges and state-of-the-art developments. *Environ Technol* 2013;34(13–16):1653–70. <https://doi.org/10.1080/09593330.2013.822022>.
- [2] Elsharnouby O, Hafez H, Nakhla G, El Naggar MH. A critical literature review on biohydrogen production by pure cultures. *Int J Hydrogen Energy* 2013;38(12):4945–66. <https://doi.org/10.1016/j.ijhydene.2013.02.032>.
- [3] Yasin NHM, Mumtaz T, Hassan MA, Abd Rahman N. Food waste and food processing waste for biohydrogen production: a review. *J Environ Manag* 2013;130:375–85. <https://doi.org/10.1016/j.jenvman.2013.09.009>.
- [4] Balachandar G, Khanna N, Das D. Biohydrogen production from organic wastes by dark fermentation. In: *Biohydrogen*. Elsevier; 2013. p. 103–44. <https://doi.org/10.1016/B978-0-444-59555-3.00006-4>.
- [5] Lee D-J, Show K-Y, Su A. Dark fermentation on biohydrogen production: pure culture. *Bioresour Technol* 2011;102(18):8393–402. <https://doi.org/10.1016/j.biortech.2011.03.041>.
- [6] Show KY, Lee DJ, Tay JH, Lin CY, Chang JS. Biohydrogen production: current perspectives and the way forward. *Int J Hydrogen Energy* 2012;37(20):15616–31. <https://doi.org/10.1016/j.ijhydene.2012.04.109>.
- [7] O-Thong S, Prasertsan P, Karakashev D, Angelidaki I. High-rate continuous hydrogen production by *Thermoanaerobacterium thermosaccharolyticum* PSU-2 immobilized on heat-pretreated methanogenic granules. *Int J Hydrogen Energy* 2008;33(22):6498–508. <https://doi.org/10.1016/j.ijhydene.2008.07.060>.
- [8] Argun H, Kargi F, Kapdan IK. Effects of the substrate and cell concentration on bio-hydrogen production from ground wheat by combined dark and photo-fermentation. *Int J Hydrogen Energy* 2009;34(15):6181–8. <https://doi.org/10.1016/j.ijhydene.2009.05.130>.
- [9] Davila-Vazquez G, Cota-Navarro CB, Rosales-Colunga LM, de León-Rodríguez A, Razo-Flores E. Continuous biohydrogen production using cheese whey: improving the hydrogen production rate. *Int J Hydrogen Energy* 2009;34(10):4296–304. <https://doi.org/10.1016/j.ijhydene.2009.02.063>.
- [10] Pawar SS, van Niel EWJ. Thermophilic biohydrogen production: how far are we? *Appl Microbiol Biotechnol* 2013;97(18):7999–8009. <https://doi.org/10.1007/s00253-013-5141-1>.
- [11] de Vrije T, Budde MA, Lips SJ, Bakker RR, Mars AE, Claassen PA. Hydrogen production from carrot pulp by the extreme thermophiles *Caldicellulosiruptor saccharolyticus* and *Thermotoga neapolitana*. *Int J Hydrogen Energy* 2010;35(24):13206–13. <https://doi.org/10.1016/j.ijhydene.2010.09.014>.
- [12] Cappelletti M, Bucchi G, de Sousa Mendes J, Alberini A, Fedi S, Bertin L, et al. Biohydrogen production from glucose, molasses and cheese whey by suspended and attached cells of four hyperthermophilic *Thermotoga* strains. *J Chem Technol Biotechnol* 2012;87(9):1291–301. <https://doi.org/10.1002/jctb.3782>.
- [13] Dipasquale L, d'Ippolito G, Gallo C, Vella FM, Gambacorta A, Picariello G, et al. Hydrogen production by the thermophilic

- eubacterium *Thermotoga neapolitana* from storage polysaccharides of the CO₂-fixing diatom *Thalassiosira weissflogii*. *Int J Hydrogen Energy* 2012;37(17):12250–7. <https://doi.org/10.1016/j.ijhydene.2012.05.160>.
- [14] Pradhan N, Dipasquale L, d'Ippolito G, Panico A, Lens PNL, Esposito G, et al. Hydrogen production by the thermophilic bacterium *Thermotoga neapolitana*. *Int J Mol Sci* 2015;16(6):12578–600. <https://doi.org/10.3390/ijms160612578>.
 - [15] Huber R, Hannig M. Thermotogales. In: Dworkin M, Falkow S, Rosenberg E, Schleifer K-H, Stackebrandt E, editors. *The prokaryotes*. New York, NY: Springer New York; 2006. p. 899–922. https://doi.org/10.1007/0-387-30747-8_38.
 - [16] Pradhan N, Dipasquale L, d'Ippolito G, Fontana A, Panico A, Lens PN, et al. Kinetic modeling of fermentative hydrogen production by *Thermotoga neapolitana*. *Int J Hydrogen Energy* 2016;41(9):4931–40. <https://doi.org/10.1016/j.ijhydene.2016.01.107>.
 - [17] Nguyen T-AD, Han SJ, Kim JP, Kim MS, Sim SJ. Hydrogen production of the hyperthermophilic eubacterium, *Thermotoga neapolitana* under N₂ sparging condition. *Bioresour Technol* 2010;101(Suppl. 1):41. <https://doi.org/10.1016/j.biortech.2009.03.041>.
 - [18] Munro SA, Zinder SH, Walker LP. The fermentation stoichiometry of *Thermotoga neapolitana* and influence of temperature, oxygen, and pH on hydrogen production. *Biotechnol Prog* 2009;25(4):1035–42. <https://doi.org/10.1002/btpr.201>.
 - [19] d'Ippolito G, Dipasquale L, Vella FM, Romano I, Gambacorta A, Cutignano A, et al. Hydrogen metabolism in the extreme thermophile *Thermotoga neapolitana*. *Int J Hydrogen Energy* 2010;35(6):2290–5. <https://doi.org/10.1016/j.ijhydene.2009.12.044>.
 - [20] Nguyen T-AD, Kim JP, Kim MS, Oh YK, Sim SJ. Optimization of hydrogen production by hyperthermophilic eubacteria, *Thermotoga maritima* and *Thermotoga neapolitana* in batch fermentation. *Int J Hydrogen Energy* 2008;33(5):1483–8. <https://doi.org/10.1016/j.ijhydene.2007.09.033>.
 - [21] Thauer RK, Jungermann K, Decker K. Energy conservation in chemotrophic anaerobic bacteria. *Bacteriol Rev* 1977;41(1):100–80.
 - [22] Basile MA, Carfagna C, Cerruti P, Gomez d'Ayala G, Fontana A, Gambacorta A, et al. Continuous hydrogen production by immobilized cultures of *Thermotoga neapolitana* on an acrylic hydrogel with pH-buffering properties. *RSC Adv* 2012;2(9):3611. <https://doi.org/10.1039/c2ra01025a>.
 - [23] Ngo TA, Bui HTV. Biohydrogen production using immobilized cells of hyperthermophilic eubacterium *Thermotoga neapolitana* on porous glass beads. *J Technol Innovat Renew Energy* 2013;231–8.
 - [24] Frascari D, Cappelletti M, Mendes JDS, Alberini A, Scimonelli F, Manfreda C, et al. A kinetic study of biohydrogen production from glucose, molasses and cheese whey by suspended and attached cells of *Thermotoga neapolitana*. *Bioresour Technol* 2013;147:553–61. <https://doi.org/10.1016/j.biortech.2013.08.047>.
 - [25] Gupta N, Pal M, Sachdeva M, Yadav M, Tiwari A. Thermophilic biohydrogen production for commercial application: the whole picture. *Int J Energy Res* 2016;40(2):127–45. <https://doi.org/10.1002/er.3438>.
 - [26] Chou C-J, Jenney FEJR, Adams MWW, Kelly RM. Hydrogenesis in hyperthermophilic microorganisms: implications for biofuels. *Metab Eng* 2008;10(6):394–404. <https://doi.org/10.1016/j.ymben.2008.06.007>.
 - [27] Westman JO, Franzen CJ. Current progress in high cell density yeast bioprocesses for bioethanol production. *Biotechnol J* 2015;10(8):1185–95. <https://doi.org/10.1002/biot.201400581>.
 - [28] Basso CL, Basso OT, Rocha NS. Ethanol production in Brazil: the industrial process and its impact on yeast fermentation. In: Dos Santos Bernardes MA, editor. *Biofuel production-recent developments and prospects*. InTech; 2011. p. 85–100. <https://doi.org/10.5772/17047>.
 - [29] Pradhan N, Dipasquale L, d'Ippolito G, Panico A, Lens PN, Esposito G, et al. Hydrogen and lactic acid synthesis by the wild-type and a laboratory strain of the hyperthermophilic bacterium *Thermotoga neapolitana* DSMZ 4359 T under capnophilic lactic fermentation conditions. *Int J Hydrogen Energy* 2017;42(25):16023–30. <https://doi.org/10.1016/j.ijhydene.2017.05.052>.
 - [30] Dipasquale L, d'Ippolito G, Fontana A. Capnophilic lactic fermentation and hydrogen synthesis by *Thermotoga neapolitana*: an unexpected deviation from the dark fermentation model. *Int J Hydrogen Energy* 2014;39(10):4857–62. <https://doi.org/10.1016/j.ijhydene.2013.12.183>.
 - [31] Mars AE, Veuskens T, Budde MA, van Doeveren PF, Lips SJ, Bakker RR, et al. Biohydrogen production from untreated and hydrolyzed potato steam peels by the extreme thermophiles *Caldicellulosiruptor saccharolyticus* and *Thermotoga neapolitana*. *Int J Hydrogen Energy* 2010;35(15):7730–7. <https://doi.org/10.1016/j.ijhydene.2010.05.063>.
 - [32] Ngo TA, Kim M-S, Sim SJ. Thermophilic hydrogen fermentation using *Thermotoga neapolitana* DSM 4359 by fed-batch culture. *Int J Hydrogen Energy* 2011;36(21):14014–23. <https://doi.org/10.1016/j.ijhydene.2011.04.058>.
 - [33] Bernfeld P. Amylases, α and β . In: Chance B, editor. *Preparation and assay of enzymes*. San Diego, Calif: Acad. Press; 1955. p. 149–58.
 - [34] d'Ippolito G, Dipasquale L, Fontana A. Recycling of carbon dioxide and acetate as lactic acid by the hydrogen-producing bacterium *Thermotoga neapolitana*. *ChemSusChem* 2014;7(9):2678–83. <https://doi.org/10.1002/cssc.201402155>.
 - [35] Lay J-J, Li Y-Y, Noike T. Influences of pH and moisture content on the methane production in high-solids sludge digestion. *Water Res* 1997;31(6):1518–24. [https://doi.org/10.1016/S0043-1354\(96\)00413-7](https://doi.org/10.1016/S0043-1354(96)00413-7).
 - [36] Argun H, Kargi F, Kapdan I, Oztekin R. Batch dark fermentation of powdered wheat starch to hydrogen gas: effects of the initial substrate and biomass concentrations. *Int J Hydrogen Energy* 2008;33(21):6109–15. <https://doi.org/10.1016/j.ijhydene.2008.08.004>.
 - [37] Kargi F, Eren NS, Ozmihci S. Effect of initial bacteria concentration on hydrogen gas production from cheese whey powder solution by thermophilic dark fermentation. *Biotechnol Prog* 2012;28(4):931–6. <https://doi.org/10.1002/btpr.1558>.
 - [38] Kádár Z, de Vrije T, van Noorden GE, Budde MAW, Szengyel Z, Réczey K, et al. Yields from glucose, xylose, and paper sludge hydrolysate during hydrogen production by the extreme thermophile *Caldicellulosiruptor saccharolyticus*. *ABAB* 2004;114(1–3):497–508. <https://doi.org/10.1385/ABAB:114:1-3:497>.
 - [39] van Niel EWJ, Budde MAW, de Haas GG, van der Wal FJ, Claassen PAM, Stams AJM. Distinctive properties of high hydrogen producing extreme thermophiles, *Caldicellulosiruptor saccharolyticus* and *Thermotoga elfii*. *Int J Hydrogen Energy* 2002;27:1391–8.
 - [40] Schröder C, Selig M, Schönheit P. Glucose fermentation to acetate, CO₂ and H₂ in the anaerobic hyperthermophilic eubacterium *Thermotoga maritima*: involvement of the Embden-Meyerhof pathway. *Arch Microbiol* 1994;161(6):460–70. <https://doi.org/10.1007/BF00307766>.
 - [41] Jayasinghearachchi HS, Sarma PM, Lal B. Biological hydrogen production by extremely thermophilic novel bacterium *Thermoanaerobacter mathranii* A3N isolated from oil producing

- well. *Int J Hydrogen Energy* 2012;37(7):5569–78. <https://doi.org/10.1016/j.ijhydene.2011.12.145>.
- [42] O-Thong S, Prasertsan P, Karakashev D, Angelidaki I. Thermophilic fermentative hydrogen production by the newly isolated *Thermoanaerobacterium thermosaccharolyticum* PSU-2. *Int J Hydrogen Energy* 2008;33(4):1204–14. <https://doi.org/10.1016/j.ijhydene.2007.12.015>.
- [43] Ren N, Cao G, Wang A, Lee D, Guo W, Zhu Y. Dark fermentation of xylose and glucose mix using isolated *Thermoanaerobacterium thermosaccharolyticum* W16. *Int J Hydrogen Energy* 2008;33(21):6124–32. <https://doi.org/10.1016/j.ijhydene.2008.07.107>.
- [44] Beckers L, Masset J, Hamilton C, Delvigne F, Töye D, Crine M, et al. Investigation of the links between mass transfer conditions, dissolved hydrogen concentration and biohydrogen production by the pure strain *Clostridium butyricum* CWBI1009. *Biochem Eng J* 2015;98:18–28. <https://doi.org/10.1016/j.bej.2015.01.008>.
- [45] Sonnleitner A, Peintner C, Wukovits W, Friedl A, Schnitzhofer W. Process investigations of extreme thermophilic fermentations for hydrogen production: effect of bubble induction and reduced pressure. *Bioresour Technol* 2012;118:170–6. <https://doi.org/10.1016/j.biortech.2012.05.046>.
- [46] Ljunggren M, Willquist K, Zacchi G, Van Niel EWJ. A kinetic model for quantitative evaluation of the effect of hydrogen and osmolarity on hydrogen production by *Caldicellulosiruptor saccharolyticus*. *Biotechnol Biofuels* 2011;4(1):31. <https://doi.org/10.1186/1754-6834-4-31>.
- [47] Zhang Y, Zhang F, Chen M, Chu P-N, Ding J, Zeng RJ. Hydrogen supersaturation in extreme-thermophilic (70°C) mixed culture fermentation. *Appl Energy* 2013;109:213–9. <https://doi.org/10.1016/j.apenergy.2013.04.019>.
- [48] Verhaart MRA, Bielen AAM, van der Oost J, Stams AJM, Kengen SWM. Hydrogen production by hyperthermophilic and extremely thermophilic bacteria and archaea: mechanisms for reductant disposal. *Environ Technol* 2010;31(8–9):993–1003. <https://doi.org/10.1080/09593331003710244>.
- [49] Belkin S, Wirsén CO, Jannasch HW. A new sulfur-reducing, extremely thermophilic eubacterium from a submarine thermal vent. *Appl Environ Microbiol* 1986;1180–5.