

TALLINN 13/06/2024



full CCUS chain demonstration

Introduction to Horizon Europe HERCCULES project

DISSEMINATION EVENT ON CO₂ CAPTURE, TRANSPORT, USE AND STORAGE TECHNOLOGY (CCUS)

HORIZON EUROPE PROJECTS HERCCULES & CCUS ZEN

Speaker: Dr. Maurizio Spinelli LEAP – Project Coordinator



HERCCULES project





HEROES IN SOUTHERN EUROPE TO DECARBONIZE INDUSTRY WITH CCUS

Demonstration of the full CCUS chain for the decarbonization of hard-toabate industries in southern Europe, focusing on cement and energy from waste sectors in Northern Italy and Greek clusters



9 Research Organizations

14 Industrial Partners









> HERCCULES: HEROES IN SOUTHERN EUROPE TO DECARBONIZE

> Demonstration of the full CCUS chain for the decarbonization of hard-to-abate industries in Southern Europe, focusing on cement and energy from waste sectors in Northern Italy and Greek clusters

- Coordinator: LEAP
- Parternship:
- 23 partners + 4 affiliated
- **Topic:** HORIZON-CL5-2022-D3-01
- Start date: 1 January, 2023
- Duration: 60 months
- **Budget total:** € 39.627.208,00
- **UE Contribution:** € 29.632.076,48

HERCCULES NUMBERS

- 3 CO₂ capture pilot plants
- 3 CO₂ use pilot plants
- 2 Storage sites
- >10.000 test hours
- >3500 ton CO₂ captured
- >1000 ton CO_2 stored
- >8000 ton of low-carbon concrete
- 7 Pre-feed and Hazop studies









2. Structure & Work Packages





- Innovation Action Budget ≈ 40 M€
- 10 Work Packages
- 56 Deliverables,

•

- 18 Milestones
- Duration : 5 years









3. Timeline (I)











3. Timeline (II)



3. Timeline (III)

Testing and demonstration of **demolished-concrete CO₂ mineralization** and production of **low carbon concrete**

	A	1)	2)	3)	4)
	Reference concrete	TTTAN and BUZZI - HERCCULES concrete with CCUS (5.000 m ³)	CELITEMENT - HERCCULES Concrete (5-10 m ³)	TITAN - HERCCULES Concrete (4000 m ³)	BUZZI - Zeolite HERCCULES Concrete (50 m ³)
Cement type	CEM II A- LL 42.5 R	CEM II A LL 42.5 CO ₂ capture and geological storage (****)	HERCCULES CELITEMENT	CEMIIALL 42.5 CO2 capture and geological storage (****)	
Cement content:	$320 kg/m^3$	320 kg/m ³	$340 \text{kg/m}^{3} ^{*}$	280 kg/m ³	280 kg/m ³
Technology		CO ₂ capture technology in cement making (WP2)	CELITEMENT production from carbon neutral CaO nch CaL purge (WP4)	CO ₂ use by demolished concrete mineral carbonation (WP4)	CO2 use by Natural zeolite (clinoptilolite) CO2 uptake (WP4)
Additions				40 kg/m ³ CO ₂ treated C&D waste	40 kg/m ³ CO ₂ treated Zeolite
CO ₂ emission	$240 kg/m^3$	50 kg/m ³ (negative with biomass firing)	100 kg/m ³	negative emission	negative CO ₂ emission
OPEX	80€/m ³ ***	125€/m ³	70€/m ³ (**)	110€/m ³	110€/m ³
Approach	ETS	CO ₂ storage	Innovation cement relat	CO ₂ storage and SCMs	CO ₂ storage and SCMs
Scale factor:	Mass production	Mass Production		Mass production	Mass production

2023 2024 2025 2026 2027



Design and optimization study of **CO₂ transportation** in Northern Italy Demonstration of **captured CO₂ transport, injection and permanent storage** in Ravenna and Prinos sites

107 - WO

NP3 - WD







Funded by the European Union



3. Timeline (IV)



2023

WP10: Communication, dissemination and knowledge sharing WP8: Social perception and community engagement

HERCCULES CCUS chain demonstration







4. CCUS: Application in Cement sector (WP2-WP7)



CO2 to storage (from PCC): 38.0 Nm3

Other gas to storage: 0.1 Nm3 (0.1 %)

Other gas to atmosphere: 119.9 Nm3

CO2 produced 100 Nm3

CO2 captured: 98 Nm3

CO2 purity: 99.9 %

Sankey Diagram , Hybrid

CO2 (100Nm3)

Other gas

CO2 to atmosphere: 2.0 Nm3

CO2 to storage (from CPU): 60.0 Nm3 (99.9 %



HERCCULES Hybrid CO₂









1- Oxyfuel calcination with CPU

\geq **Oxyfuel pilot plant characteristics**

- Goal of this demonstration: partial oxyfuel technology benchmarking with conventional and alternative fuels. including biomass and waste
- **1.5** MW_{th} oxyfuel demo plant + CO_2 Purification and liquefaction Unit (CPU)
- **Capture rate oxyfuel + CPU 80%**
- 4.5-5 ton_{co2}/day of high-purity (>99.9%vol) liquid CO₂ produced













4. CCUS: Application in Cement sector (WP2-WP7)



2- Novel solvent-based post-combustion capture (PCC)

- > PCC pilot plant characteristics
 - Design to treat at least <u>250-300 Nm³/h</u> of cement flue gases
 - Capture rate >95%
 - <u>2.5-3 ton_{CO2}/day of Liquid CO₂ produced</u>
 - Solvents targeted: <u>MEA (validation),</u> <u>improved solvent</u>
 - Innovative design, considering:
 - Lean-vapor compression
 - Membrane contactor

> PCC pilot plant testing

 The unit will be design as a movable skid-mounted system, to be tested in Vernasca in the standalone PCC mode (flue gas at the stack), or flue gas from rotary kiln mixed with CPU off-gas in the hybrid mode (Greece)











4. CCUS: Application in Energy from Waste sector (WP3-WP7)

- **HERCCULES** will demonstrate at **TRL 7-8** for the first time the **CFB CaL process coupled with CPU**
- Preliminary lab experiments will characterize the Ca-based sorbent exposed to EfW flue gases
- The demo plant will be installed and operated at the EfW Silla 2 plant owned by A2A Ambiente (A2AAMB)
- The CFB CaL pilot will be operated with SRF and sewage sludge, targeting the following KPIs:
 - i. <u>CO₂ Capture efficiency</u> **95%**
 - ii. <u>Ultra-high CO₂ purity</u> (>99.9%)
- Scale-up studies and techno-economic analyses:
- i. <u>Negative CO₂ emissions</u> (<-400 kg_{CO2}/t_{waste})
- ii. <u>Net electric efficiency improvement of 3%</u> <u>compared to MEA</u>











4. CCUS: Application in Energy from Waste sector (WP3-WP7)

HERCCULES

Calcium Looping + CPU configuration

The design of the CaL and CPU units are underway, based on:

- Characteristics of WtE host plant (Silla2 in <u>Milan, Italy</u>)
- Chemical-physical characteristics of the flow gas entering the Carbonator (~1500 Nm³/h)
- Properties of the fuel derived from waste (1 MW_{th}), as input to Calciner

Area selected for the installation of the systems











Funded by the European Union. This project has received funding from the European Union's Horizon Europe research and innovation programme under grant agreement No. 101096691. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or European Climate, Infrastructure and Environment Executive Agency (CINEA). Neither the European Union nor the granting authority can be held responsible for them.

storage sections



5. CCUS: CO₂ utilization and resource circularity (WP4-WP7)

Cement and concrete carbon footprint reduction:

- HERCCULES Sources
- **by-product materials recycle processes** exploiting the **CaO sorbent** (purged from the **CaL pilot plant**)





The carbon-sink materials produced via by-products circularity include the **low carbon CELITEMENT® hydraulic binder,** and the **low carbon sulfo-alluminate clinker**









5. CCUS: CO₂ utilization and resource circularity (WP4-WP7)

Cement and concrete carbon footprint reduction:

- by-product materials recycle processes exploiting the CaO sorbent (purged from the CaL pilot plant)
- ii. two CO₂ mineralization skid integrated to CC demo plants (waste demolition & zeolite-based materials)



Funded by

the European Union





5. CCUS: CO₂ utilization and resource circularity (WP4-WP7)

Cement and concrete carbon footprint reduction:



- two CO₂ mineralization skid integrated to CC demo plants (waste demolition & zeolite-based materials)
- → Four novel, low carbon concrete formulation will be produced (>8000 t) and compared with standard concrete

	Α	1)	2)	3)	4)
	Reference concrete	TITAN and BUZZI - HERCCULES concrete with CCUS (5.000 m ³)	CELITEMENT - HERCCULES Concrete (5-10 m ³)	TTTAN - HERCCULES Concrete (4000 m ³)	BUZZI - Zeolite HERCCULES Concrete (50 m ³)
Cement type	CEM II A- LL 42.5 R	CEM II A LL 42.5 CO ₂ capture and geological storage (****)	HERCCULES CELITEMENT	CEM II A LL 42.5 CO ₂ capture and geological storage (****)	
Cement content:	320 kg/m ³	320 kg/m ³	340 kg/m ³ *	$280\mathrm{kg/m^3}$	280 kg/m ³
CO ₂ emission	240 kg/m ³	50 kg/m ³ (negative with biomass firing)	100 kg/m³	negative emission	negative CO ₂ emission
OPEX	80€/m³***	125 €/m³	70€/m³ (**)	110€/m³	110€/m³



Other circularities and synergies between cement and EfW sectors

- **SRF valorization** as fuel for both the cement and EfW capture technologies
- Sharing and optimizing the infrastructure for CO₂ transportation



Ĭ.









- HERCCULES will safe and effective permanent CO₂ storage of more than 1000 ton of captured CO₂ in the most advanced CO₂ storage sites in Southern Europe: <u>Ravenna (ENI) and</u> <u>Prinos (ENERGEAN)</u>
 - High storage capacity and costeffective potential, good connection with clusters of emitters and possibility to repurpose existing infrastructures





- Important CCS Hub in Southern Europe and Mediterranean
- Supports decarbonization of industrial clusters in Italy & Mediterranean – storage site for the PCI Callisto
- Transportation network being developed to receive CO₂ both via pipeline and shipping
- Strong interest from nearby and international emitters, including beneficiaries from Innovation Fund
- Over 20 feasibility studies in collaboration with national and international industrial emitters
- Over 500 MTON of CO₂ total capacity
- Phased expansion of injection up to 16Mtpa after 2030





Funded by the European Union





- HERCCULES will safe and effective permanent CO₂ storage of more than 1000 ton of captured CO₂ in the most advanced CO₂ storage sites in Southern Europe: <u>Ravenna (ENI) and</u> <u>Prinos (ENERGEAN)</u>
 - High storage capacity and costeffective potential, good connection with clusters of emitters and possibility to repurpose existing infrastructures













- HERCCULES will safe and effective permanent CO₂ storage of more than 1000 ton of captured CO₂ in the most advanced CO₂ storage sites in Southern Europe: <u>Ravenna (ENI) and</u> <u>Prinos (ENERGEAN)</u>
 - High storage capacity and costeffective potential, good connection with clusters of emitters and possibility to repurpose existing infrastructures
 - Monitoring strategies, modelling of the storage reservoirs, development of guidelines for future storage site permitting and authorization procedures.













- HERCCULES will safe and effective permanent CO₂ storage of more than 1000 ton of captured CO₂ in the most advanced CO₂ storage sites in Southern Europe: <u>Ravenna (ENI) and</u> <u>Prinos (ENERGEAN)</u>
 - High storage capacity and costeffective potential, good connection with clusters of emitters and possibility to repurpose existing infrastructures
 - Monitoring strategies, modelling of the storage reservoirs, development of guidelines for future storage site permitting and authorization procedures.
- Multi-criteria optimization methods for the design of the optimal CO₂ transport network for utilization and storage under different infrastructural evolution scenarios

Optimization framework: Mixed Integer Linear Programming











- In the short term, pre-commercial demonstration at TRL 8-9 of a complete CCUS value chain (scale-up HERCCULES demo plants, WP7 scale-up studies)
- In the medium term, the results in HERCCULES can facilitate large-scale CCS implementation in cement (need of modernization) and EfW (increase of non-recyclable waste)



- Identification of **business models** and financial mechanisms tailored to CCUS, **LCA** and **CBA** in **WP9**
- Assessment of the societal readiness of the integrated CCUS chain; analysis of socio-economic and political barriers, policies and regulations to facilitate the development of regulatory framework (WP8)









Kick-off meeting – Piacenza, Italy 15-16th February 2023

























First Regional stakeholder committee – Bologna, Italy 16th January 2024













Disseminations on social medias









Funded by

the European Union





> THANKS FOR YOUR ATTENTION

> CONTACTS

maurizio.spinelli@polimi.it herccules-leap@polimi.it

www.herccules.eu