

Kongsfjorden 2010-2011

LAT: 78° 57.754'N
 LON: 011° 45.556'E
 DEPTH: 221m
 DEPLOYED: 1300Z 26/09/2010
 RECOVERED: 2100Z 02/09/2011

Argos s/n 098 id24333 & light

1591 T (4 m) Pellets on surface, line cut! **FAULTY**

10m 14mm seasteel

40" S/S buoy

'3 chain links' used for stopping off throughout the mooring. These pass through block and winch without problems on the Jan Mayen. Mooring deployed anchor first from the starboard rail.

The top microcat & SBE16+ are not inline, they are shackled onto the mooring line.

1m x 1/2" L/L chain

Swivel

SBE 37 s/n 5509 (16 m)

1 x 10m 10mm 6x19FC wire

Vemco miniloggers

1592 T (27 m)

SBE16+ s/n 6067 & Fluo s/n 2354 & PAR s/n 70190 (27 m)

1593 T (37 m)

1 x 20m 10mm 6x19FC wire

1598 T (47 m)

1602 T (57 m)

1 x 50m 10mm 6x19FC wire

1620 T (67 m)

1622 T (98 m)

RDI 300KHz ADCP s/n 9579 (98 m)
SBE16+ s/n 5182

1 x 5m 10mm 6x19FC wire

4 x 17" glass spheres

1623 T (133 m)

1 x 50m 10mm 6x19FC wire

1624T (168 m)

1 x 50m 10mm 6x19FC wire

SBE 37SMP s/n 5510 (208 m)

Swivel

A/R S/N 529
15C0 (W)
1549 (D) 22.1V Lithium Batteries
1555 (R)

1 x 10m 13mm 6x19FC wire

600Kgs Chain Anchor

221m