



3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



Modeling of lateral sleeper-ballast interaction on rail track

Jeniffer Barreto, José Varandas

Universidade Nova de Lisboa-Faculdade de Ciências e Tecnologias,
Lisboa, Portugal



FACULDADE DE
CIÊNCIAS E TECNOLOGIA
UNIVERSIDADE NOVA DE LISBOA



3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



GEO-INSTITUTE

TRB

TRANSPORTATION CENTER FOR RESEARCH AND PRACTICE

RUTGERS

Center for Advanced Infrastructure and Transportation




1. Introduction
2. Methods
3. Results
4. Conclusions
5. Further developments



1. Introduction

Stiffness and lateral resistance of the track

Fig. 1- Lateral behaviour of the track. Kish (2011)



area under study



3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



2. Methods

Pegasus

Developed by Varandas (2013)

- Matlab program
- Linear (Hook's Law) and non-linear (K- θ) ballast behaviour
- Non-linear contact between the sleepers and the ballast (Penalty formulation)




Fig.2 - The E_r - θ relationship . From Varandas (2013)



3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



GEO-INSTITUTE



Center for Advanced Infrastructure and Transportation

2. Methods

Model




Fig.3 - Elements in study




Fig.4- Geometry



Vertical Load influence


Test	Soil layer 1 :	Soil foundation :	F_z [kN]	F_y [kN]	F_y/F_z	K_y [kN/mm]		K_z [kN/mm]	
	E[mPa] -v- ρ [t/m ³]	E[mPa] - v - ρ [t/m ³]				Non Linear	Linear	Non Linear	Linear
	D1	200 - 0,35 - 1,8				150 - 0,35 - 1,8	1	8	8,00
D2	200 - 0,35 - 1,8	150 - 0,35 - 1,8	0	8	inf	71,4	178,1	0,0	0,0
D3	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-1	8	8,00	74,0	177,6	144,7	222,6
D4	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-8	8	1,00	89,8	177,8	110,3	264,0
D5	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-10	8	0,80	93,5	177,9	111,4	265,4
D6	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-16	8	0,50	103,1	178,1	114,8	267,5
D7	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-24	8	0,33	103,1	178,3	119,1	268,7
D8	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-40	8	0,20	129,1	-	125,7	-
D10	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-60	8	0,13	143,8	-	131,7	-
D11	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-75	8	0,11	152,8	-	135,2	-
D12	200 - 0,35 - 1,8	150 - 0,35 - 1,8	-100	8	0,08	165,5	-	140,0	-




3. Results

Vertical Load influence – Stifiness : $K_i = 2F_i / (u_{i,end} - u_{i,initial})$

Linear



Nonlinear







3. Results

Vertical Load influence : p-q

Linear



Nonlinear





3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



3. Results

Soil Foudation influence


Test	Soil layer 1: E[mPa] - v - ρ [t/m ³]	Soil foundation : E[mPa] - v - ρ [t/m ³]	F _z [kN]	F _y [kN]	K _y [kN/mm]		K _z [kN/mm]	
					Non	Linear	Non	Linear
					Linear	Linear	Linear	Linear
A9	200 - 0,35 - 1,8	20 - 0,45- 2	-75	25	83,6	161,7	110,2	227,2
B9	200 - 0,35 - 1,8	60 - 0,3 - 2	-75	25	121,9	91,8	169,0	105,4
C9	200 - 0,35 - 1,8	100 - 0,3 - 1,68	-75	25	140,1	189,7	232,8	292,8
D9	200 - 0,35 - 1,8	150-0,35-1,8	-75	25	152,0	208,2	269,5	341,9
E9	200 - 0,35 - 1,8	200 - 0,35 - 2	-75	25	159,6	138,5	301,4	164,7
F9	200 - 0,35 - 1,8	300-0,3-2,04	-75	25	169,7	178,9	338,2	265,9




3. Results

Soil Foudation influence : u_y

Linear



Nonlinear







3. Results

Soil Foundation influence : u_z

Linear



Nonlinear






3. Results

Test D9 – comparison between the linear model and the nonlinear

Displacements







Test D9 – comparison between the linear model and the nonlinear

Stress

σ_z Linear



σ_z Nonlinear





3. Results



Influence of the lateral sleeper-ballast interaction , $K_{c,h}$ on the stress distribution in the ballast

	Test 1	Test 2	Test 3	Test 4	Test 5	Test 6	Test 7
$K_{c,h}[\text{kN/m}^2]$	0	1×10^2	1×10^4	1×10^5	1×10^6	5×10^6	1×10^7
$F_z[\text{kN}]$	-75	-75	-75	-75	-75	-75	-75
$F_y[\text{kN}]$	0	0	0	0	0	0	0
Foudation soil	D	D	D	D	D	D	D



3. Results

Influence of the lateral sleeper-ballast interaction on the stress distribution in the ballast $-\sigma_z$







3. Results

Influence of the lateral sleeper-ballast interaction on the stress distribution in the ballast - σ_y


Elem 1




Elem 3



Elem 2



Elem 6





Conclusions

- Load study – It was possible to obtain vertical load (F_z) - lateral stiffness (K_y) relation. For higher F_y/F_z relation, the graph p-q lies above the failure line .
- Soil foundation study – As expected, it was observed that the higher the Young modulus of the soil the higher the lateral stiffness .
- Influence of the lateral sleeper-ballast interaction on the stress distribution in the ballast – It is noted that the parameter $K_{c,h}$ has a non negligible influence on the stress distribution inside the ballast layer, therefore denoting the importance of a care representation of this friction interface in studies focused on the granular layers of the track .



3rd ICTG 2016

04-07 September 2016, Guimarães, Portugal



University of Minho
School of Engineering



GEO-INSTITUTE

TRB

TRANSPORTATION CENTER FOR RESEARCH AND PRACTICE

RUTGERS

Center for Advanced Infrastructure and Transportation



ORDEM DOS ENGENHEIROS



ORDEM DOS ENGENHEIROS REGIONAL NORTE

Thank you for your attention

Universidade Nova de Lisboa-Faculdade de Ciências e Tecnologias, Lisboa, Portugal

Jeniffer costa Barreto - jc.barreto@campus.fct.unl.pt

José Varandas - jnsf@fct.unl.pt