

Quantile Regression Averaging

Evan L. Ray

20 May, 2020

```
knitr:::opts_chunk$set(message=FALSE, warning=FALSE)
```

Introduction

The purpose of this document is to demonstrate and verify the functionality of the package with a few simple simulated examples.

We will use the following packages:

```
library(covidEnsembles)
library(zeallot)
library(tidyverse)
library(gridExtra)
```

Simple QRA Example

We consider QRA for the following scenario:

- The observed training data are $X_1, \dots, X_{100} \stackrel{\text{i.i.d.}}{\sim} \text{Normal}(0, 1)$
- We have three misspecified predictive models:
 - **wide**: $P_1 = \text{Normal}(0.0, \sqrt{2})$
 - **narrow**: $P_2 = \text{Normal}(0.0, \sqrt{0.5})$
 - **bias_wide**: $P_3 = \text{Normal}(0.2, \sqrt{2})$

The pdfs for these distributions are illustrated below:

```
model_params <- data.frame(
  model = c('DGP', 'Wide', 'Narrow', 'Bias_Wide'),
  mean = c(0.0, 0.0, 0.0, 0.5),
  sd = c(1.0, sqrt(2), sqrt(0.5), sqrt(2)),
  stringsAsFactors = FALSE
)

x_grid <- seq(from=-3, to=3, length=201)
curves <- purrr::pmap_dfr(
  model_params,
```

```

function(model, mean, sd) {
  data.frame(
    model = model,
    x = x_grid,
    pdf = dnorm(x_grid, mean=mean, sd=sd),
    cdf = pnorm(x_grid, mean=mean, sd=sd)
  )
}


p1 <- ggplot(data = curves,
  mapping = aes(x = x, y = pdf, color=model, linetype=model)) +
  geom_line() +
  theme_bw() +
  ggtitle('Probability Density Functions')

p2 <- ggplot(data = curves,
  mapping = aes(x = x, y = cdf, color=model, linetype=model)) +
  geom_line() +
  theme_bw() +
  ggtitle('Cumulative Distribution Functions')


grid.arrange(p1, p2)

```

Probability Density Functions



Cumulative Distribution Functions



Throughout, we evaluate forecast skill with the weighted interval score (WIS) based on the following

quantile levels:

```
c(0.01, 0.025, seq(0.05, 0.95, by = 0.05), 0.975, 0.99)  
## [1] 0.010 0.025 0.050 0.100 0.150 0.200 0.250 0.300 0.350 0.400 0.450 0.500  
## [13] 0.550 0.600 0.650 0.700 0.750 0.800 0.850 0.900 0.950 0.975 0.990
```

Train and test set set up, component model predictions

We simulate $n_{train} = 10^2$ observations for the training set used to estimate quantile regression averaging parameters, and $n_{test} = 10^4$ observations for the purpose of evaluating performance.

```
set.seed(7462934) # mashed keyboard for science  
n_train <- 10^2  
y_train <- rnorm(n_train)  
  
n_test <- 10^4  
y_test <- rnorm(n_test)
```

For all observations, the predictive quantiles from the three component models are the same. We assemble training and test set QuantileForecastMatrix objects representing these predictions.

```
make_predictive_quantile_objects <- function(n) {  
  predictive_quantiles_df <- expand.grid(  
    obs_ind = seq_len(n),  
    model = model_params$model,  
    quantile_level = c(0.01, 0.025, seq(0.05, 0.95, by = 0.05), 0.975, 0.99),  
    stringsAsFactors = FALSE  
  ) %>%  
    left_join(model_params, by='model') %>%  
    mutate(quantile_value = qnorm(quantile_level, mean=mean, sd=sd)) %>%  
    select(-mean, -sd)  
  
  qfm <- new_QuantileForecastMatrix_from_df(  
    predictive_quantiles_df %>% filter(model != 'DGP'),  
    model_col = 'model',  
    id_cols = c('obs_ind'),  
    quantile_name_col = 'quantile_level',  
    quantile_value_col = 'quantile_value'  
  )  
  
  qfm_per_model <- purrr::map(  
    model_params$model,  
    function(model) {  
      new_QuantileForecastMatrix_from_df(  
        predictive_quantiles_df %>% filter(model == UQ(model)),  
        model_col = 'model',  
        id_cols = c('obs_ind'),  
        quantile_name_col = 'quantile_level',  
      )  
    }  
  )  
}  
qfm_per_model
```

```

        quantile_value_col = 'quantile_value'
    )
}
) %>%
`names<-` (model_params$model)

return(c(list(predictive_quantiles_df, qfm), qfm_per_model))
}

c(train_predictive_quantiles_df,
train_qfm,
train_qfm_DGP,
train_qfm_Wide,
train_qfm_Narrow,
train_qfm_Bias_Wide) %<-% make_predictive_quantile_objects(n_train)

c(test_predictive_quantiles_df,
test_qfm,
test_qfm_DGP,
test_qfm_Wide,
test_qfm_Narrow,
test_qfm_Bias_Wide) %<-% make_predictive_quantile_objects(n_test)

```

Here are test set scores for the four models individually:

```

test_scores <- model_params['model'] %>%
  mutate(
    wis = purrr::map_dbl(
      model,
      function(model) {
        mean(wis(y_test, get(paste0('test_qfm_', model))))
      }
    )
  )
test_scores

##          model      wis
## 1        DGP 0.5103418
## 2        Wide 0.5304833
## 3     Narrow 0.5244168
## 4 Bias_Wide 0.5811568

```

QRA Method 1: Equally weighted combination of misspecified models

```

ew_qra_fit <- estimate_qra(qfm_train = train_qfm, qra_model = 'ew')
test_qfm_EW_QRA <- predict(ew_qra_fit, test_qfm)

```

```

test_scores <- data.frame(model = c('DGP', 'Wide', 'Narrow', 'Bias_Wide', 'EW_QRA')) %>%
  mutate(
    wis = purrr::map_dbl(
      model,
      function(model) {
        mean(wis(y_test, get(paste0('test_qfm_', model))))
      }
    )
  )
test_scores

##          model      wis
## 1       DGP 0.5103418
## 2       Wide 0.5304833
## 3     Narrow 0.5244168
## 4 Bias_Wide 0.5811568
## 5    EW_QRA 0.5208812

```

QRA Method 2: Convex Combination of misspecified models, one weight per model across all quantile levels

```

convex_qra_fit <- estimate_qra(qfm_train = train_qfm, y_train = y_train, qra_model = 'convex_p
test_qfm_Convex_QRA <- predict(convex_qra_fit[[2]], test_qfm)

test_scores <- data.frame(model = c('DGP', 'Wide', 'Narrow', 'Bias_Wide', 'EW_QRA', 'Convex_QR
  mutate(
    wis = purrr::map_dbl(
      model,
      function(model) {
        mean(wis(y_test, get(paste0('test_qfm_', model))))
      }
    )
  )
test_scores

##          model      wis
## 1       DGP 0.5103418
## 2       Wide 0.5304833
## 3     Narrow 0.5244168
## 4 Bias_Wide 0.5811568
## 5    EW_QRA 0.5208812
## 6 Convex_QRA 0.5104026

```

QRA Method 2: Convex Combination of misspecified models, one weight per model across all quantile levels

```
unconstrained_qra_fit <- estimate_qra(qfm_train = train_qfm, y_train = y_train, qra_model = 'unconstrained_qra')
test_qfm_Unconstrained_QRA <- predict(unconstrained_qra_fit[[2]], test_qfm)
```

All Test Set Scores

```
all_qra_approaches <- c('DGP', 'Wide', 'Narrow', 'Bias_Wide', 'EW_QRA', 'Convex_QRA', 'Unconstrained_QRA')
test_scores <- data.frame(model = all_qra_approaches) %>%
  mutate(
    wis = purrr::map_dbl(
      model,
      function(model) {
        mean(wis(y_test, get(paste0('test_qfm_', model))))
      }
    )
  )
test_scores
```

##	model	wis
## 1	DGP	0.5103418
## 2	Wide	0.5304833
## 3	Narrow	0.5244168
## 4	Bias_Wide	0.5811568
## 5	EW_QRA	0.5208812
## 6	Convex_QRA	0.5104026
## 7	Unconstrained_QRA	0.5171923