



# Salia PLC Charge Controller API Guide

eCharge Hardy Barth GmbH  
August 5, 2020

Revisions

Revision	Release Date	Changes
1.02	August 7, 2020	added some MQTT topics added use cases
1.01	August 5, 2020	added MQTT topics added screenshots
1	June 20, 2020	initial release

# Contents

1. Introduction	4
2. Configuration	4
2.1 Hardware	4
2.2 Network access	4
2.3 Web GUI	5
2.4 Firmware Update	6
3. Remote access	7
3.1 REST API	7
3.2 MQTT	8
3.3 RFID File Format	8
4. Use cases	9
4.1 Wallbox in manual mode (controlled by external controller)	9

# 1. Introduction

The Salia board is an ISO 15118 compliant charging controller for Electric Vehicle Supply Equipment (EVSE). It is equipped with an Fast Ethernet 100 MBit/s network device. The board can be accessed via webbrowser on Port 80 or MQTT on Port 1883.

## 2. Configuration

### 2.1 Hardware

By default the Moon Connect wallbox is delivered as a single socket charger with a fixed type-2 cable.




### 2.2 Network access

By default the Ethernet device is in DHCP mode.  
The default Fallback-IP is: 169.254.12.53

To configure a static IP connect a PC/Notebook via network cable and open then Web-GUI  
<http://169.254.12.53>

Under Windows OS you can detect alls reachable Salia boards in Explorer -> Network



## 2.3 Web GUI

Standard configuration can be changed via webbrowser

<http://169.254.12.53/config.php>

# Salia PLCC Slave 2310006

## salia - eCHARGE Eingang

[Home](#)[Chargelog](#)[RFID Tags](#)[Firmware](#)[Configuration](#)

### System configuration

#### Global options

Wallbox type	<input checked="" type="radio"/> Cable <input type="radio"/> Socket
Timezone	Europe/Berlin
Location/Name	eCHARGE Eingang
Auth. Mode	Free charging
Min./max. current	6 - 32 A
External control	<input type="checkbox"/> Enable Heartbeat
aWATTar	<input type="checkbox"/> Enable API

#### Mains options

Mains type	SMA Energymeter
IP address	192.168.1.58
Serial	1900200943
Mains fuse	50 A
Overcurrent	<input type="checkbox"/> Stop charging
Peak shave (optional)	0 W
ECO reference	200 W

#### OCPP options

OCPP	<input type="checkbox"/> Enable
URI/CP-Id	e.g. ws://193.186.98.138:8080/
Verify CERT	<input type="checkbox"/> Enable
APN Name	e.g. egv2.a1.net
APN User	ppp@A1plus.at
APN Pass	PPP

#### Network options

DHCP	<input type="checkbox"/> Enable
IP address	192.168.104.204
Subnetmask	255.255.0.0
Gateway	192.168.1.254
DNS	192.168.1.254
NTP	time1.google.com

[Save and Reboot](#)

Copyright © 2018 eCHARGE GmbH

<http://www.echarge.de/>

More detailed configuration can be done under

<http://169.254.12.53/customeredit/>

## Salia customer.json Editor (beta)

[Save and Reboot](#) [Restore to Default](#) [valid](#)

customer config

JSON

Properties

IO Configuration

JSON

Uplink

JSON

Network

JSON

OCPP

JSON

ports

## 2.4 Firmware Update

Check the current firmware version in „Home“ tab and install newest image under „Firmware“ if necessary.  
Download link:

<http://moon.echarge.de/firmware/stable/>

To update firmware via USB-Stick copy the image file to a blank USB stick and connect the stick to the salia board. Wait until the board is rebooted.

*<TODO>: USB config stuff*

**EV(s) must not be connected while updating firmware !**

## 3. Remote access

### 3.1 REST API

All states and values can be accessed via weblink: <http://169.254.12.53/api/>

Specific values (e. g. meter values) can be accessed: <http://169.254.12.53/api/secc/port0/metering/power>

The returned data is in JSON format.

JSON	<b>Rohdaten</b>	Kopfzeilen
Speichern	Kopieren	Einheitlich formatieren
<pre>{   "meter": {     "serialnumber": "18010137",     "type": "klefr",     "available": "1",     "power": {       "active": {         "ac": {           "l1": {             "actual": "0",             "l2": {               "actual": "0",               "l3": {                 "actual": "0"               }             }           },           "active_total": {             "actual": "0"           },           "current": {             "ac": {               "l1": {                 "actual": "0",                 "l2": {                   "actual": "0",                   "l3": {                     "actual": "0"                   }                 }               },               "energy": {                 "active_total": {                   "actual": "5019420",                   "active_export": {                     "actual": "250",                     "active_import": {                       "actual": "5019420"                     }                   }                 }               }             }           }         }       }     }   } }</pre>		

Values can be changed through HTTP POST.

writeable topics	value(s)	description
salia/chargemode	eco / power / manual	set charging mode
grid_current_limit	0, 6 - 32	set charging current (A) (0 = stop charging)
salia/max_amp	6 - 32	set max current (A)
salia/min_amp	6 - 32	set min current (A)
salia/heartbeat	<anything>	refresh heartbeat
salia/datetime	<timestamp>	set date/time
salia/importrfidfile	url	import rfid-tag-list from another salia module (json-format) (existing tags will be overwritten !)
salia/rfidallow	<Transponder-ID>	set a UID to allowed state
salia/rfidreject	<Transponder-ID>	set a UID to rejected state
salia/rfiddelete	<Transponder-ID>	delete an existing UID

Examples (see chapter use cases)

## 3.2 MQTT

<TODO>

Example:

<https://github.com/bluerhinos/phpMQTT>

...

## 3.3 RFID File Format

To import Transponder Tags via weblink, the file must be in JSON Format.

Example File:

```
{
  "AA4A6910" : { "name" : "John Smith", "state" : 1 },
  "043B89B2B31F80" : { "name" : "Testuser 2", "state" : 1 },
  "B614C32E" : { "name" : "Testuser 3", "state" : 1 }
}
```

(see example command `salia/importrfidfile`)









## 4. Use cases

### 4.1 Wallbox in manual mode (controlled by external controller)

Activate Heartbeat in „configuration“ tab.

**System configuration**

Global options	
Wallbox type	<input checked="" type="radio"/> Cable  <input type="radio"/> Socket 
Timezone	Europe/Berlin 
Location/Name	eCHARGE Eingang 
Auth. Mode	Free charging  
Min./max. current	6 - 32 A
External control	<input checked="" type="checkbox"/> Enable Heartbeat
aWATTar	<input type="checkbox"/> Enable API

Set manual mode:

```
curl -X PUT -d '{"salia/chargemode":"manual"}' http://169.254.12.53/api/secc
```

Set charging current to 10 A:

```
curl -X PUT -d '{"grid_current_limit":"10"}' http://169.254.12.53/api/secc
```

Send heartbeat (< 60 sec interval):

```
curl -X PUT -d '{"salia/heartbeat":"alive"}' http://169.254.12.53/api/secc
```

Stop charging:

```
curl -X PUT -d '{"grid_current_limit":"0"}' http://169.254.12.53/api/secc
```

Import RFID-Tag-List from another salia module:

```
curl -X PUT -d '{"salia/importrfidfile":"http://169.254.12.54/rfidtags.json"}' http://169.254.12.53/api/secc
```