

How to Install and Reproduce TVMFuzz

1 TVMFUZZ

To release reviewers from laborious tasks of building experimental environments, we have created a docker image in which TVMfuzz, TVM0.7 and TVM0.8 are all deployed and pushed it to docker hub.

You can download the image and reproduce our experiments about TVMfuzz in the following steps:

1) Input the following commands:

```
1 docker pull mhypony/tvmfuzz:latest
2 docker run -it mhypony/tvmfuzz:latest /bin/bash
```

2) Now you are in our docker container, to eliminate unexpected situations that may corrupt our experiment, you should input the following two commands:

```
1 source /etc/profile
2 source activate
```

3) Now go to the folder called **DLCstudy** and run the program by the commands.

```
1 python run.py
```

4) Finally, you can check the generated program (**program.py**) in the folder named **byproduct**.

If you want to compare execution message given by two TVM branches, you can follow the steps below:

1) Run 'program.py' in '/DLCstudy/byproduct' under the default tvm version, 0.7.

2) Change the default tvm version specified in '/etc/profile' by replace 'export TVM_HOME=/tvm0.7' to 'export TVM_HOME=/tvm0.8' and type the following commands:

```
1 source /etc/profile
2 source activate
```

3) Run 'program.py' in '/DLCstudy/byproduct' under the current default tvm version, 0.8 and compare two execution messages.

To make it more clear, the program synthesized by TVMfuzz is not guaranteed to be logically correct. The major purpose of the synthesized program is to find the different behaviors among different versions of TVM. Thus, TVMfuzz may generate a logically incorrect program and expect the consistent warning messages given by several TVM branches. For instance, TVMfuzz intentionally requires the shapes before and after 'reshape' operation are inconsistent and expect consistency among warning messages from different branches.