

```

1 function fe2d_r_fast ( alpha, beta, gamma, delta, T, delt, u0f, v0f, k1, k2 )
2 %*****80
3 %
4 %% FE2D_R_FAST applies Scheme 2 with Kinetics 1 to predator prey in a region.
5 %
6 % Discussion:
7 %
8 % FE2D_R_FAST is a "fast" version of FE2D_R.
9 %
10 % FE2D_R is a finite element Matlab code for Scheme 2 applied
11 % to the predator-prey system with Kinetics 1 solved over a region
12 % which has been triangulated. The geometry and grid are read from
13 % user-supplied files 't_triang.dat' and 'p_coord.dat' respectively.
14 %
15 % Robin boundary conditions are applied.
16 %
17 % This function has 10 input parameters. All, some, or none of them may
18 % be supplied as command line arguments or as functional parameters.
19 % Parameters not supplied through the argument list will be prompted for.
20 %
21 % The parameters ALPHA, BETA, GAMMA and DELTA appear in the predator-prey
22 % equations as follows:
23 %
24 %      dUdT =          nabla U +          U*V/(U+ALPHA) + U*(1-U)
25 %      dVdT = delta * nabla V + BETA*U*V/(U+ALPHA) - GAMMA * V
26 %
27 % Licensing:
28 %
29 % Copyright (C) 2014 Marcus R. Garvie.
30 % See 'mycopyright.txt' for details.
31 %
32 % Modified:
33 %
34 % 29 April 2014
35 %
36 % Author:
37 %
38 % Marcus R. Garvie and John Burkardt.
39 %
40 % Reference:
41 %
42 % Marcus R Garvie, John Burkardt, Jeff Morgan,
43 % Simple Finite Element Methods for Approximating Predator-Prey Dynamics
44 % in Two Dimensions using MATLAB,
45 % Submitted to Bulletin of Mathematical Biology, 2014.
46 %
47 % Parameters:
48 %
49 % Input, real ALPHA, a parameter in the predator prey equations.
50 % 0 < ALPHA.
51 %
52 % Input, real BETA, a parameter in the predator prey equations.
53 % 0 < BETA.
54 %
55 % Input, real GAMMA, a parameter in the predator prey equations.

```

```

56 %      0 < GAMMA.
57 %
58 %      Input, real DELTA, a parameter in the predator prey equations.
59 %      0 < DELTA.
60 %
61 %      Input, real T, the maximum time.
62 %      0 < T.
63 %
64 %      Input, real DELT, the time step to use in integrating from 0 to T.
65 %      0 < DELT.
66 %
67 %      Input, string U0F or function pointer @U0F, a function for the initial
68 %      condition of U(X,Y).
69 %
70 %      Input, string V0F or function pointer @V0F, a function for the initial
71 %      condition of V(X,Y).
72 %
73 %      Input, real K1, the coefficient for the Robin boundary condition
74 %      to be applied to U:  $dU/dn = k1 * U$ .
75 %
76 %      Input, real K2, the coefficient for the Robin boundary condition
77 %      to be applied to V:  $dV/dn = k2 * V$ .
78 %
79 %*****80
80 % Enter data for mesh geometry.
81 %*****80
82 %
83 % Read in 'p(2,n)', the 'n' coordinates of the nodes.
84 %
85 load p_coord.dat -ascii
86 p = ( p_coord )';
87 %
88 % Read in 't(3,no_elems)', the list of nodes for 'no_elems' elements.
89 %
90 load t_triang.dat -ascii
91 t = ( round ( t_triang ) )';
92 %
93 % Construct the connectivity for the nodes on Gamma.
94 %
95 edges = boundedges ( p',t' );
96 %
97 % E = number of edges on Gamma.
98 %
99 [ e, ~ ] = size ( edges );
100 %
101 % N = degrees of freedom per variable.
102 %
103 [ ~, n ] = size ( p );
104 %
105 % NO_ELEMS = number of elements.
106 %
107 [ ~, no_elems ] = size ( t );
108 %
109 % Extract vector of 'x' and 'y' values.
110 %
111 x = p(1,:);
112 y = p(2,:);

```

```

113 %*****80
114 % Enter data for model.
115 %*****80
116 if ( nargin < 1 )
117     alpha = input ( 'Enter parameter alpha:  ' );
118 elseif ( ischar ( alpha ) )
119     alpha = str2num ( alpha );
120 end
121 if ( nargin < 2 )
122     beta = input ( 'Enter parameter beta:  ' );
123 elseif ( ischar ( beta ) )
124     beta = str2num ( beta );
125 end
126 if ( nargin < 3 )
127     gamma = input ( 'Enter parameter gamma:  ' );
128 elseif ( ischar ( gamma ) )
129     gamma = str2num ( gamma );
130 end
131 if ( nargin < 4 )
132     delta = input ( 'Enter parameter delta:  ' );
133 elseif ( ischar ( delta ) )
134     delta = str2num ( delta );
135 end
136 if ( nargin < 5 )
137     T = input ( 'Enter maximum time T:  ' );
138 elseif ( ischar ( T ) )
139     T = str2num ( T );
140 end
141 if ( nargin < 6 )
142     delt = input ( 'Enter time-step delt:  ' );
143 elseif ( ischar ( delt ) )
144     delt = str2num ( delt );
145 end
146 fprintf ( 1, ' Using ALPHA = %g\n', alpha );
147 fprintf ( 1, ' Using BETA = %g\n', beta );
148 fprintf ( 1, ' Using GAMMA = %g\n', gamma );
149 fprintf ( 1, ' Using DELTA = %g\n', delta );
150 fprintf ( 1, ' Using T = %g\n', T );
151 fprintf ( 1, ' Using DELT = %g\n', delt );
152 %
153 % Initial conditions.
154 %
155 if ( nargin < 7 )
156     u0_str = input ( 'Enter initial data function u0(x,y):  ', 's' );
157     u0f = @(x,y) eval ( u0_str );
158 elseif ( ischar ( u0f ) )
159     u0_str = u0f;
160     u0f = @(x,y) eval ( u0_str );
161 end
162 u = ( arrayfun ( u0f, x, y ) )';
163 if ( nargin < 8 )
164     v0_str = input ( 'Enter initial data function v0(x,y):  ', 's' );
165     v0f = @(x,y) eval ( v0_str );
166 elseif ( ischar ( v0f ) )
167     v0_str = v0f;
168     v0f = @(x,y) eval ( v0_str );
169 end

```

```

170 v = ( arrayfun ( v0f, x, y ) )';
171 %
172 % Boundary conditions.
173 %
174 if ( nargin < 9 )
175     k1 = input('Enter the parameter k1 in the Robin b.c. for u ');
176 elseif ( ischar ( k1 ) )
177     k1 = str2num ( k1 );
178 end
179 if ( nargin < 10 )
180     k2 = input('Enter the parameter k2 in the Robin b.c. for v ');
181 elseif ( ischar ( k2 ) )
182     k2 = str2num ( k2 );
183 end
184 %
185 % N = number of time steps.
186 %
187 N = round ( T / delt );
188 fprintf ( 1, ' Taking N = %d time steps\n', N );
189 %*****80
190 % Assembly.
191 %*****80
192 m_hat = zeros ( n, 1 );
193 K = sparse ( n, n );
194 for elem = 1 : no_elems
195 %
196 % Identify nodes ni, nj and nk in element 'elem'.
197 %
198     ni = t(1,elem);
199     nj = t(2,elem);
200     nk = t(3,elem);
201 %
202 % Identify coordinates of nodes ni, nj and nk.
203 %
204     xi = p(1,ni);
205     xj = p(1,nj);
206     xk = p(1,nk);
207     yi = p(2,ni);
208     yj = p(2,nj);
209     yk = p(2,nk);
210 %
211 % Calculate the area of element 'elem'.
212 %
213     triangle_area = abs(xj*yk-xk*yj-xi*yk+xk*yi+xi*yj-xj*yi)/2;
214 %
215 % Calculate some quantities needed to construct elements in K.
216 %
217     h1 = (xi-xj)*(yk-yj)-(xk-xj)*(yi-yj);
218     h2 = (xj-xk)*(yi-yk)-(xi-xk)*(yj-yk);
219     h3 = (xk-xi)*(yj-yi)-(xj-xi)*(yk-yi);
220     s1 = (yj-yi)*(yk-yj)+(xi-xj)*(xj-xk);
221     s2 = (yj-yi)*(yi-yk)+(xi-xj)*(xk-xi);
222     s3 = (yk-yj)*(yi-yk)+(xj-xk)*(xk-xi);
223     t1 = (yj-yi)^2+(xi-xj)^2;
224     t2 = (yk-yj)^2+(xj-xk)^2;
225     t3 = (yi-yk)^2+(xk-xi)^2;
226 %

```

```

227 % Calculate local contributions to m_hat.
228 %
229     m_hat_i = triangle_area/3;
230     m_hat_j = m_hat_i;
231     m_hat_k = m_hat_i;
232 %
233 % Calculate local contributions to K.
234 %
235     K_ki = triangle_area*s1/(h3*h1);
236     K_ik = K_ki;
237     K_kj = triangle_area*s2/(h3*h2);
238     K_jk = K_kj;
239     K_kk = triangle_area*t1/(h3^2);
240     K_ij = triangle_area*s3/(h1*h2);
241     K_ji = K_ij;
242     K_ii = triangle_area*t2/(h1^2);
243     K_jj = triangle_area*t3/(h2^2);
244 %
245 % Add contributions to vector m_hat.
246 %
247     m_hat(nk)=m_hat(nk)+m_hat_k;
248     m_hat(nj)=m_hat(nj)+m_hat_j;
249     m_hat(ni)=m_hat(ni)+m_hat_i;
250 %
251 % Add contributions to K.
252 %
253     K=K+sparse(nk,ni,K_ki,n,n);
254     K=K+sparse(ni,nk,K_ik,n,n);
255     K=K+sparse(nk,nj,K_kj,n,n);
256     K=K+sparse(nj,nk,K_jk,n,n);
257     K=K+sparse(nk,nk,K_kk,n,n);
258     K=K+sparse(ni,nj,K_ij,n,n);
259     K=K+sparse(nj,ni,K_ji,n,n);
260     K=K+sparse(ni,ni,K_ii,n,n);
261     K=K+sparse(nj,nj,K_jj,n,n);
262 end
263 %
264 % Construct matrix L.
265 %
266     ivec = 1 : n;
267     IM_hat = sparse(ivec,ivec,1./m_hat,n,n);
268     L = delt * IM_hat * K;
269 %
270 % Construct matrices B1 and B2.
271 %
272     B1 = sparse(1:n,1:n,1,n,n) + L;
273     B2 = sparse(1:n,1:n,1,n,n) + delta * L;
274 %
275 % Do the incomplete LU factorization of B1 and B2.
276 %
277     [ LB1, UB1 ] = ilu ( B1, struct('type','ilutp','droptol',1e-5) );
278     [ LB2, UB2 ] = ilu ( B2, struct('type','ilutp','droptol',1e-5) );
279 %*****80
280 % Time-stepping.
281 %*****80
282     for nt = 1 : N
283 %

```

```

284 % Evaluate modified functional response.
285 %
286     hhat = u ./ ( alpha + abs ( u ) );
287 %
288 % Update right-hand-side of linear system.
289 %
290     F = u - u .* abs ( u ) - v .* hhat;
291     G = beta * v .* hhat - gamma * v;
292     rhs_u = u + delt * F;
293     rhs_v = v + delt * G;
294 %
295 % Impose Robin boundary conditions on Gamma.
296 %
297     for i = 1 : e
298         node1 = edges(i,1);
299         node2 = edges(i,2);
300         x1 = p(1,node1);
301         y1 = p(2,node1);
302         x2 = p(1,node2);
303         y2 = p(2,node2);
304         im_hat1 = 1/m_hat(node1);
305         im_hat2 = 1/m_hat(node2);
306         gamma12 = sqrt((x1-x2)^2 + (y1-y2)^2);
307         rhs_u(node1) = rhs_u(node1) + delt*k1*u(node1)*im_hat1*gamma12/2;
308         rhs_u(node2) = rhs_u(node2) + delt*k1*u(node2)*im_hat2*gamma12/2;
309         rhs_v(node1) = rhs_v(node1) + delt*k2*v(node1)*im_hat1*gamma12/2;
310         rhs_v(node2) = rhs_v(node2) + delt*k2*v(node2)*im_hat2*gamma12/2;
311     end
312 %
313 % Solve for u and v using GMRES.
314 %
315     [u,flagu,relresu,iteru] = gmres ( B1,rhs_u,[],1e-6,[],LB1,UB1,u );
316     if flagu ~= 0
317         flagu
318         relresu
319         iteru
320         error('GMRES did not converge')
321     end
322     [v,flagv,relresv,iterv] = gmres ( B2,rhs_v,[],1e-6,[],LB2,UB2,v );
323     if flagv ~= 0
324         flagv
325         relresv
326         iterv
327         error('GMRES did not converge')
328     end
329
330 end
331 %*****80
332 % Plot solutions.
333 %*****80
334 %
335 % Plot U;
336 %
337 figure;
338 set(gcf,'Renderer','zbuffer');
339 trisurf(t',x,y,u,'FaceColor','interp','EdgeColor','interp');
340 colorbar;

```

```
341 axis off;
342 title('u');
343 view ( 2 );
344 axis equal on tight;
345 filename = 'fe2d_r_fast_u.png';
346 print ( '-dpng', filename );
347 fprintf ( 1, ' Saved graphics file "%s"\n', filename );
348 %
349 % Plot V.
350 %
351 figure;
352 set(gcf,'Renderer','zbuffer');
353 trisurf(t',x,y,v,'FaceColor','interp','EdgeColor','interp');
354 colorbar;
355 axis off;
356 title('v');
357 view ( 2 );
358 axis equal on tight;
359 filename = 'fe2d_r_fast_v.png';
360 fprintf ( 1, ' Saved graphics file "%s"\n', filename );
361 print ( '-dpng', filename );
362 return
363 end
```