

```

1 function fe2dx_d
2 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
3 %                                     Discussion
4 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
5 % 'fe2dx_d.m'    2D finite element Matlab code for Scheme 1 applied
6 % to the predator-prey system with Kinetics 1. The nodes and elements
7 % of the unstructured grid are loaded from external files 't_triang.dat'
8 % and 'p_coord.dat' respectively.
9 %
10 % Boundary conditions:
11 %   Gamma: Dirichlet
12 %
13 % (C) 2009 Marcus R. Garvie. See 'mycopyright.txt' for details.
14 %
15 % Modified April 7, 2014
16 %
17 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
18 %                                     Enter data for mesh geometry
19 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
20 % Read in 'p(2,n)', the 'n' coordinates of the nodes
21 load p_coord.dat -ascii
22 p = (p_coord)';
23 % Read in 't(3,no_elems)', the list of nodes for 'no_elems' elements
24 load t_triang.dat -ascii
25 t = (round(t_triang))';
26 % Construct the connectivity for the nodes on Gamma
27 edges = boundedges (p',t');
28 % Identify the boundary nodes on Gamma
29 bn = unique(edges(:));
30 % Number of nodes (isn) on Gamma
31 [junk,isn]=size(bn);
32 % Degrees of freedom per variable (n)
33 [junk,n]=size(p);
34 % Number of elements (no_elems)
35 [junk,no_elems]=size(t);
36 % Extract vector of 'x' and 'y' values
37 x = p(1,:); y = p(2,:);
38 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
39 %                                     Enter data for model
40 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
41 % User inputs of parameters
42 alpha = input('Enter parameter alpha ');
43 beta = input('Enter parameter beta ');
44 gamma = input('Enter parameter gamma ');
45 delta = input('Enter parameter delta ');
46 T = input('Enter maximum time T ');
47 delt = input('Enter time-step Delta t ');
48 % User inputs of initial data
49 u0_str = input('Enter initial data function u0(x,y) ','s');
50 u0_anon = @(x,y)eval(u0_str); % create anonymous function
51 u = arrayfun(u0_anon,x,y)';
52 v0_str = input('Enter initial data function v0(x,y) ','s');
53 v0_anon = @(x,y)eval(v0_str); % create anonymous function
54 v = arrayfun(v0_anon,x,y)';
55 % Enter the boundary conditions

```

```

56 gu_str = input('Enter the Dirichlet b.c. gu(x,y,t) for u ','s');
57 gu = @(x,y,t)eval(gu_str); % create anonymous function
58 gv_str = input('Enter the Dirichlet b.c. gv(x,y,t) for v ','s');
59 gv = @(x,y,t)eval(gv_str); % create anonymous function
60 % Calculate and assign some constants
61 N=round(T/delt);
62 % Degrees of freedom per variable (n)
63 [junk,n]=size(p);
64 % Number of elements (no_elems)
65 [junk,no_elems]=size(t);
66 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
67 %                                     Assembly
68 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
69 m_hat=zeros(n,1);
70 K=sparse(n,n);
71 for elem = 1:no_elems
72     % Identify nodes ni, nj and nk in element 'elem'
73     ni = t(1,elem);
74     nj = t(2,elem);
75     nk = t(3,elem);
76     % Identify coordinates of nodes ni, nj and nk
77     xi = p(1,ni);
78     xj = p(1,nj);
79     xk = p(1,nk);
80     yi = p(2,ni);
81     yj = p(2,nj);
82     yk = p(2,nk);
83     % Calculate the area of element 'elem'
84     triangle_area = abs(xj*yk-xk*yj-xi*yk+xk*yi+xi*yj-xj*yi)/2;
85     % Calculate some quantities needed to construct elements in K
86     h1 = (xi-xj)*(yk-yj)-(xk-xj)*(yi-yj);
87     h2 = (xj-xk)*(yi-yk)-(xi-xk)*(yj-yk);
88     h3 = (xk-xi)*(yj-yi)-(xj-xi)*(yk-yi);
89     s1 = (yj-yi)*(yk-yj)+(xi-xj)*(xj-xk);
90     s2 = (yj-yi)*(yi-yk)+(xi-xj)*(xk-xi);
91     s3 = (yk-yj)*(yi-yk)+(xj-xk)*(xk-xi);
92     t1 = (yj-yi)^2+(xi-xj)^2; % g* changed to t*
93     t2 = (yk-yj)^2+(xj-xk)^2;
94     t3 = (yi-yk)^2+(xk-xi)^2;
95     % Calculate local contributions to m_hat
96     m_hat_i = triangle_area/3;
97     m_hat_j = m_hat_i;
98     m_hat_k = m_hat_i;
99     % calculate local contributions to K
100     K_ki = triangle_area*s1/(h3*h1);
101     K_ik = K_ki;
102     K_kj = triangle_area*s2/(h3*h2);
103     K_jk = K_kj;
104     K_kk = triangle_area*t1/(h3^2);
105     K_ij = triangle_area*s3/(h1*h2);
106     K_ji = K_ij;
107     K_ii = triangle_area*t2/(h1^2);
108     K_jj = triangle_area*t3/(h2^2);
109     % Add contributions to vector m_hat
110     m_hat(nk)=m_hat(nk)+m_hat_k;
111     m_hat(nj)=m_hat(nj)+m_hat_j;
112     m_hat(ni)=m_hat(ni)+m_hat_i;

```

[illegible]

```
170 figure;
171 set(gcf,'Renderer','zbuffer');
172 trisurf(t',x,y,u,'FaceColor','interp','EdgeColor','interp');
173 colorbar;axis off;title('u');
174 view ( 2 );
175 axis equal on tight;
176 % Plot solution for v
177 figure;
178 set(gcf,'Renderer','zbuffer');
179 trisurf(t',x,y,v,'FaceColor','interp','EdgeColor','interp');
180 colorbar;axis off;title('v');
181 view ( 2 );
182 axis equal on tight;
```
