

Format specification for the SMET Weather Station Meteorological Data Format version 1.1

Mathias Bavay

November 28, 2017

Abstract

The goal of this data format is to ease the exchange of meteorological point measurements by providing both the data and the metadata in an easy to interpret and to manipulate format. Data manipulations should be possible manually using a standard text editor or using some tools (shell scripting, awk, perl, as well as spreadsheets, R, as well as standard programming languages). The format is versioned, which means that format updates could break backward compatibility if necessary.

Compared to specification 1.0, when using a unit offset/multiplier, the multiplier is now applied *before* the offset so that it is possible to easily force a whole column to nodata.

1 Requirements

- it should contain both data and metadata
- it should be "self documented" (not regarding the format, but regarding the data, ie we are not talking about schema!)
- it should contain an arbitrary number of meteo parameters, for an arbitrary number of time steps
- it should support any kind of timesteps (ie: no fixed sampling rate)
- it should be easy to parse with common languages and tools (ie: fortran, c, c++, java, awk, perl, bash)
- it should be easy to preview with common tools (ie: no preprocessing needed even if losing a few timesteps/capability). Common tools include R, gnuplot, Excel, Matlab
- it should be possible to format it in a user friendly, eyes-friendly way (read: columns alignment)
- it should be extensible
- it should be useful for a wide range of applications

2 File structure

The file is structured in three sections: a signature line as the very first line, followed by a header, followed by the data. Lines are [CR] or [CR][LF] or [LF] terminated. Comments are supported, starting with a ”#” or a ”;” character and extending to the end of the line. A comment can follow values on a line. Empty lines can be found anywhere in the file (in the header as well as in the data).

2.1 Signature

The signature line is used to identify the file type, the file format specification version and the format type (ascii or binary). This signature has a fixed format in order to be easy to parse and the parser can reject any file that does not follow this signature or whose specification version does not match. However, the parsers are strongly encouraged to support past specifications and to try parsing more recent versions. The signature is formatted as follow:

```
{file identifier} {specification version} {file type}
```

with:

- file identifier: fixed string ”SMET”
- specification version: decimal number
- file type: string, either ”ASCII” or ”BINARY”
- all fields separated by one and only one space

Example:

```
SMET 0.95 ASCII
```

2.2 Header section

The header section contains all the metadata. It starts by a section marker, that is the following fixed string, alone on a line, capitalized:

```
[HEADER]
```

Then, the header section purely consists of key-value pairs. Some keys are mandatory while other keys are optional. The general format for a key-value pair is the following:

```
{key} = {value}
```

with:

- key: any string of alphanumeric characters as well as ”-.:.”, US-ASCII encoded
- value: any string of character, UTF-8 encoded

- the delimiter¹ can be any mixture and any number of spaces and tabs (at least one)

The following keys are mandatory:

- station_id: identifier for the station, any string
- location information (see below)
- nodata: nodata value that is used in the data section, decimal number
- fields: string of spaces/tabs delimited field types.

The location information must be at least one of the following keys:

- latitude: decimal latitude, decimal number
- longitude: decimal longitude, decimal number
- altitude: altitude above sea level, in meters, decimal number

and/or

- easting: easting coordinate in a cartesian grid, decimal number
- northing: northing coordinate in a cartesian grid, decimal number
- altitude: altitude above sea level, in meters, decimal number
- epsg: epsg coordinate system code, integer number

If both are specified, they must match to within +/-5m the same location. Whenever possible, it is recommended to provide both, since depending on the application one or the other one is the most convenient. The location information can be written in each data line (adding the necessary columns) in case of a mobile station. In any case, the whole location data set must be either in the header or in the data section, with the exception of the epsg code always being in the header. Conversions between latitude/longitude and cartesian coordinate systems can be made using the Proj4 (or libproj4) software available at <http://trac.osgeo.org/proj/>².

The following are optional:

- station_name: human readable name for the station, any string
- tz: timezone of the measurements, decimal number positive going east. If not provided, utc is assumed
- creation: timestamp of the file's creation date (ISO 8601 Combined date and time formatted)
- source: string describing the origin of the file

¹ie: in the given example, the spaces between the key and the "=" sign as well as between the "=" sign and the value

²The conversion string is built similarly as what follow: cs2cs +init=epsg:{epsg_code} +to +proj=latlong +datum=wgs84 +ellps=wgs84

- **units_offset**: a vector of decimal numbers to add to each value of the matching column in order to get back to MKSA
- **units_multiplier**: a vector of decimal numbers to multiply each value of the matching column (*before* potential offset addition) in order to get back to MKSA
- **comment**: a free string to write any comment

The field types are measurement parameter identifier chosen from the following list:

P Air pressure, in Pa

TA Temperature Air, in Kelvin

TSS Temperature Snow Surface, in Kelvin

TSG Temperature Surface Ground, in Kelvin

RH Relative Humidity, between 0 and 1

VW_MAX Maximum wind velocity, in m/s

VW Velocity Wind, in m/s

DW Direction Wind, in degrees, clockwise and north being zero degrees

ISWR Incoming Short Wave Radiation, in W/m^2

OSWR Reflected Short Wave Radiation, in W/m^2

ILWR Incoming Long Wave Radiation, in W/m^2

OLWR Outgoing Long Wave Radiation, in W/m^2

PINT Precipitation Intensity, in mm/h, as an average over the timestep

PSUM Precipitation accumulation, in mm, summed over the last timestep

HS Height Snow, in m

timestamp ISO 8601 Combined date and time formatted

julian as the decimal number of days and fractions of a day since January 1, 4713 BC Greenwich noon, Julian proleptic calendar³. If both timestamps and julian are present, they must be within less than 1 second of each other.

Unrecognized/unsupported fields for any given application should be silently skipped.

³Please keep in mind that year zero does not exist and that by starting at noon, it makes a half-day shift compared to usual meteorological time bases

2.3 Data section

The data section contains the data and starts with a section marker, that is the following fixed string, alone on a line, capitalized:

```
[DATA]
```

Each data point occupies one line and the fields are delimited by any mixture and number of spaces and tabs (at least one). All units must be as specified above, that is MKSA with a few case using multipliers (precipitation in mm/h). It is also possible to use of the above mentionned multipliers/offsets, but in such a case they must be specified. The data is sorted by ascendant temporal order (the use of a timestamp as the first field makes an alphabetic ascending order equivalent to ascending temporal order).

3 Format variations

The file can be gzipped (as a whole). In such a case, only the gzip signature will be visible and the file will either need to be manually gunzipped before reading or read using libgzip (then giving access to the specific WS MDF signature). A binary version of the format is also available, the only difference with the ASCII version being that the data section (excluding the section marker) is coded as 32 bits IEEE754 single precision binary floating-point format. In such a case, no timestamp can be used, instead a julian date can be used (and must be coded as 64 bits IEEE754 double precision). Each data "line" must be terminated by a carriage return ('`\n`' character).

4 Example file

```
SMET 0.9 ASCII
[HEADER]
station_id = test_station
latitude   = 46.5
longitude  = 9.8
altitude   = 1500
nodata     = -999
tz         = +01
fields     = timestamp TA RH VW ISWR
units_offset = 0 273.15 0 0 0
units_multiplier = 1 1 0.01 1 1
[DATA]
2010-06-22T12:00:00    2.0  52  1.2  320.
2010-06-22T13:00:00    3.0  60  2.4  340.
2010-06-22T14:00:00    2.8  56  2.0  330.
```