

HEADER

the python package and function in my lib to upload and constants

In []:

```
import pandas as pd
import numpy as np
import networkx as nx
from lib import ReactionEnthalpyCalculation, FromNetworkDataFrameToNetworkClass

##### CONSTANT #####
ph_list = ['e-', 'CRP', 'CR', 'Photon']
nan = ['NaN', 'nan', np.nan, ' ', '']
FROMHETOKJMOL = 2625.5002
FROMKTOKJMOL = 0.00831441
#####
```

PARAMETERS THAT MUST BE DEFINED FOR THE CLEANING PROCEDURE

The path_to_network must be in a different folder than the original one, in order to save the information in a work directory and to not override the info.

- path_to_molecules_database --> path to the molecules database
- path_to_network --> path to the network to be clean
- threshold_endothermicity_kJmol --> threshold to determined the reactions to be deleted for endothermicity (in kJ/mol)

In []:

```
path_to_molecules_database = '/Users/tinaccil/Documents/GitHub/GreToBaPe_Cleaning/tmp_ne
path_to_network = '/Users/tinaccil/Documents/GitHub/GreToBaPe_Cleaning/tmp_ne
threshold_endothermicity_kJmol = 10
```

Reading the network and print the species that are not present in the Database Be aware that in many network, the same species is reported with different name. Please control, in the database is reported the number of atoms per species.

In []:

```
with open(path_to_molecules_database,"r") as data:
    df_info_mol = pd.read_csv(data, delimiter = '\t')
#with open(path_to_network,"r") as data:
#    df_net = pd.read_csv(data, delimiter = '|t')
df_net = FromNetworkKidaDATtoCSV(path_to_network, save=False)
df_net_tmp = df_net.copy()
df_mol_new = ExtractMolFromNetwork(df_net)
df_info_mol['In_Network'] = df_info_mol['species'].isin(df_mol_new['species'])
df_mol_new['In_database'] = df_mol_new['species'].isin(df_info_mol['species'])
df_mol_new = df_mol_new[(~df_mol_new['species'].isin(nan)) | (~df_mol_new['sp
df_info_mol = df_info_mol[df_info_mol['In_Network'] == True]
print("Species not present in Database:")
with pd.option_context('display.max_rows', None, 'display.max_columns', None)
    display(df_mol_new[(df_mol_new['In_database']==False) & (~ df_mol_new['sp
del df_mol_new
```

ENDOTHERMICITY CALCULATION

it will generate a `_endo.dat` file with all the reactions addresses as endothermic (i.e. above the threshold_endothermicity_kJmol)

In []:

```
net = FromNetworkDataFrameToNetworkClassList(df_net_tmp)
df_info_mol['Energy'].astype(float)
df_info_mol['ZPE'].astype(float)
df_info_mol['enthalpy'] = df_info_mol['Energy'] + df_info_mol['ZPE']
df_net_tmp['enthalpy'] = np.array([ReactionEnthalpyCalculation(net, df_info_mol[i]) for i in df_info_mol.index])
df_net_tmp['enthalpy'] = df_net_tmp['enthalpy'] * FROMHETOKJMOL
print('tot reaction with enthalpy data: ' + str(df_net_tmp[df_net_tmp['enthalpy'].notnull()]))
#with open("/Users/tinaccil/Documents/GitHub/GreToBaPe_Cleaning/tmp_network_to_kida.dat", "w") as output:
#    output.write(df_net_tmp.to_csv(sep="\t", index=False))
tmp_endo = df_net_tmp[df_net_tmp['enthalpy'].notnull()].copy()
print('tot reaction endothermic: ' + str(tmp_endo[tmp_endo['enthalpy'] > threshold_endothermicity_kJmol]))
print('tot reaction endothermic not formula 3: ' + str(tmp_endo[(tmp_endo['enthalpy'] > threshold_endothermicity_kJmol) & (tmp_endo['enthalpy'] < threshold_endothermicity_kJmol)])
# print('tot reaction endothermic formula 3 with dH/C > ' + str(epsilon) + ':')
print('tot reaction endothermic formula 3 with dH-C > ' + str(threshold_endothermicity_kJmol))
print('tot reaction endothermic formula 3 barrierless: ' + str(tmp_endo[(tmp_endo['enthalpy'] > threshold_endothermicity_kJmol) & (tmp_endo['enthalpy'] < threshold_endothermicity_kJmol)])
tmp_endo = tmp_endo[((tmp_endo['enthalpy'] > 0) & (tmp_endo['enthalpy'] < threshold_endothermicity_kJmol))]
#tmp_endo = tmp_endo[((tmp_endo['enthalpy'] > threshold_endothermicity_kJmol)]
tmp_endo['C_kjmol'] = tmp_endo['C']*FROMKTOKJMOL
tmp_endo['enthalpy-C_kjmol'] = tmp_endo['enthalpy'] - (tmp_endo['C'])*FROMKTOKJMOL
print('tot reaction to be deleted: ' + str(tmp_endo.shape[0]))
with pd.option_context('display.max_rows', None, 'display.max_columns', None):
    display(tmp_endo)
FromNetworkCSVtoKidaDAT(tmp_endo, path_to_network[:-4] + '_endo.dat')
with open("/Users/tinaccil/Documents/GitHub/GreToBaPe_Cleaning/tmp_network_to_kida.dat", "w") as output:
    output.write(tmp_endo.to_csv(sep="\t", index=False))
```

Convert pandas reaction network dataframe to graph reaction network with species and reaction as different type of nodes

In []:

```
net_g = nx.DiGraph()
mol_vec = df_info_mol['species'].to_numpy()
mol_ene = (df_info_mol['Energy'] + df_info_mol['ZPE']).to_numpy()
net_id = df_net_tmp['Number'].to_numpy()
net_rec = df_net_tmp['enthalpy'].to_numpy()
#create nodes and add attribute
for i,mol in enumerate(mol_vec):
    net_g.add_node(mol)
    tmp_attr = {'type': 'species', 'energy': mol_ene[i]}
    net_g.nodes[mol].update(tmp_attr.copy())
for i,mol in enumerate(ph_list):
    net_g.add_node(mol)
    tmp_attr = {'type': 'species', 'energy': np.nan}
    net_g.nodes[mol].update(tmp_attr.copy())
#create edges and attribute
for i,rec in enumerate(net):
    net_g.add_node(net_id[i])
    tmp_attr = {'type': 'reaction', 'enthalpy': net_rec[i]}
    net_g.nodes[net_id[i]].update(tmp_attr.copy())
    for j,item_j in enumerate(set(net[i].reactants)):
        if item_j not in nan:
            net_g.add_edge(item_j,net_id[i])
    for k,item_k in enumerate(set(net[i].products)):
        if item_k not in nan:
            net_g.add_edge(net_id[i],item_k)
```

DELETED ALL THE ENDOOTHERMIC REACTIONS AND CONSEQUENT DOMINO EFFECT

it will generate a `_domino_endo.dat` file with all the reactions addresses as endothermic and deleted by Domino effect

also will create the clean network `_clean.dat`