

CLEAN clinker by calcium
looping for low- CO_2 cement

CLEAN KER

8th High Temperature Solid Looping Network Cycle Meeting
Geleen, 20th of January 2020

Characterization of cement raw meal as CO_2
sorbent in an entrained flow calcium looping
 CO_2 capture system for cement plants


*Matthias Hornberger
Institute of Combustion and Power Plant Technology
University of Stuttgart*



CaL characteristics:

- Sorbent: raw meal
- Reactor type: entrained flow (EF)
- Calciner: combined oxy-fuel calciner

- ➔ Raw meal split stream required to cool kiln off gas
- ➔ Significant share of CO₂ capture by oxy-fuel calcination
- ➔ Reduced CO₂ loading of flue gas



WP4: Comparative characterization of raw meals for CaL

Main activities

- **Determination of calcination and carbonation conversion and kinetics of various raw meal qualities representative for Europe**


Main results:

- ➔ **Extrapolation of the Calcium Looping demonstration test in Vernasca to other cement plants/raw meal qualities**
- ➔ **Development of a guideline on raw meal characterization in respect to suitability for Calcium Looping applications**




Experimental setup





- **Energy supply**
 - Resistance heating
 - Natural gas combustion
- **Raw meal feeding**
 - Weight based controlled screw feeder
 - Dispersion by venturi nozzle
- **Quench of solids ($T_{\text{Gas}} < 500 \text{ }^{\circ}\text{C}$) to avoid further carbonation /calcination**



Calcination (EF):



	T_{Calc}	τ_{Solid}	Y_{CO_2}
Air	860 °C	2 ... 6 s	~ 26 vol.%
Oxy-fuel	900 °C 920 °C	2 ... 6 s	~ 90 vol.%

Carbonation (TGA):

T_{Carb}	Y_{CO_2}		
600 °C	5 vol.%	10 vol.%	20 vol.%
650 °C			
700 °C			

Chemical composition of investigated raw meals



	CaO (CaCO ₃)	SiO ₂	Al ₂ O ₃	Fe ₂ O ₃	LOI
	wt-%, wf				
RM1	41.28 (73.71)	16.73	3.56	2.33	33.08
RM1: Limestone	50.34 (89.90)	2.98	0.91	0.47	43.15
RM1: Marl	37.31 (66.63)	22.45	4.36	1.65	30.24
RM2	40.07 (71.56)	14.39	6.28	1.95	33.49




Methodology



- I. Adjustment of gas concentration for different residence times / velocities
- II. Start of raw meal dosing
- III. Collection of solid samples after/at cyclone (top of reactor)
- IV. Stop of raw meal dosing
- V. Reactor and gas filter cleaning





- Calcination Degree:



$$x_{\text{Calc}} = 1 - \frac{x_{\text{CO}_2, \text{Sample}} \cdot (1 - x_{\text{CO}_2, \text{RawMeal}})}{(1 - x_{\text{CO}_2, \text{Sample}}) \cdot x_{\text{CO}_2, \text{RawMeal}}}$$

- (Re)Carbonation Degree:

$$\tilde{x} = \frac{N_{\text{CO}_2, \text{ReCarb}}}{N_{\text{CaO, Sample}} - N_{\text{CaCO}_3, \text{Sample}}}$$


Results






- ➡ Slight increase in calcination degree with residence time
- ➡ Reduced calcination degree for oxy-fuel calcination
- ➡ Calcination degree increases with temperature for oxy-fuel calcination

- ➡ High burnability raw meal: Constant calcination degree throughout all experiments



- High amount fuel lead to hot spots at reactor bottom
- Improved calcination when fuel is fed into the reactor
➡ Heat transfer by radiation insufficient
- Increased fuel feeding leads to:
 - Increase calcination degree
 - Decreasing recarbonation degree




- TGA sorbent analysis show reduced CO₂ carrying capacities for cement raw meals
 - Belit formation binds CaO
 - Marl type raw meal show increased deactivation
- Entrained flow calcined samples show
 - RM1: slightly lower X_{CO₂}
 - RM2: significantly increased X_{CO₂}

TGA Cycles:

T_{Calc} = 860 °C | τ_{calc} = 10 min | y_{CO₂} = 0

T_{Carb} = 650 °C | τ_{Carb} = 10 min | y_{CO₂} = 10 vol.%





- **RM1: Decrease of CO₂ carrying capacity when oxy-fuel calcined**
- **RM2: Increase of CO₂ carrying capacity for initial cycles**

➔ **Sorbent deactivation depended on T_{Calc} , τ_{Calc} and p_{CO_2}**

TGA Cycles:

$T_{\text{Calc}} = 920 \text{ }^\circ\text{C}$ | $\tau_{\text{calc}} = 10 \text{ min}$ | $y_{\text{CO}_2} = 90 \text{ vol.}\%$

$T_{\text{Carb}} = 650 \text{ }^\circ\text{C}$ | $\tau_{\text{Carb}} = 10 \text{ min}$ | $y_{\text{CO}_2} = 10 \text{ vol.}\%$



- **Belite formation occurs at calcium looping conditions in the oxy-fuel calciner and will consequently deactivate the sorbent**
- **Belite formation more pronounced for marl type raw meals**
- **Hot spots during calcination lead to stronger deactivation**
- **EF calcined sorbent hold sufficient activity to run an EF calcium looping system**

- **Investigation of further raw meal qualities to achieve a broader data basis and more comprehensive understanding**

This project has received funding from the European Union's Horizon 2020 research and innovation programme under Grant Agreement n. 764816

This work is supported by the China Government (National Natural Science Foundation of China) under contract No.91434124 and No.51376105


www.cleanker.eu

XXXTwitter: @CLEANKERXXX

XXXFacebook: CLEANKER channelXXX



RM1: CO₂ uptake vs. available CaO



RM2: CO₂ uptake vs. available CaO

