

CLEAN clinker by calcium
looping for low-CO₂ cement

CLEAN^N KER

9th High Temperature
Solid Looping Cycles Network Meeting
Piacenza, 14. - 15.03.2023

Scale-up and Economics
for a Full-size Plant


*Jörg Hammerich
Marco Lindemann Lino
Kari Myöhänen*



Scale-up for a Full-size Plant

Plant with Integrated CaL Process

- 2 Strings
 - Calciner with Co₂ Preheater
 - Kiln Preheater and Carbonator
- Cyclones
- Transfer Chutes
- Sorbent Cooler
- Material Feeding/Distribution
- Gas Coolers
- ASU / CPU as Cost Drivers




Source: POLIMI



Scale-up for a Full-size Plant

Vernasca: Flow Sheet



- Extract
Calciner/Carbonator



Scale-up for a Full-size Plant

Vernasca: Plant Overview

- **CLEANER Plant Layout**
- **Raw Meal Feed: 10 t/h**
- **Standard Cement Plant: >150 t/h**



Vernasca: Calciner

- **Calciner (45 m), directly heated**
 - Shell: Mild Steel / Refractory
 - Heat Expansion joints
 - Scale-up as per gas speed
- **Oxyfuel Burner**
 - Geometrical Scale-up (more or less depending on the Fuel type)

Photo: LEAP



Vernasca: Carbonator




- Carbonator (Vernasca)
 - Length: 105 m
 - Diameter: 0,25 m (Up), 0,35 m (down)
 - Material: Stainless Steel
 - Insulation: Partially
- Carbonator (Scale-Up)
 - Shorter: approx. 65 m
 - Material: Mild Steel / Refractory / Insulation



Scale-up for a Full-size Plant

Scale-up: Carbonator

- **Shorter Pipe**
 - Effective Mixing Chamber at Material Feed
 - Acceptable capture rate already after 60 m



Source: LUT



Vernasca: Cyclones

- Cyclones
 - State of the Art
- Ductwork
 - State of the Art



Vernasca: Transfer Chutes Water-cooled Screws


- Carbonator Outlet bin
- Screw Conveyors (HX21, HX23)
 - Carbonator -> Calciner
 - Watercooled devices
 - 650 / 600 °C
 - Diameter: 0,4 m
 - Not suitable for Scale-up



Scale-up: Transfer Chutes

- **Hot Air Slide**

- Refractory covered ducting
- 10/20 degree inclination
- Ceramic Aeration floor
- Minimum Aeration for no cooling, just transportation
- Fine Jet Slots for transport efficiency



Scale-up: Transfer Chutes

- Hot Air Slide
 - Installation at Test Facility
 - 10/20 degree inclination



Scale-up for a Full-size Plant

Scale-up: Transfer Chutes

- **Hot Air Slide - Test Runs**
 - 900 °C
 - Calcined Raw Meal
 - Basic tests at ambient with Raw Meal



Scale-up for a Full-size Plant

Vernasca: Sorbent Cooler Water-cooled Screw






- **Screw Conveyor / Screw Cooler (HX24)**
 - Calciner -> Carbonator
 - 900 / 700 °C
 - Watercooled, Shaft and Shell
- **Not suitable for Scale-up**





Scale-up: Sorbent Cooler

- **Sorbent Cooler**

- Calciner -> Carbonator
- 900 / 700 °C
- Air Cooled
- Concept Variation of HAS
- Wider Slots for more air
- Cooling Air Source



one hot air slide segment
 main dimensions: (1900x1310x1000)
 weight: 1,3t
 steel: 0,46t



Scale-up for a Full-size Plant



Vernasca: Material Feeding Splash-Box

- **Splash Box**
 - Calciner
 - Raw Meal Feed



Scale-up: Material Feeding Splash-Chamber

- **Splash-Box (Vernasca, left)**
 - Scaled-down from Plant devices
 - Circulating Flow
- **Splash-Chamber**
 - Similar Flow Pattern
 - Additional Feed Points



Source: LUT


Vernasca: CO₂ Cooler

- **Gas Cooler**
 - 700 / 500 °C
 - Water Cooled
 - Concept not really suitable for Scale-up
 - Alternative Proposals
 - Under investigation



Vernasca: Oxygen-Tank

- Vernasca Installation
 - Oxygen Valve Train
 - Tank / Gasifier
- Full Scale
 - Complete ASU Plant



Conclusions:

- **Safe for Scale-Up**
 - Calciner
 - Carbonator
 - Cyclones
- **Some Challenges ahead**
 - Hot Air Slides
 - Sorbent Cooler
 - Splash-Chambers
 - Various Heat Exchangers



CLEAN clinker by calcium looping for low-CO₂ cement


CLEAN^N KER



Economic analysis



- Economic assessment based on CEMCAP methodology
- New cost functions were drawn to improve the accuracy of the Total Plant Cost estimation
- Retrofitting a 3000 t/d BAT Cement plant with CaL EF was assessed (100% coal firing)
- 2018 year basis
- Targeted cost uncertainty: $\pm 30\%$
- Estimations based on the results of validated process models



Source: CEMCAP D4.6





- Some relevant assumptions for the economic assessment:

| <i>Utilities and Consumables</i> | <i>Unit price</i> | | <i>Amount</i> | <i>Plant without CO₂ capture (Ref. Plant)</i> | <i>Plant with CO₂ capture (EF CaL)</i> |
|----------------------------------|------------------------|-------|--|--|---|
| | | | | | |
| Raw Meal | €/t _{RawMeal} | 3.125 | t _{RawMeal} /t _{clk} | 1.6 | 1.6 |
| Fuel | €/GJ _{LHV} | 2.40 | GJ _{LHV} /t _{clk} | 3.24 | 5.44 |
| Electricity | €/MWh _e | 69.30 | MWh _e /t _{clk} | 0.13 | 0.17 |

| Economic variables | Uncertainty range |
|-------------------------------------|--------------------------|
| Fuel | ± 50% |
| Electricity | ± 30% |
| CO ₂ emission allowances | 0 - 100 |
| CAPEX Carbon Capture plant | ± 30% |


- Total CaL EF Plant Cost estimation: ~175 M€; 2018 year basis (retrofitting)
- 6 components account for over 95% of the total cost (ASU; CPU; WHR; Structures; Coal grinding system; cyclones)
- The remaining 5 % include CO₂-rich and CO₂-lean gas ducts; fans; sorbent cooler; carbonator, etc.
- Calciner and fuel feeding system need to be adapted → not included






Interpretation:

- Cost of cement differential < 0 → more economic to pay CO₂ allowances
- Cost of cement differential = 0 → breakeven range
- Cost of cement differential > 0 → more economic to install EF CaL than pay CO₂ tax (without CO₂ transport and storage)



Benchmarking of EF CaL against Oxyfuel:

- No clear winner
- Case by case assessment is required



Including CO₂ transport and storage cost and CO₂ price at 100 €/t:

- CO₂ transport and storage cost > 40 €/t cement
→ more economic to pay CO₂ allowances
- CO₂ transport and storage cost in the range 25 to 40 €/t cement → evaluate case by case
- CO₂ transport and storage cost < 25 €/t cement
→ more economic to invest in CC with EF CaL

Conclusions:

- CO₂ price higher than 65 €/tCO₂ is required to make this technology interesting under the boundary conditions and respective uncertainty ranges chosen (excluding transport and storage)
- At current CO₂ prices of around 100 €/tCO₂, only an increment on cement cost allocated to CO₂ transport and storage lower than 25 €/t cement would make EF CaL economic viable.
- Strategies to decrease the ASU and CPU size shall be developed
 - optimization of the carbonation efficiency and ratio $\dot{m}_{\text{CaO}} / \dot{m}_{\text{CO}_2\text{captured}}$ is fundamental
 - synergies with other technologies shall be evaluated (e.g. water electrolyzers)
- Structures account for 15% of TPC. Depending on plant layout, it might be even higher
- An FEED project in a real plant should be performed. It is fundamental in order to have a higher certainty on CAPEX and a better understanding of the complexity associated to retrofitting a cement plant with EF CaL.



Conclusions (cont.):

- The use of “air slides” for transporting hot materials between both reactors might be a good technical option and will not have a relevant impact on TPC
- Experimental campaigns revealed that the carbonator can be 33% shorter than first envisaged. The carbonator with the new length represents only around 1% of TPC → further optimization will not have any relevant impact on the TPC
- Results are strongly dependent on the boundary conditions chosen:
 - 1) Cost of utilities (CaL is sensitive to fuel price; Oxyfuel to electricity price)
 - 2) cement plant operation conditions; ref. case scenario; capture rates; CO₂-Price)



This project has received funding from the European Union's Horizon 2020 research and innovation programme under Grant Agreement n. 764816

This work is supported by the China Government (National Natural Science Foundation of China) under contract No.91434124 and No.51376105



Disclaimer: The European Commission support for the production of this publication does not constitute endorsement of the contents which reflects the views only of the authors, and the Commission cannot be held responsible for any use which may be made of the information contained therein

